


20 Linear Surface

WG-20LDL-...-OD-W
Delivered Lumens Per Foot

		Power			
		L [3 W/ft]	M [6 W/ft]	H [10 W/ft]	RGBW [7.6 W/ft]
CCT	927	176	352	617	—
	930	192	383	670	—
	935	227	455	796	—
	940	270	540	946	—
	WD ²	135	280	405	—
	RGBW ³	—	—	—	229
UGR ⁴		26.7	29.3	31.1	—




BEAM ANGLE (0-180) = 110.3
BEAM ANGLE (90-270) = 110.4

ILLUMINANCE - 48" OD H 3500K
WG-20LDL-...-S-48-H-935-...-OD-W-...¹

Mounting Height [ft]	Illuminance [fc at max cd]	Beam Width [ft]
2	277	5.7
4	69	11.5
6	31	17.2
8	17	23
10	11	28.7
12	8	34.5
14	6	40.2
16	4	46
18	3	51.7
20	3	57.5

WG-20LDL-...-SD-W
Delivered Lumens Per Foot

		Power			
		L [3 W/ft]	M [6 W/ft]	H [10 W/ft]	RGBW [7.6 W/ft]
CCT	927	247	495	867	—
	930	270	538	942	—
	935	319	640	1119	—
	940	380	760	1330	—
	WD ²	189	394	569	—
	RGBW ³	—	—	—	322
UGR ⁴		25.3	27.9	29.7	—




BEAM ANGLE (0-180) = 80.8
BEAM ANGLE (90-270) = 103.4

ILLUMINANCE - 48" SD H 3500K
WG-20LDL-...-S-48-H-935-...-SD-W-...¹

Mounting Height [ft]	Illuminance [fc at max cd]	Beam Width [ft]
2	511	3.4
4	128	6.8
6	57	10.2
8	32	13.6
10	20	17
12	14	20.4
14	10	23.8
16	8	27.2
18	6	30.7
20	5	34.1

WG-20LDL-...-MPL-W
Delivered Lumens Per Foot

		Power			
		L [3 W/ft]	M [6 W/ft]	H [10 W/ft]	RGBW [7.6 W/ft]
CCT	927	209	418	731	—
	930	227	454	795	—
	935	270	540	944	—
	940	321	641	1122	—
	WD ²	160	332	480	—
	RGBW ³	—	—	—	272
UGR ⁴		26.3	28.9	30.7	—




BEAM ANGLE (0-180) = 73.8
BEAM ANGLE (90-270) = 85.5

ILLUMINANCE - 48" MPL H 3500K
WG-20LDL-...-S-48-H-935-...-MPL-W-...¹

Mounting Height [ft]	Illuminance [fc at max cd]	Beam Width [ft]
2	478	3
4	119	6
6	53	9
8	30	12
10	19	15
12	13	18
14	10	21
16	7	24
18	6	27
20	5	30

WG-20LDL-...-NL16-W
Delivered Lumens Per Foot

		Power			
		L [3 W/ft]	M [6 W/ft]	H [10 W/ft]	RGBW [7.6 W/ft]
CCT	927	207	414	725	—
	930	225	450	787	—
	935	267	535	936	—
	940	318	635	1112	—
	WD ²	158	329	476	—
	RGBW ³	—	—	—	269
UGR ⁴		17.8	20.3	22.1	—



BEAM ANGLE (0-180) = 10.4
BEAM ANGLE (90-270) = 75.1

ILLUMINANCE - 48" NL16 H 3500K
WG-20LDL-...-S-48-H-935-...-NL16-W-...¹

Mounting Height [ft]	Illuminance [fc at max cd]	Beam Width [ft]
2	2387	0.4
4	597	0.7
6	265	1.1
8	149	1.5
10	95	1.8
12	66	2.2
14	49	2.6
16	37	2.9
18	29	3.3
20	24	3.7


Power Multiplier				
	L [3 W/ft]	M [6 W/ft]	H [10 W/ft]	RGBW [7.6 W/ft]
9XX/RGBW	0.29	0.57	1.00	0.29
WD	0.17	0.35	0.51	—
CCT Multiplier				
	927	930	935	940
	0.77	0.84	1.00	1.19

- 1 Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.
- 2 WD lumen data at maximum output (3000K).
- 3 RGBW lumen data at maximum output with 3000K White LED.
- 4 UGR value noted is the maximum UGR (crosswise) with 935 LEDs / 48" length.

20 Linear Surface

WG-20LDL-...-LL45B-W
Delivered Lumens Per Foot

		Power			
		L [3 W/ft]	M [6 W/ft]	H [10 W/ft]	RGBW [7.6 W/ft]
CCT	927	53	107	187	—
	930	58	116	203	—
	935	69	138	241	—
	940	82	164	287	—
	WD ²	41	85	123	—
	RGBW ³	—	—	—	69
UGR ⁴		0.0	0.0	0.0	—




BEAM ANGLE (0-180) = 45.3
BEAM ANGLE (90-270) = 49.7

ILLUMINANCE - 48" LL45B H 3500K
WG-20LDL-...-S-48-H-935-...-LL45B-W-...¹

Mounting Height [ft]	Illuminance [fc at max cd]	Beam Width [ft]
2	385	1.7
4	96	3.3
6	43	5
8	24	6.7
10	15	8.4
12	11	10
14	8	11.7
16	6	13.4
18	5	15
20	4	16.7

WG-20LDL-...-LL45W-W
Delivered Lumens Per Foot

		Power			
		L [3 W/ft]	M [6 W/ft]	H [10 W/ft]	RGBW [7.6 W/ft]
CCT	927	115	229	402	—
	930	125	250	437	—
	935	148	297	519	—
	940	176	352	616	—
	WD ²	88	183	264	—
	RGBW ³	—	—	—	149
UGR ⁴		21.6	24.1	25.9	—




BEAM ANGLE (0-180) = 48.1
BEAM ANGLE (90-270) = 57.3

ILLUMINANCE - 48" LL45W H 3500K
WG-20LDL-...-S-48-H-935-...-LL45W-W-...¹

Mounting Height [ft]	Illuminance [fc at max cd]	Beam Width [ft]
2	495	1.8
4	124	3.6
6	55	5.4
8	31	7.1
10	20	8.9
12	14	10.7
14	10	12.5
16	8	14.3
18	6	16.1
20	5	17.9

WG-20LDL-...-BDO-W
Delivered Lumens Per Foot

		Power			
		L [3 W/ft]	M [6 W/ft]	H [10 W/ft]	RGBW [7.6 W/ft]
CCT	927	219	438	767	—
	930	239	477	834	—
	935	283	566	991	—
	940	336	673	1177	—
	WD ²	168	349	504	—
	RGBW ³	—	—	—	285
UGR ⁴		31.5	34	35.8	—




BEAM ANGLE (0-180) = 174.7
BEAM ANGLE (90-270) = 107.8

ILLUMINANCE - 48" BDO H 3500K
WG-20LDL-...-S-48-H-935-...-BDO-W-...¹

Mounting Height [ft]	Illuminance [fc at max cd]	Beam Width [ft]
2	181	86.3
4	45	172.5
6	20	258.8
8	11	345
10	7	431.3
12	5	517.6
14	4	603.8
16	3	690.1
18	2	776.3
20	2	862.6

WG-20LDL-...-ROD-W
Delivered Lumens Per Foot

		Power			
		L [3 W/ft]	M [6 W/ft]	H [10 W/ft]	RGBW [7.6 W/ft]
CCT	927	248	497	870	—
	930	271	540	945	—
	935	321	642	1123	—
	940	381	763	1335	—
	WD ²	190	395	571	—
	RGBW ³	—	—	—	323
UGR ⁴		30.8	33.4	35.2	—



BEAM ANGLE (0-180) = 97.2
BEAM ANGLE (90-270) = 130.1

ILLUMINANCE - 48" ROD H 3500K
WG-20LDL-...-S-48-H-935-...-ROD-W-...¹

Mounting Height [ft]	Illuminance [fc at max cd]	Beam Width [ft]
2	279	4.5
4	70	9.1
6	31	13.6
8	17	18.2
10	11	22.7
12	8	27.2
14	6	31.8
16	4	36.3
18	3	40.8
20	3	45.4

Power Multiplier				
	L [3 W/ft]	M [6 W/ft]	H [10 W/ft]	RGBW [7.6 W/ft]
9XX/RGBW	0.29	0.57	1.00	0.29
WD	0.17	0.35	0.51	—
CCT Multiplier				
	927	930	935	940
	0.77	0.84	1.00	1.19

- 1 Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.
- 2 WD lumen data at maximum output (3000K).
- 3 RGBW lumen data at maximum output with 3000K White LED.
- 4 UGR value noted is the maximum UGR (crosswise) with 935 LEDs / 48" length.