

# Aura

## PENDANT

Direct illumination with indirect glow

### Model 1520

#### Type

P Pendant

#### Size

15	15.6" (396mm)
18	18.6" (472mm)
22	22.6" (574mm)
25	25.6" (651mm)
30	30.0" (763mm)
36	36.0" (915mm)
Custom	

#### Wattage<sup>1,2</sup>

<b>15"</b>	
L	8W (1065lm)
M	16W (1980lm)
<b>18"</b>	
L	11W (1465lm)
M	22W (2725lm)
<b>22"</b>	
L	16W (2135lm)
M	32W (3965lm)
<b>25"</b>	
L	24W (3200lm)
M	48W (5945lm)
<b>30"</b>	
L	38W (5065lm)
M	76W (9410lm)
<b>36"</b>	
L	56W (7465lm)

#### Color Temp<sup>3</sup>

30	3000
35	3500
40	4000

#### Voltage

U 120/277 Volt

#### Driver<sup>4,5</sup>

RD	Remote
ID	Integral

#### Control - (RD/ID)

S	Non-dim
D010	0-10V 1%
L3DAE	Lutron Hi-lume 1% EcoSystem
L3DOE	Hi-lume Premier 0.1% EcoSystem (remote only)

#### Diffuser Bottom

SW Satin opal acrylic

#### Diffuser Top

SW Satin opal acrylic

#### Finish<sup>6</sup>

19	Painted anodized aluminum - RAL 9006 matte
21	Painted white - RAL 9010 matte
26	Painted black - RAL 9005 matte
22	Painted custom color

#### Mounting

CE Center canopy

#### Power Cable<sup>7</sup>

CC	Clear insulated cable (standard)
WC	White cable
BC	Black cable

#### Notes

- 1 Nominal lumens value specified
- 2 Linear LED board, constant voltage 24 Volt
- 3 90+ CRI standard
- 4 Remote driver for 15" and 18" sizes
- 5 Integral or remote driver for 22", 25", 30" and 36" sizes
- 6 Canopy finish matches housing
- 7 96" standard cable length

