



### Advantages

- Available in multiple lengths to accommodate exacting installations
- Multiple wattages and lumen output for maximum flexibility within any application
- Four (4) standard color temperatures from 2700K-4000K; non-standard available
- Compatible with all common dimmer and control standards such as 0-10V, 3-wire, forward phase w/ neutral, DALI and DMX. For others, please contact factory
- High efficiency design delivers more lumens per watt
- Same LED technology used throughout all Whitegoods products for color and performance consistency
- 5-year warranty

### Technical Data

■ form	linear
■ fcircuitry	parallel
■ power (W/ft)	3W, 6W, 10W
■ supply type	CV
■ operating voltage (VDC)	24
■ color rendering index Ra	90+
■ MacAdam	3 step
■ viewing angle (°)	120
■ LED (SMD) quantity (per foot)	72 (3W/6W), 80 (10W)
■ Cut increment	1.31" (3W/6W), 1.23" (10W)
■ lifetime—L70 (h)*	60,000
■ working temperature	-77°F - 104°F

\*Tested to LM80

Power (w/ft)	CCT (k)	Lum.Flux (lm/ft)	lm/watt
3	2700	341	114
3	3000	359	120
3	3500	365	122
3	4000	375	125
6	2700	685	114
6	3000	725	121
6	3500	735	123
6	4000	755	126
10	2700	1090	109
10	3000	1150	115
10	3500	1170	117
10	4000	1200	120