

## ANELLO



Housing: Circular Aluminum-profile with translucent foil. Direct light distribution. Additional indirect lighting possible for background lighting.  
Design: SATTLER



Size: L x W x H mm	Inches	LED Watt	Lumen <sup>1</sup>	Weight kg / lbs <sup>2</sup>	Item No.	LED Row 1	Dimming	LED Row 2	Finish	Power supply cable	Mounting version
<b>Sizes</b>											
Ø 1600 x 260 x 60	62.9 x 10.2 x 2.4"	240	20,383	20 / 44	<b>288.</b>	x x.	x x.	x x.	x x.	x x x.	x
Ø 2000 x 260 x 60	78.7 x 10.2 x 2.4"	300	25,150	25 / 55	<b>290.</b>	x x.	x x.	x x.	x x.	x x x.	x
Ø 2600 x 260 x 60	102.3 x 10.2 x 2.4"	380	32,306	35 / 77	<b>292.</b>	x x.	x x.	x x.	x x.	x x x.	x
<b>DIRECT LED</b> 24V		<b>Standard: Neutral-white</b>	<b>4000 K</b>		x x x.	<b>40.</b>	x x.	x x.	x x.	x x x.	x
		<b>Optional: Warm-white</b>	<b>3000 K</b>		x x x.	<b>30.</b>	x x.	x x.	x x.	x x x.	x
		<b>Extra warm-white</b>	<b>2700 K</b>		x x x.	<b>27.</b>	x x.	x x.	x x.	x x x.	x
<small>CRI &gt; 90 Mac Adam 3 SELV L80 B10 100,000 hours</small>											
<b>INDIRECT LED</b> 24V		<b>Standard: No indirect LED'S</b>			x x x.	x x.	x x.	<b>00.</b>	x x.	x x x.	x
		<b>Optional: Neutral-white</b>	<b>4000 K</b>		x x x.	x x.	x x.	<b>40.</b>	x x.	x x x.	x
		<b>Warm-white</b>	<b>3000 K</b>		x x x.	x x.	x x.	<b>30.</b>	x x.	x x x.	x
		<b>Extra warm-white</b>	<b>2700 K</b>		x x x.	x x.	x x.	<b>27.</b>	x x.	x x x.	x
		<b>RGB color control*</b>			x x x.	x x.	x x.	<b>60.</b>	x x.	x x x.	x
<small>CRI &gt; 90 Mac Adam 3 SELV L80 B10 100,000 hours</small>											
<small>Indirect light is significantly weaker than direct light output</small>											
<b>Dimming</b>		<b>Standard: 0 - 10 V</b>			x x x.	x x.		<b>51.</b>	x x.	x x x.	x
		<b>Optional: Lutron EcoSystem**</b>			x x x.	x x.		<b>91.</b>	x x.	x x x.	x
		<b>DMX</b>			x x x.	x x.		<b>31.</b>	x x.	x x x.	x
		<small>First digit indicates Dimming protocol. Second digit indicates number of rows of LED. Codes shown with 1x row of LED (Standard). For 2x rows of LED replace the second digit accordingly.</small>									
		<small>**Lutron EcoSystem driver must be ordered separately and remote mounted with mounting version A.</small>									
<b>Finish</b>											
<b>Standard:</b>		<b>12</b>	<b>10</b>	<b>11</b>	<b>30</b>	<b>32</b>	<b>33</b>				
	white, powder coated, similar to RAL 9003	black fine textured	white, similar to RAL 9010	anthracite fine textured	crocodile black	sand silver fine textured					
<b>Optional (Powder coated):</b>		<b>34</b>	<b>35</b>	<b>36</b>	<b>37</b>	<b>38</b>					
		bronze satined	gold	brass	bronze fine textured	copper					
<b>Optional (Premium):</b>		<b>22</b>	<b>27</b>								
		aluminum polished	brush-finished aluminum								
					x x x.	x x.	x x.	x x.		x x x.	x

## ANELLO



Housing: Circular Aluminum-profile with translucent foil. Direct light distribution. Additional indirect lighting possible for background lighting.  
Design: SATTLER



### Power supply cable

Standard:



**Z 70**  
Silver

Optional:




**Z 71**  
white




**Z 73**  
black

Item No.	LED	Dimming	LED	Finishes	Power supply cable	Mounting version
X X X.	X X.	X X.	X X.	X X.	---	X


### Mounting Version



4-point suspension with external power supply unit in suspended ceiling.



Up to Ø 2000 mm / 78.7" 4-point suspension with external power supply unit in separate canopy.



Up to Ø 2000 mm / 78.7" suspension through canopy.

X X X.	X X.	X X.	X X.	X X.	X X X	-
--------	------	------	------	------	-------	---

**A, B,** = Distance of external power supply unit to light fixture max. 10m / 394"

**E** = Minimum suspension height half the diameter of light fixture, maximum suspension height two times diameter of light fixture

Including steel cable suspension 5000 mm / 197" and power supply cable 5000 mm / 197"



Complete order number

**Power supply unit: (1 LED Stripe)**

Type/ Size mm / inch  
L x W x H

Included with Mounting version

Protective rating

**DE 3F** 360 / 400 / 85 mm / 14.2 x 15.7 x 3.3" **A** **IP 20**

Quantity of power supply units depends on configuration

**Canopy: (1 LED Stripe)**

Type/ Size mm / inch  
Ø cover plate / body / H

Included with Mounting version

Protective rating


**DB 500** Ø 510 / 470 mm / 20,0 x 18.5" **B, E** (up to Ø 2000 mm) **IP 20**

**Color: 12 white, similar RAL 9003, contact factory for other finishes**

Canopy mounts to 4" octagonal junction box.

Input voltage for all external power supply units and canopy is **120-277 VAC 47-63 Hz**

### Optional



### Ceiling fixation included with mounting version A

**200. 00. 00. 00. 12** (white)

Consisting of a cavity ceiling box with 80 mm / 3.1" round metal cover. Powder coated in white, fine textured. Applicable to mounting version A.

