


CIRCOLO

I-Version

Housing: Circular aluminum profile, opal acrylic diffuser on the inside
 Design: SATTLER, Patented



Size: L x W x H mm	inches	LED Watt	Lumen ¹	weight ² kg / lbs	Item No.	LED	Dimming	LED	Finishes	Power Supply cable	Total height	Mounting Version
Ø 750	29.5"	48	3,629	8 17.6	252	x x .	x x .	x x .	x x .	x x x .	x x .	x
Ø 900	35.5"	58	4,388	10 22.0	253	x x .	x x .	x x .	x x .	x x x .	x x .	x
Ø 1320	51.9"	84	6,523	20 44.0	254	x x .	x x .	x x .	x x .	x x x .	x x .	x
Ø 1600	62.9"	102	7,991	25 55.1	255	x x .	x x .	x x .	x x .	x x x .	x x .	x
Ø 1800	70.8"	114	9,027	30 66.0	256	x x .	x x .	x x .	x x .	x x x .	x x .	x
Ø 2300	90.5"	144	11,650	35 77.2	257	x x .	x x .	x x .	x x .	x x x .	x x .	x
Ø 2600	102.3"	164	13,272	40 88.0	258	x x .	x x .	x x .	x x .	x x x .	x x .	x
Ø 3500	137.8"	220	19,504	53 117.0	259	x x .	x x .	x x .	x x .	x x x .	x x .	x

LED	Standard	Optional:	Neutral-white	4000 K	x x x .	40.	x x .	x x .	x x .	x x x .	x x x .	x
24V			Cold-white	5000 K	x x x .	50.	x x .	x x .	x x .	x x x .	x x x .	x
			Warm-white	3000 K	x x x .	30.	x x .	x x .	x x .	x x x .	x x x .	x
			Extra warm-white	2700 K	x x x .	27.	x x .	x x .	x x .	x x x .	x x x .	x
CRI > 80			Ultra warm-white	2200 K	x x x .	22.	x x .	x x .	x x .	x x x .	x x x .	x
			Tunable white*	2700 - 6500 K	x x x .	65.	x x .	x x .	x x .	x x x .	x x x .	x
			RGB*		x x x .	60.	x x .	00.	x x .	x x x .	x x x .	x

*(available with DMX or Casambi dimming only)

Dimming	Standard	Optional:	0 - 10 V	x x x .	x x .	51.	00.	x x .	x x x .	x x x .	x
			DMX	x x x .	x x .	31.	00.	x x .	x x x .	x x x .	x
			LUTRON 3-wire / EcoSystem (contact factory)**	x x x .	x x .	71.	00.	x x .	x x x .	x x x .	x
			CASAMBI	x x x .	x x .	81.	00.	x x .	x x x .	x x x .	x

First digit indicates dimming protocol. Second digit indicates number of rows of LED.
 Codes shown with 1x row of LED (Standard). For 2x rows of LED replace the second digit accordingly.
 **(available with mounting versions A, C & G only. Consult factory for driver quantity and dimensions)

LED	Standard	Optional:	No second row of LED	x x x .	x x .	x x .	00.	x x .	x x x .	x x x .	x
24V			Neutral-white	x x x .	x x .	x x .	40.	x x .	x x x .	x x x .	x
			Cold-white	x x x .	x x .	x x .	50.	x x .	x x x .	x x x .	x
			Warm-white	x x x .	x x .	x x .	30.	x x .	x x x .	x x x .	x
			Extra warm-white	x x x .	x x .	x x .	27.	x x .	x x x .	x x x .	x
CRI > 80			Ultra warm-white	x x x .	x x .	x x .	22.	x x .	x x x .	x x x .	x
			Tunable white*	x x x .	x x .	x x .	65.	x x .	x x x .	x x x .	x
			RGB*	x x x .	x x .	x x .	00.	x x .	x x x .	x x x .	x

Combinations up to 2 rows of LED possible.
 Select appropriate dimming code and change the second digit to a 2 for 2 rows of LED
 Example, for 0-10V and 2x rows of 4000K: 238.40.52.40.11.Z70.170.A.
 Consult factory for wattage and lumens as well as enclosure/canopy dimensions.
 For fixtures with White + RGB with dimming code 32, the white LED is controlled as 0-10V, the RGB as DMX

▶ x x x . x x . x x . x x . x x . x x x . x x x . x

Complete order number

CIRCOLO I-Version



410 381 1497 answers@inter-lux.com
 inter-lux reserves the right to make technical changes without notice



Light distribution direct / indirect





Conforms to UL-STD 1598
 Certified to CSA-STD C22.2
 No.250.0-08

Technical data is subject to change. Errors and omissions excepted ¹Net lumen output: Losses due to diffusers and reflectors are considered.
²Lumen values refer to an ambient temperature of max. 35° Celsius / 95° Fahrenheit. ³Weight of lights without remote technical unit or canopy.

CIRCOLO

I-Version

Housing: Circular aluminum profile, opal acrylic diffuser on the inside
 Design: SATTLER, Patented



Standard

A 4/6-point straight suspension (5m/197" max.) with remote mounted drivers, separate power cable

B 4-point suspension (5m/197" max.) with drivers in offset surface mounted canopy, separate power cable. (Up to Ø 2600mm/102.3")

C 1-point suspension (up to 197") with remote mounted drivers, separate power cable. (Up to Ø1800mm/70.8")

D 1-point suspension (up to 5m/197") with drivers in offset surface mounted canopy, separate power cable. (Up to Ø 1800mm/70.8")

E Drivers in center surface mounted canopy¹, separate power cable. (Up to Ø 1800mm/70.8")

F Drivers in center surface mounted canopy¹, current carrying suspension cables. (Up to Ø 1800mm)^{2,3}

G 4-point straight suspension (5m/197" max.) with remote mounted drivers, current carrying suspension cables. (Up to Ø 1800mm/70.8")^{2,3}

H 1-point suspension with drivers in pendant canopy PB 366, separate power cable from canopy down. (Up to Ø 1800mm/70.8")² (a) Max. 5m / 196" + (b) Max. 3m/118"

I 1-point suspension with drivers in pendant canopy PB 366, current-carrying suspension cables from canopy down. (Up to Ø 1800mm/70.8")^{2,3} (a) Max. 5m / 196" + (b) Max. 3m/118"

J Semi-flush mounting (50mm /1.9" white standoffs) with remote mounted drivers, separate power cable (2997mm/118")

K Semi-flush mounting (50mm /1.9" white standoffs) with drivers in offset surface mounted canopy, separate power cable (2997mm/118")

L Small clamping canopy with 4 current-carrying cables and a remote mounted driver. (Up to Ø 1800mm /70.8")²

Item No.	LED	Dimming	LED	Finishes	Power Supply cable	Total height	Mounting Version
----------	-----	---------	-----	----------	--------------------	--------------	------------------

- 1 Mounting versions E & F = Minimum suspension height half the diameter of the light fixture, maximum suspension height two times the diameter of the light fixture
- 2 Only available with 1 row of LED.
- 3 Not in combination with RGB

X X X.	X X X.	X X X.	X				
--------	------	------	------	------	--------	--------	---

Driver enclosure dimensions (1 row of LED)

Type	Size mm / inch L W H	Size of lamp mm / inch.	Included with Mounting Version
DE 1F	360 x 150 x 85 mm 14.2 x 5.9 x 3.3"	up to Ø 1800 / 62.9"	A, C, G, K, R
DE 2F	360 x 300 x 85 mm 14.2 x 11.8 x 3.3"	up to size Ø 3500 / 137.8"	A, G


Power cable cover plate
 (included with mounting version A, C & G)
 Ceiling opening box for power supply cable (80mm / 3.1" Ø round metal cover). White powder coated finish.

Canopy dimensions (1 row of LED)

Type	Size mm / inch Ø cover plate / body	Included with Mounting Version
DB 290	Ø 290-260 x 60 mm / 11.4-10.2 x 2.4" up to size Ø 1800 / 62.9"	B, D, E, F, H
DB 350	Ø 350-320 x 60 mm / 13.7-12.5 x 2.4" up to size Ø 3500 / 137.8"	B, H
DB 145	Ø 145-133 x 55 mm / 5.7-5.2 x 2.2" up to size Ø 1800 / 62.9"	K
PB 366	Ø 90mm x H 366 mm / 3.5 x 14.4" up to size Ø 1320 / 51.9"	S, T
PB 656	Ø 90mm x H 656 mm / 3.5 x 25.8" up to size Ø 1800 / 70.8"	S, T

Canopy finish: white (11) contact factory for other finishes
 USA/Canada: Canopy mounts to 4" octagonal junction box

Input voltage for all drivers is
120 / 277 VAC 50/60 Hz



Complete order number

X X X.	X X X.	X X X.	X				
--------	------	------	------	------	--------	--------	---

Optional



CASAMBI Xpress (Order separately. Available Q3 2019. Contact factory)
 Casambi remote control / wireless wall-switch. The four buttons can control a fixture, multiple fixtures or a scene (programmable through the Casambi app). Up to 4 groups may be individually programmed. The switch can be magnetically attached to the provided wall mounting plate.

207. 00. 00. 00. 11 (white)
207. 00. 00. 00. 10 (black)

