


SOFT DELTA LIGHT + ACOUSTIC

Housing: Aluminum profile, integrated acrylic cover. Fabric covering as a light and acoustic diffuser.
Design: SATTLER



	Size: L x W x H mm	inches	LED Watt	Lumen ¹⁾	weight kg ²⁾ / lbs ²⁾	Item No.	LED	Dimming	LED	Finishes	Power Supply cable	Mounting Version						
Sizes	1340 x 1309 x 80	52.7 x 51.5 x 3.1	64	5,642	14 / 30.0	850.	x x.	x x.	x x.	x x.	x x x.	x						
	1735 x 1717 x 80	68.3 x 67.5 x 3.1	82	6,412	17 / 37.5	862.	x x.	x x.	x x.	x x.	x x x.	x						
LED 24V CRI > 80			Neutral-white Cold-white Warm-white Extra warm-white Extra warm-white Tunable white* RGB color control* RGB + Neutral-White*	4000 K 5000 K 3000 K 2700 K 2200 K 2700 - 6500 K 4000 K 4000 K	(Standard) (Optional) (Optional) (Optional) (Optional) (Optional) (Optional) (Optional)	x x x. x x x. x x x. x x x. x x x. x x x. x x x. x x x.	40. 50. 30. 27. 22. 65. 60. 60.	x x. x x. x x. x x. x x. x x. x x. x x.	x x. x x. x x. x x. x x. x x. x x. x x.	x x. x x. x x. x x. x x. x x. x x. x x.	x x x. x x x. x x x. x x x. x x x. x x x. x x x. x x x.	x x x x x x x x						
Dimming			Dimmable 0 - 10 V DMX (RGB possible) LUTRON (contact factory)		(Standard) (Optional) (Optional)	x x x. x x x. x x x.	x x. x x. x x.	51. 31. 71.	00. 00. 00.	x x. x x. x x.	x x x. x x x. x x x.	x x x						
Finishes		11 white (Standard)		22 aluminum polished (Optional)		30 anthracite		27 brush-finished aluminum		32 crocodile black		33 sand silver fine textured						
				35 gold		36 brass		37 bronze fine textured		38 copper		10 black fine textured						
				40 brass patinated		42 bronze patinated		44 wood veneer, white borders		XX Custom finish	x x x.	x x.	x x.	x x.		x x x.	x	
Power Supply Cable		Z 70 Silver (Standard)		Z 71 white (Optional)		Z 72 grey		Z 73 black										
				Z 74 orange		Z 75 red		Z 76 green										

1.8.17 SOFT DELTA LIGHT + ACOUSTIC




410 381 1497 answers@inter-lux.com
inter-lux reserves the right to make technical changes without notice

IP 20 Light distribution direct Conforms to UL-STD 1598 Certified to CSA-STD C22.2 No.250.0-08


1) Net lumen output: Losses due to diffusers and reflectors are considered. Lumen values refer to an ambient temperature of max. 35° Celsius / 95° Fahrenheit.
2) Weight of lights without remote technical unit or canopy.

SOFT DELTA LIGHT + ACOUSTIC


Housing: Aluminum profile, integrated acrylic cover. Fabric covering as a light and acoustic diffuser.
Design: SATTLER




Mounting Version




3-point suspension with external power supply unit in suspended ceiling




3-point suspension with external power supply unit in separate canopy




suspension through canopy




3 current-carrying steel cables. Only 1 strip LED possible. Not in combination with RGB




Suspension with pendant canopy PB 366 and steel cables
(a) 5000 mm / 196.8" +
(b) 3000 mm / 118.1"




Suspension with pendant canopy PB 366 and current-carrying steel cables.
(a) 5000 mm / 196.8" +
(b) 3000 mm / 118.1"
Not in combination with RGB.



Direct ceiling mounting 50mm / 1.9" with external power supply unit in suspended ceiling



Direct ceiling mounting (white) 50mm / 1.9" with external power supply unit in separate canopy



Suspension point as clamping unit with 3 current-carrying cables and remote technical unit in suspended ceiling.

Item No.	LED	Dimming	LED	Finishes	Power Supply cable	Mounting Version
x x x.	x x.	x x.	x x.	x x.	x x x	.

A, B, G, H = Distance of external power supply unit to light fixture max. 10m / 394".

S, T, K, E, F = Minimum suspension height half the diameter of light fixture, maximum suspension height two times diameter of light fixture

Including steel cable suspension 5000mm / 197" ; Version F, S, T 5000 / 3000mm / 197"/118" and/or power supply cable 5000mm / 197"

x x x.	x x.	x x.	x x.	x x.	x x x	x
--------	------	------	------	------	-------	---

Complete order number


Typ	Dimensions of external power supply units (1 LED Stripe)			For use with Mounting Version
	Size mm / inch	L	W H	
DE 1F	360 x 150 x 85 mm / 14.2 x 5.9 x 3.3"			A, G, K

Typ	Dimensions of canopy (1 LED Stripe)		For use with Mounting Version
	Size mm / inch	Ø cover plate / body	
DB 290	Ø 290 / 260 mm / 11.4 x 10.2"	size 1340 x 1309 mm	B, E, F, H
DB 350	Ø 350 / 320 mm / 13.7 x 12.5"	size 1735 x 1717 mm	B, E, F, H
PB 366	Ø 90 H 366 mm / 13.7 x 12.5"		S, T

Canopy finish: white (11) contact factory for other finishes
USA/Canada: Canopy mounts to 4" octagonal junction box.

Input voltage for all external power supply units and canopy is 120 / 277 VAC 50/60 Hz

Optional



Ceiling fixation for mounting version A

200. 00. 00. 00. 11 (white)

Ceiling opening for power supply cable. Existing of cavity ceiling box with 80mm / 3.1" round metal cover. Powder coated in white, fine textured. Applicable to mounting version A.