



# Step RC

## SURFACE

Direct illumination with indirect glow



### Model 1541

#### Type

S Surface

#### Size

24 24.0" (610mm)  
 28 28.0" (711mm)  
 32 32.0" (813mm)  
 36 36.0" (914mm)  
 48 48.0" (1219mm)  
 Custom

#### Wattage<sup>1,2</sup>

**24"**  
 L 8W (1065lm)  
 M 16W (1980lm)  
**28"**  
 L 10W (1335lm)  
 M 20W (2475lm)  
**32"**  
 L 12W (1600lm)  
 M 24W (2970lm)  
**36"**  
 L 14W (1865lm)  
 M 28W (3465lm)  
**48"**  
 L 20W (2665lm)  
 M 40W (4955lm)

#### Color Temp<sup>3</sup>

30 3000  
 35 3500  
 40 4000

#### Voltage

U 120/277 Volt

#### Driver

RD Remote  
 ID Integral

#### Control - (RD/ID)

S Non-dim  
 D010 0-10V 10%  
 L3DAE Lutron Hi-lume 1% EcoSystem  
 L3DOE Hi-lume Premier 0.1% EcoSystem (remote only)

#### Diffuser Bottom

SW Satin opal acrylic

#### Diffuser Top

CPS Clear polycarbonate - sanded both sides

#### Finish

16 Clear anodized aluminum  
 21 Painted white - RAL 9010 matte  
 26 Painted black - RAL 9005 matte  
 22 Painted custom color

#### Notes

- Nominal lumens value specified
- Linear LED board, constant voltage 24 Volt
- 90+ CRI standard

