

Step RC

SURFACE

Direct illumination with indirect glow



Model 1541

Type

S Surface

Size

24 24.0" (610mm)
28 28.0" (711mm)
32 32.0" (813mm)
36 36.0" (914mm)
48 48.0" (1219mm)
Custom

Wattage^{1,2}

24"
L 8W (1065lm)
M 16W (1980lm)
28"
L 10W (1335lm)
M 20W (2475lm)
32"
L 12W (1600lm)
M 24W (2970lm)
36"
L 14W (1865lm)
M 28W (3465lm)
48"
L 20W (2665lm)
M 40W (4955lm)

Color Temp³

30 3000
35 3500
40 4000

Voltage

U 120/277 Volt

Driver

RD Remote
ID Integral

Control - (RD/ID)

S Non-dim
D010 0-10V 10%
L3DAE Lutron Hi-lume 1% EcoSystem
L3DOE Hi-lume Premier 0.1% EcoSystem (remote only)

Diffuser Bottom

SW Satin opal acrylic

Diffuser Top

CPS Clear polycarbonate - sanded both sides

Finish

16 Clear anodized aluminum
21 Painted white - RAL 9010 matte
26 Painted black - RAL 9005 matte
22 Painted custom color

Notes

- 1 Nominal lumens value specified
- 2 Linear LED board, constant voltage 24 Volt
- 3 90+ CRI standard

