



### Advantages

- Field replaceable boards for sustainability
- Available in multiple lengths to accommodate exacting installations
- Multiple wattages and lumen output for maximum flexibility within any application
- Four (4) standard color temperatures from 2700K-4000K; non-standard available
- Compatible with all common dimmer and control standards such as 0-10V, 3-wire, forwardphase w/neutral, DALI and DMX. For others, please contact factory
- High efficiency design delivers more lumens per watt
- CV is used throughout all Whitegoods products for color and performance consistency
- 5-year warranty

### Technical Data

- form linear
- circuitry parallel
- power (W/ft) 3W, 6W, 10W, 13W
- supply type CV
- operating voltage (VDC) 24
- color rendering index Ra\* 82
- MacAdam 3 step
- viewing angle (°) 110
- LED (SMD) quantity (per foot) 42
- PCB substrate FR4
- lifetime-L70 (h)\*\* 60,000
- working temperature -20°C - 60°C

\*Typical. Higher CRI available

\*\*Tested to LM80

Power (w/ft)	CCT (k)	Lum.Flux (lm/ft)	lm/watt
3	2700	400	133
3	3000	400	133
3	3500	416	138
3	4000	424	141
6	2700	743	123
6	3000	743	123
6	3500	774	129
6	4000	789	131
10	2700	1174	117
10	3000	1174	117
10	3500	1222	122
10	4000	1246	124

90+ CRI will result in 16% lower lumen output.

Conformal coated boards for damp and wet location applications are available.