


WG-MEC-...-SSD-W								
Delivered Lumens Per Foot								
	Power							
	P0 [1.5 W/ft]	P1 [3 W/ft]	P2 [6 W/ft]	P3 [10 W/ft]	P4 [15 W/ft]	L [2.7 W/ft]	M [5.5 W/ft] ²	H [8.0 W/ft]
CCT	927	243	470	884	1358	2001	-	-
	930	254	490	920	1415	2084	-	-
	935	263	507	953	1466	2182	-	-
	940	265	520	978	1505	2241	-	-
	TW ¹	141	255	457	694	-	-	-
	WD ¹	-	-	-	-	204	424	613
	RGBW ²	-	-	-	-	-	346	-



Beam Angle (0-180) = 53.4
Beam Angle (90-270) = 115.9

	Power Multiplier							
	P0 [1.5 W/ft]	P1 [3 W/ft]	P2 [6 W/ft]	P3 [10 W/ft]	P4 [15 W/ft]	L [2.7 W/ft]	M [5.5 W/ft] ²	H [8.0 W/ft]
9XX	0.12	0.23	0.44	0.67	1.00	-	-	-
TW	0.06	0.12	0.21	0.32	-	-	-	-
WD	-	-	-	-	-	0.09	0.19	0.28
RGBW	-	-	-	-	-	-	0.16	-

CCT Multiplier			
927	930	935	940
0.92	0.95	1.00	1.03

- 1 TW lumen data at maximum output (4000K). WD lumen data at maximum output (3000K).
- 2 RGBW lumen data at maximum output with 3000K White LED. M- RGBW power level wattage is 7.6W/ft.
- 3 Polar Plot and Isofootcandle diagram are applicable to part number noted; use Multiplier table(s) to approximate other Power / CCT options.