


Vos_Q | Downlight | powerLED | Damp location | Driver remote | 1.5W 500mA



Balance - CRI 92

White	E90620	2700 K	134 lm	M	Medium Flood	20
Black	E90621	3000 K	153 lm	W	Medium Flood	35
		3500 K	153 lm	T		



Efficiency - CRI 80

White	E90406	2700 K	187 lm	M	Medium Flood	20
Black	E90407	3000 K	199 lm	W	Medium Flood	35
		3500 K	199 lm	T		
		4000 K	213 lm	N		

power supply options (remote only)

ECO30W-500 0-10V EldoLED ECOdrive 30W for 1-10 fixtures	SOLO50W-500 0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	SOLO100W-500 0-10V EldoLED SOLOdrive 100W for 1-40 fixtures
--	--	--

Vos_Q | Downlight | powerLED | Damp locatoin | Driver remote | 2W 630mA



Balance - CRI 92

White	E90624	2700 K	157 lm	M	Spot	15
Black	E90625	3000 K	179 lm	W	Medium Flood	30
		3500 K	179 lm	T	Flood	60



White	E90630
Black	E90631

Efficiency - CRI 80

White	E90410	2700 K	219 lm	M	Spot	15
Black	E90411	3000 K	233 lm	W	Medium Flood	30
		3500 K	233 lm	T	Flood	60
		4000 K	249 lm	N		





White	E90628
Black	E90629

power supply options (remote only)

ECO30W-630 0-10V EldoLED ECOdrive 30W for 1-10 fixtures	SOLO50W-630 0-10V EldoLED SOLOdrive 50W for 1-16 fixtures	SOLO100W-630 0-10V EldoLED SOLOdrive 100W for 1-32 fixtures
--	--	--

technical information

Vos_Q | Downlight | powerLED | Damp locatoin | Driver remote | 4W 350mA



Balance - CRI 92

White	E90636	2700 K	395 lm	M	Spot	15
Black	E90637	3000 K	423 lm	W	Medium Flood	30
		3500 K	423 lm	T	Flood	60
		4000 K	456 lm	N		



White **E90642**

Black **E90643**

Efficiency - CRI 80

White	E90414	2700 K	490 lm	M	Spot	15
Black	E90415	3000 K	490 lm	W	Medium Flood	30
		3500 K	490 lm	T	Flood	60
		4000 K	529 lm	N		



White **E90640**

Black **E90641**

power supply options (remote only)

ECO30W-350

0-10V EldoLED ECOdrive
30W for 1-3 fixtures



SOLO50W-350

0-10V EldoLED SOLOdrive
50W for 1-6 fixtures

SOLO100W-350

0-10V EldoLED SOLOdrive
100W for 1-12 fixtures

Vos_Q | Downlight | powerLED | Damp location | Driver remote | 6W 500mA



Balance - CRI 92

White	E90648	2700 K	532 lm	M	Spot	15
Black	E90649	3000 K	569 lm	W	Medium Flood	30
		3500 K	569 lm	T	Flood	60
		4000 K	614 lm	N		



White **E90654**

Black **E90655**

Efficiency - CRI 80

White	E90418	2700 K	659 lm	M	Spot	15
Black	E90419	3000 K	659 lm	W	Medium Flood	30
		3500 K	659 lm	T	Flood	60
		4000 K	711 lm	N		



White **E90652**

Black **E90653**

power supply options (remote only)

ECO30W-500


0-10V EldoLED ECOdrive
30W for 1-3 fixtures

SOLO50W-500



0-10V EldoLED SOLOdrive
50W for 1-6 fixtures

SOLO100W-500

0-10V EldoLED SOLOdrive
100W for 1-12 fixtures



Vos_Q | Downlight | powerLED | Damp location | Driver remote | 8W 700mA



2.5

Balance - CRI 92

White	E90660	2700 K	689 lm	M	Spot	15
Black	E90661	3000 K	738 lm	W	Medium Flood	30
		3500 K	738 lm	T	Flood	45
		4000 K	796 lm	N		

HC

White	E90666
Black	E90667

Efficiency - CRI 80

White	E90428	2700 K	854 lm	M	Spot	15
Black	E90429	3000 K	854 lm	W	Medium Flood	30
		3500 K	854 lm	T	Flood	45
		4000 K	922 lm	N		

HC

White	E90664
Black	E90665

power supply options (remote only)

ECO30W-700

0-10V EldoLED ECOdrive
30W for 1-3 fixtures



SOLO50W-700

0-10V EldoLED SOLOdrive
50W for 1-4 fixtures

SOLO100W-700

0-10V EldoLED SOLOdrive
100W for 1-8 fixtures

Vos_Q | Downlight | arrayLED | Damp location | Driver remote | 15W 400mA



3.7

Balance - CRI 92

White	E90672	2700 K	1568 lm	M	Spot	15
Black	E90673	3000 K	1677 lm	W	Medium Flood	30
		3500 K	1677 lm	T	Flood	60
		4000 K	1804 lm	N		

HC

White	E90678
Black	E90679

Efficiency - CRI 80

White	E90438	2700 K	1932 lm	M	Spot	15
Black	E90439	3000 K	1932 lm	W	Medium Flood	30
		3500 K	1932 lm	T	Flood	60
		4000 K	2078 lm	N		

HC

White	E90676
Black	E90677

power supply options (remote only)

ECO30W-400

0-10V EldoLED ECOdrive
30W for 1 fixture

SOLO50W-400



0-10V EldoLED SOLOdrive
50W for 1-2 fixtures

SOLO100W-400

0-10V EldoLED SOLOdrive
100W for 1-4 fixtures

technical
information

Vos_Q | Downlight | arrayLED | Damp location | Driver remote | 25W 700mA



Balance - CRI 92

White	E80726	2700 K	2598 lm	M	Spot	15
Black	E80727	3000 K	2794 lm	W	Medium Flood	30
		3500 K	2794 lm	T	Flood	60
		4000 K	2990 lm	N		



White	E90686
Black	E90687

Efficiency - CRI 80

White	E80728	2700 K	3210 lm	M	Spot	15
Black	E80729	3000 K	3431 lm	W	Medium Flood	30
		3500 K	3431 lm	T	Flood	60
		4000 K	3431 lm	N		



White	E90684
Black	E90685

power supply options (remote only)

SOLO50W-700

0-10V EldoLED SOLOdrive
50W for 1 fixture

SOLO100W-700

0-10V EldoLED SOLOdrive
100W for 1-3 fixtures

technical
information