


Vos_R | Downlight | powerLED | Damp location | Driver remote | 1.5W 500mA



Balance - CRI 92

White	E90622	2700 K	134 lm	M	Medium Flood	20
Black	E90623	3000 K	153 lm	W	Medium Flood	35
		3500 K	153 lm	T		



Efficiency - CRI 80

White	E90408	2700 K	187 lm	M	Medium Flood	20
Black	E90409	3000 K	199 lm	W	Medium Flood	35
		3500 K	199 lm	T		
		4000 K	213 lm	N		

power supply options (remote only)

ECO 30W-500 0-10V EldoLED ECOdrive 30W for 1-10 fixtures	SOLO50W-500 0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	SOLO100W-500 0-10V EldoLED SOLOdrive 100W for 1-40 fixtures
---	--	--

Vos_R | Downlight | powerLED | Damp location | Driver remote | 2W 630mA



Balance - CRI 92

White	E90626	2700 K	157 lm	M	Spot	15
Black	E90627	3000 K	179 lm	W	Medium Flood	30
		3500 K	179 lm	T	Flood	60

White	E90634
Black	E90635

Efficiency - CRI 80

White	E90412	2700 K	219 lm	M	Spot	15
Black	E90413	3000 K	233 lm	W	Medium Flood	30
		3500 K	233 lm	T	Flood	60
		4000 K	249 lm	N		



White	E90632
Black	E90633

power supply options (remote only)

ECO30W-630 0-10V EldoLED ECOdrive 30W for 1-10 fixtures	SOLO50W-630 0-10V EldoLED SOLOdrive 50W for 1-16 fixtures	SOLO100W-630 0-10V EldoLED SOLOdrive 100W for 1-32 fixtures
--	--	--

technical information

Vos_R | Downlight | powerLED | Damp location | Driver remote | 4W 350mA



Balance - CRI 92

White	E90638	2700 K	395 lm	M	Spot	15
Black	E90639	3000 K	423 lm	W	Medium Flood	30
		3500 K	423 lm	T	Flood	60
		4000 K	456 lm	N		



White **E90646**

Black **E90647**

Efficiency - CRI 80

White	E90416	2700 K	490 lm	M	Spot	15
Black	E90417	3000 K	490 lm	W	Medium Flood	30
		3500 K	490 lm	T	Flood	60
		4000 K	529 lm	N		



White **E90644**

Black **E90645**

power supply options (remote only)

ECO30W-350

0-10V EldoLED ECOdrive
30W for 1-3 fixtures



SOLO50W-350

0-10V EldoLED SOLOdrive
50W for 1-6 fixtures

SOLO100W-350

0-10V EldoLED SOLOdrive
100W for 1-12 fixtures

Vos_R | Downlight | powerLED | Damp location | Driver remote | 6W 500mA



Balance - CRI 92

White	E90650	2700 K	532 lm	M	Spot	15
Black	E90651	3000 K	569 lm	W	Medium Flood	30
		3500 K	569 lm	T	Flood	60
		4000 K	614 lm	N		



White **E90658**

Black **E90659**

Efficiency - CRI 80

White	E90420	2700 K	659 lm	M	Spot	15
Black	E90421	3000 K	659 lm	W	Medium Flood	30
		3500 K	659 lm	T	Flood	60
		4000 K	711 lm	N		



White **E90656**

Black **E90657**

power supply options (remote only)

ECO30W-500


0-10V EldoLED ECOdrive
30W for 1-3 fixtures

SOLO50W-500


0-10V EldoLED SOLOdrive
50W for 1-6 fixtures

SOLO100W-500

0-10V EldoLED SOLOdrive
100W for 1-12 fixtures



Vos_R | Downlight | powerLED | Damp location | Driver remote | 8W 700mA



2.5

HC

Balance - CRI 92

White	E90662	2700 K	689 lm	M	Spot	15
Black	E90663	3000 K	738 lm	W	Medium Flood	30
		3500 K	738 lm	T	Flood	45
		4000 K	796 lm	N		

White **E90670**

Black **E90671**

Efficiency - CRI 80

White	E90430	2700 K	854 lm	M	Spot	15
Black	E90431	3000 K	854 lm	W	Medium Flood	30
		3500 K	854 lm	T	Flood	45
		4000 K	922 lm	N		

HC

White **E90668**

Black **E90669**

power supply options (remote only)

ECO30W-700

0-10V EldoLED ECOdrive
30W for 1-3 fixtures


SOLO50W-700

0-10V EldoLED SOLOdrive
50W for 1-4 fixtures

SOLO100W-700

0-10V EldoLED SOLOdrive
100W for 1-8 fixtures

Vos_R | Downlight | arrayLED | Damp location | Driver remote | 15W 400mA



3.7

HC

Balance - CRI 92

White	E90674	2700 K	1568 lm	M	Spot	15
Black	E90675	3000 K	1677 lm	W	Medium Flood	30
		3500 K	1677 lm	T	Flood	60
		4000 K	1804 lm	N		

White **E90682**

Black **E90683**

Efficiency - CRI 80

White	E90440	2700 K	1932 lm	M	Spot	15
Black	E90441	3000 K	1932 lm	W	Medium Flood	30
		3500 K	1932 lm	T	Flood	60
		4000 K	2078 lm	N		

HC

White **E90680**

Black **E90681**

power supply options (remote only)

ECO30W-400

0-10V EldoLED ECOdrive
30W for 1 fixture

SOLO50W-400


0-10V EldoLED SOLOdrive
50W for 1-2 fixtures

SOLO100W-400

0-10V EldoLED SOLOdrive
100W for 1-4 fixtures

technical information

Vos_R | Downlight | arrayLED | Damp location | Driver remote | 25W 700mA



 4.8

 HC

Balance - CRI 92

White	E80722	2700 K	2598 lm	M	Spot	15
Black	E80723	3000 K	2794 lm	W	Medium Flood	30
		3500 K	2794 lm	T	Flood	60
		4000 K	2990 lm	N		

White **E90690**

Black **E90691**

Efficiency - CRI 80

White	E80724	2700 K	3210 lm	M	Spot	15
Black	E80725	3000 K	3431 lm	W	Medium Flood	30
		3500 K	3431 lm	T	Flood	60
		4000 K	3431 lm	N		

 HC

White **E90688**

Black **E90689**


power supply options (remote only)

SOLO50W-700

0-10V EldoLED SOLOdrive
50W for 1 fixture

SOLO100W-700

0-10V EldoLED SOLOdrive
100W for 1-3 fixtures



technical
information