



Warp_R | Downlight | powerLED | Damp Location | Driver remote | 2W 630mA



Balance - CRI 92

White	E90542	2700 K	157 lm	M	Spot	15
Black	E90543	3500 K	179 lm	T	Medium Flood	30
		3000 K	179 lm	W	Flood	60

White	E90722
Black	E90723

Efficiency - CRI 80



White	E90544	2700 K	219 lm	M	Spot	15
Black	E90545	3000 K	233 lm	W	Medium Flood	30
		3500 K	233 lm	T	Flood	60

White	E90720	4000 K	249 lm	N
Black	E90721			

Power supply options (remote only)

ECO30W-630 0-10V EldoLED ECOdrive 30W for 1-10 fixtures	SOLO50W-630 0-10V EldoLED SOLOdrive 50W for 1-16 fixtures	SOLO100W-630 0-10V EldoLED SOLOdrive 100W for 1-32 fixtures
--	--	--

Warp_R | Downlight | powerLED | Damp Location | Driver remote | 4W 350mA



Balance - CRI 92

White	E90740	2700 K	395 lm	M	Spot	15
Black	E90741	3000 K	423 lm	W	Medium Flood	30
		3500 K	423 lm	T	Flood	60

White	E90744	4000 K	456 lm	N
Black	E90745			

Efficiency - CRI 80

White	E90546	2700 K	490 lm	M	Spot	15
Black	E90547	3000 K	490 lm	W	Medium Flood	30
		3500 K	490 lm	T	Flood	60



White	E90742	4000 K	529 lm	N
Black	E90743			

Power supply options (remote only)

ECO30W-350 0-10V EldoLED ECOdrive 30W for 1-3 fixtures	SOLO50W-350 0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	SOLO100W-350 0-10V EldoLED SOLOdrive 100W for 1-12 fixtures
---	---	--

technical
information

Warp_R | Downlight | powerLED | Damp Location | Driver remote | 6W 500mA



Balance - CRI 92

White	E90748	2700 K	532 lm	M	Spot	15
Black	E90749	3000 K	569 lm	W	Medium Flood	30
		3500 K	569 lm	T	Flood	60
White	E90752	4000 K	614 lm	N		
Black	E90753					



Efficiency - CRI 80



White	E90548	2700 K	659 lm	M	Spot	15
Black	E90549	3000 K	659 lm	W	Medium Flood	30
		3500 K	659 lm	T	Flood	60
White	E90750	4000 K	711 lm	N		
Black	E90751					



Power supply options (remote only)

ECO30W-500 0-10V EldoLED ECOdrive 30W for 1-3 fixtures	SOLO50W-500 0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	SOLO100W-500 0-10V EldoLED SOLOdrive 100W for 1-12 fixtures
---	---	--

Warp_R | Downlight | powerLED | Damp Location | Driver remote | 10W 800mA



Balance - CRI 92

White	E90762	2700 K	960 lm	M	Spot	15
Black	E90763	3000 K	1034 lm	W	Medium Flood	30
		3500 K	1034 lm	T	Flood	60
White	E90766	4000 K	1108 lm	N		
Black	E90767					



Efficiency - CRI 80

White	E90550	2700 K	1108 lm	M	Spot	15
Black	E90551	3000 K	1194 lm	W	Medium Flood	30
		3500 K	1194 lm	T	Flood	60
White	E90764	4000 K	1280 lm	N		
Black	E90765					





Power supply options (remote only)

ECO30W-800 0-10V EldoLED ECOdrive 30W for 1-2 fixtures	SOLO100W-800 0-10V EldoLED SOLOdrive 100W for 1-4 fixtures
---	---

technical information

Warp_R | Downlight | arrayLED | Damp Location | Driver remote | 15W 400mA



Balance - CRI 92

White E90776	2700 K	1568 lm	M	Spot	15
Black E90777	3000 K	1677 lm	W	Medium Flood	30
	3500 K	1677 lm	T	Flood	60
White E90780	4000 K	1804 lm	N		
Black E90781					


Efficiency - CRI 80

White E90552	2700 K	1932 lm	M	Spot	15
Black E90553	3000 K	1932 lm	W	Medium Flood	30
	3500 K	1932 lm	T	Flood	60
White E90778	4000 K	2078 lm	N		
Black E90779					

Power supply options (remote only)

ECO30W-400	SOLO50W-400	SOLO100W-400
0-10V EldoLED ECOdrive 30W for 1 fixture	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

Warp_R | Downlight | arrayLED | Damp Location | Driver remote | 25W 700mA



Balance - CRI 92

White E90790	2700 K	2598 lm	M	Spot	15
Black E90791	3000 K	2794 lm	W	Medium Flood	30
	3500 K	2794 lm	T	Flood	60
White E90794	4000 K	2990 lm	N		
Black E90795					

Efficiency - CRI 80

White E90612	2700 K	3210 lm	M	Spot	15
Black E90613	3000 K	3431 lm	W	Medium Flood	30
	3500 K	3431 lm	T	Flood	60
White E90792	4000 K	3431 lm	N		
Black E90793					



Power supply options (remote only)

SOLO50W-700	SOLO100W-700
0-10V EldoLED SOLOdrive 50W for 1 fixture	0-10V EldoLED SOLOdrive 100W for 1-3 fixtures

technical
information



Warp_R | Downlight | arrayLED | Damp Location | Driver remote | 45W 1250mA



Balance - CRI 92

White	E81487	2700 K	5033 lm	M	Spot	15
Black	E81488	3000 K	5383 lm	W	Medium Flood	30
		3500 K	5383 lm	T	Flood	60
White	E81491	4000 K	5784 lm	N		
Black	E81492					

Efficiency - CRI 80

White	E81485	2700 K	6185 lm	M	Spot	15
Black	E81486	3000 K	6185 lm	W	Medium Flood	30
		3500 K	6185 lm	T	Flood	60
White	E81489	4000 K	6649 lm	N		
Black	E81490					



Power supply options (remote only)

SOLO100W-1250

0-10V EldoLED SOLOdrive
100W for 1 fixture