

concentrica



The Concentrica uplight creates an unusual and eye-catching effect. The UV-resistant optics compartment is fitted with F.O.L.™ technology, while the AquaStop® provides effective protection against water and moisture.

Materials

Anodized aluminum body

Single or double opalescent polycarbonate diffuser



Concentrica_R | Drive-over spotlights | 24 V | topLED | Wet location | Driver remote | Drive over | 1.4W



CRI 80

White	E95474	2700 K	54 lm	M	General	00
Black	E95475	3000 K	60 lm	W		
Grey	E95476	4000 K	63 lm	N		

Power supply options (remote only)


OT96-D010

Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-dim 24V DC, 120-277VAC, Wet location

Recessed casings



Concentrica_R | Drive-over spotlights | 24 V | topLED | Wet location | Driver remote | Drive over | 2.6W



CRI 80

White	E95486	2700 K	216 lm	M	General	00
Black	E95487	3000 K	240 lm	W		
Grey	E95488	4000 K	252 lm	N		

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location enclosure


OT96-JBX

Osram, Non-dim 24V DC, 120-277VAC, Wet location

Recessed casings



Concentrica_Q | Drive-over spotlights | 24 V | topLED | Wet location | Driver remote | Drive over | 1.4W



CRI 80

White	E96659	2700 K	54 lm	M	General	00
Black	E96660	3000 K	60 lm	W		
Grey	E96661	4000 K	63 lm	N		

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-dim 24V DC, 120-277VAC, Wet location

Recessed casings

4.01 / 4.8




2.05

E98402

Steel and PVC outer casing for floor-mounted installation

Concentrica_Q | Drive-over spotlights | 24 V | topLED | Wet location | Driver remote | Drive over | 2.6W



CRI 80

White	E94059	2700 K	216 lm	M	General	00
Black	E94060	3000 K	240 lm	W		
Grey	E94061					

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location enclosure

OT96-JBX

Osram, Non-dim 24V DC, 120-277VAC, Wet location

Recessed casings

4.21 / 5



3.31

E98403

Steel and PVC outer casing for floor-mounted installation