

Orma

inter•lux



A drive-over uplight whose undisputable strength is its **reduced height**. A **good luminous flux and high protection** make this lighting fixture the ideal partner to illuminate outdoor architecture in a versatile way.

Passive heat dissipation

Anodized aluminum casing or AISI 316 stainless steel casing for high salinity environments

Light management


Partly black silk-screened diffuser to reduce glare

Reduced installation space

Minimum installation space, 2.2 to 2.6 in total height



Orma_R | Drive-over spotlight | powerLED 3W 350 mA




type		color			optic		
Steel/Alu	CRI 80	E96098	2700 K	408 lm	M	15°	15
			3000 K	435 lm	W	30°	30
			4000 K	465 lm	N	60°	60

power supply options (remote only)



ECO30W-350	SOLO50W-350	SOLO100W-350	E98057
0-10V EIdoLED ECOdrive 30W, for 1-5 fixtures	0-10V EIdoLED SOLOdrive 50W, for 1-10 fixtures	0-10VEIdoLED SOLOdrive 100W, for 1-20 fixtures	Outer casing (required, order separately)

Orma_R | Drive-over spotlight | powerLED 6W 350 mA




type		color			optic		
Steel/Alu	CRI 80	E93980	2700 K	816 lm	M	8°	08
			3000 K	870 lm	W	30°	30
			4000 K	930 lm	N	60°	60
						Diff.	00

power supply options (remote only)



ECO30W-350	SOLO50W-350	SOLO100W-350	E98399
0-10V EIdoLED ECOdrive 30W, for 1-2 fixtures	0-10V EIdoLED SOLOdrive 50W, for 1-4 fixtures	0-10VEIdoLED SOLOdrive 100W, for 1-8 fixtures	Outer casing (required, order separately)

Orma_RI | Drive-over spotlight | powerLED 3W 350 mA | stainless steel




type		color			optic		
Steel	CRI 80	E96100	2700 K	408 lm	M	15°	15
			3000 K	435 lm	W	30°	30
			4000 K	465 lm	N	60°	60

power supply options (remote only)



ECO30W-350	SOLO50W-350	SOLO100W-350	E98057
0-10V EIdoLED ECOdrive 30W, for 1-5 fixtures	0-10V EIdoLED SOLOdrive 50W, for 1-10 fixtures	0-10VEIdoLED SOLOdrive 100W, for 1-20 fixtures	Outer casing (required, order separately)

Orma_RI | Drive-over spotlight | powerLED 6W 350 mA | stainless steel



type		color			optic		
Steel	CRI 80	E93993	2700 K	816 lm	M	8°	08
			3000 K	870 lm	W	30°	30
			4000 K	930 lm	N	60°	60
						Diff.	00

power supply options (remote only)





ECO30W-350	SOLO50W-350	SOLO100W-350	E98399
0-10V EIdoLED ECOdrive 30W, for 1-2 fixtures	0-10V EIdoLED SOLOdrive 50W, for 1-4 fixtures	0-10VEIdoLED SOLOdrive 100W, for 1-8 fixtures	Outer casing (required, order separately)

Orma | Outer-casing



type	Ø in	h. in	suitable for	
PVC	2.3	2.2	Orma - Techo67 3W	E98057

Orma_Q | Drive-over spotlight | powerLED 3W 350 mA




type		color			optic	
Steel/Alu	CRI 80	E96099	2700 K	408 lm	M	15° 15
			3000 K	435 lm	W	30° 30
			4000 K	465 lm	N	60° 60

power supply options (remote only)



ECO30W-350	SOLO50W-350	SOLO100W-350	E98057
0-10V EIdoLED ECOdrive 30W, for 1-5 fixtures	0-10V EIdoLED SOLOdrive 50W, for 1-10 fixtures	0-10VEIdoLED SOLOdrive 100W, for 1-20 fixtures	Outer casing (required, order separately)

Orma_Q | Drive-over spotlight | powerLED 6W 350 mA




type		color			optic	
Steel/Alu	CRI 80	E93981	2700 K	816 lm	M	8° 08
			3000 K	870 lm	W	30° 30
			4000 K	930 lm	N	60° 60
						Diff. 00

power supply options (remote only)



ECO30W-350	SOLO50W-350	SOLO100W-350	E98399
0-10V EIdoLED ECOdrive 30W, for 1-2 fixtures	0-10V EIdoLED SOLOdrive 50W, for 1-4 fixtures	0-10VEIdoLED SOLOdrive 100W, for 1-8 fixtures	Outer casing (required, order separately)

Orma_QI | Drive-over spotlight | powerLED 3W 350 mA | stainless steel




type		color			optic	
Steel	CRI 80	E96101	2700 K	408 lm	M	15° 15
			3000 K	435 lm	W	30° 30
			4000 K	465 lm	N	60° 60

power supply options (remote only)



ECO30W-350	SOLO50W-350	SOLO100W-350	E98057
0-10V EIdoLED ECOdrive 30W, for 1-5 fixtures	0-10V EIdoLED SOLOdrive 50W, for 1-10 fixtures	0-10VEIdoLED SOLOdrive 100W, for 1-20 fixtures	Outer casing (required, order separately)

Orma_QI | Drive-over spotlight | powerLED 6W 350 mA | stainless steel



type		color			optic	
Steel	CRI 80	E93992	2700 K	816 lm	M	8° 08
			3000 K	870 lm	W	30° 30
			4000 K	930 lm	N	60° 60
						Diff. 00

power supply options (remote only)



ECO30W-350	SOLO50W-350	SOLO100W-350	E98399
0-10V EIdoLED ECOdrive 30W, for 1-2 fixtures	0-10V EIdoLED SOLOdrive 50W, for 1-4 fixtures	0-10VEIdoLED SOLOdrive 100W, for 1-8 fixtures	Outer casing (required, order separately)

Orma | Outer-casing



type	Ø in	h. in	suitable for	
PVC	4.2	2.6	Orma 6W	E98399