

Suelo

inter•lux



This drive-over uplight, offering directional and non-directional emissions, is available in several versions with many different finishes, optics and shapes and features **high energy efficiency** and **maximum external protection**. Suelo is visual comfort, performance and the reliability of the Aqua-Stop system.

Passive heat dissipation

Aluminum dissipating casing

Light management

Protective shade with black silk-screened pattern along the edge for glare reduction

Sturdy appearance

Sturdy flange available in three different material and finish versions

Suelo_R




	body		driver	power	size	optics
Suelo_R	Aluminum			8W	Ø 4.7 in	30° - 50° - 60° - Asymmetric
				13W 25W	Ø 7.9 in Ø 11.4 in	5° - 15° - 30° - 60° - Diffused - Asymmetric
Suelo_RJ	Aluminum			8W	Ø 4.7 in	15° - 30° - 60°
				13W 25W	Ø 7.9 in Ø 11.4 in	
Suelo_RI	Steel flange			13W 20W	Ø 7.1 in Ø 12 in	15° - 30° - 60° - Diffused - Asymmetric
Suelo_RJI	Steel flange			13W 20W	Ø 7.1 in Ø 12 in	15° - 30° - 60°

Suelo_Q



	body		driver	power	size	optics
Suelo_Q	Aluminum			3W 6W	Ø 2.8 in Ø 4.7 in	30° - 50° - 70° - Diffused 10° - 30° - 50° - 120° - Diffused
Suelo_QJ	Aluminum			6W	Ø 4.7 in	10° - 30° - 50° - 120°
Suelo_QI	AISI 316L			3W	Ø 2.8 in	30° - 50° - 70° - Diffused
				6W	Ø 4.7 in	10° - 30° - 50° - 120° - Diffused
Suelo_QJI	AISI 316L			6W	Ø 4.7 in	10° - 30° - 50° - 120°

Suelo_R | Drive-over spotlight | powerLED 8W 630 mA




type			color			optic	
Grey	CRI 80	E93997	2700 K	610 lm	M	15°	15
Chrome	CRI 80	E93996	3000 K	644 lm	W	30°	30
Steel	CRI 80	E93998	4000 K	711 lm	N	60°	60
						Asym.	07

power supply options (remote only)



ECO30W-630	SOLO50W-630	SOLO100W-630	E98121
0-10V EldoLED ECOdrive 30W, for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W, for 1-4 fixtures	0-10VEldoLED SOLOdrive 100W, for 1-8 fixtures	Outer casing (required, order separately)

Suelo_RJ | Drive-over spotlight | powerLED 8W 630 mA | tiltable beam



type			color			optic	
Grey	CRI 80	E93957	2700 K	610 lm	M	15°	15
Chrome	CRI 80	E93956	3000 K	644 lm	W	30°	30
Steel	CRI 80	E93958	4000 K	711 lm	N	60°	60


power supply options (remote only)



ECO30W-630	SOLO50W-630	SOLO100W-630	E98121
0-10V EldoLED ECOdrive 30W, for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W, for 1-4 fixtures	0-10VEldoLED SOLOdrive 100W, for 1-8 fixtures	Outer casing (required, order separately)



Suelo_R | Drive-over spotlight | powerLED 13W 350 mA



type		color			optic	
Grey	CRI 80	E96085				
		2700 K	1243 lm	M	15°	15
		3000 K	1338 lm	W	30°	30
		4000 K	1434 lm	N	60°	60
					Diff.	00




power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350	E84933
0-10V EIdoLED ECOdrive 30W, for 1-3 fixtures	0-10V EIdoLED SOLOdrive 50W, for 1-4 fixtures	0-10VEIdoLED SOLOdrive 100W, for 1-8 fixtures	Outer casing (required, order separately)



Suelo_RI | Drive-over spotlight | powerLED 13W 350 mA | stainless steel



type		color			optic	
Steel	CRI 80	E96083				
		2700 K	1243 lm	M	15°	15
		3000 K	1338 lm	W	30°	30
		4000 K	1434 lm	N	60°	60
					Diff.	00




power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350	E84933
0-10V EIdoLED ECOdrive 30W, for 1-3 fixtures	0-10V EIdoLED SOLOdrive 50W, for 1-4 fixtures	0-10VEIdoLED SOLOdrive 100W, for 1-8 fixtures	Outer casing (required, order separately)



Suelo_R | Walk-over spotlight | arrayLED 13W 350 mA



type		color			optic	
Grey	CRI 80	E95799				
		2700 K	1743 lm	M	Asym.	07
		3000 K	1863 lm	W		
		4000 K	1863 lm	N		




power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350	E84932
0-10V EIdoLED ECOdrive 30W, for 1-3 fixtures	0-10V EIdoLED SOLOdrive 50W, for 1-4 fixtures	0-10VEIdoLED SOLOdrive 100W, for 1-8 fixtures	Outer casing (required, order separately)



Suelo_RI | Walk-over spotlight | arrayLED 13W 350 mA | stainless steel



type

Steel CRI 80 **E95779**

color

2700 K	1743 lm	M
3000 K	1863 lm	W
4000 K	1863 lm	N

optic

Asym. **07**

power supply options (remote only)



ECO30W-350

0-10V EidoLED
ECOdrive 30W,
for 1-3 fixtures

SOLO50W-350

0-10V EidoLED
SOLOdrive 50W,
for 1-4 fixtures


SOLO100W-350

0-10VEidoLED
SOLOdrive 100W,
for 1-8 fixtures

E84932

Outer casing
(required, order
separately)

Suelo_RI | Drive-over spotlight | arrayLED 20W 580 mA | stainless steel



type

Steel CRI 80 **E96917**

color

2700 K	2714 lm	M
3000 K	2900 lm	W
4000 K	2900 lm	N

optic

15°	15
30°	30
60°	60
Asym.	07
Diff.	00

power supply options (remote only)



ECO30W-580

0-10V EidoLED
ECOdrive 30W,
for 1-3 fixtures

SOLO50W-580

0-10V EidoLED
SOLOdrive 50W,
for 1-4 fixtures


SOLO100W-580

0-10VEidoLED
SOLOdrive 100W,
for 1-8 fixtures

E98353

Outer casing
(required, order
separately)

Suelo_R | Drive-over spotlight | arrayLED 25W 720 mA



type

Grey CRI 80 **E96087**

color

2700 K	3400 lm	M
3000 K	3637 lm	W
4000 K	3909 lm	N

optic

15°	15
30°	30
60°	60
Asym.	07
Diff.	00

power supply options (remote only)



ECO30W-720

0-10V EidoLED
ECOdrive 30W,
for 1-3 fixtures

SOLO50W-720


0-10V EidoLED
SOLOdrive 50W,
for 1-4 fixtures

SOLO100W-720

0-10VEidoLED
SOLOdrive 100W,
for 1-8 fixtures

E98353


Outer casing
(required, order
separately)



type			color			optic	
Grey	CRI 80	E960862	2700 K	1243 lm	M	15°	15
			3000 K	1338 lm	W	30°	30
			4000 K	1434 lm	N	60°	60

ECO30W-350	SOL050W-350	SOL0100W-350	E84933
0-10V EidoLED ECODrive 30W, for 1-3 fixtures	0-10V EidoLED SOLODrive 50W, for 1-4 fixtures	0-10VEidoLED SOLODrive 100W, for 1-8 fixtures	Outer casing (required, order separately)


Suelo_RJI | Drive-over spotlight | powerLED 13W 350 mA



type		color			optic	
Steel	CRI 80	E96084	2700 K	1243 lm	M	15°
			3000 K	1338 lm	W	30°
			4000 K	1434 lm	N	60°

ECO30W-350	SOL050W-350	SOL0100W-350	E84933
0-10V EidoLED ECOdrive 30W, for 1-3 fixtures	0-10V EidoLED SOLdrive 50W, for 1-4 fixtures	0-10VEidoLED SOLdrive 100W, for 1-8 fixtures	Outer casing (required, order separately)


Suelo_RJ | Drive-over spotlight | arrayLED 25W 720 mA



type			color			optic	
Grey	CRI 80	E96088	2700 K	3400 lm	M	15°	15
			3000 K	3637 lm	W	30°	30
			4000 K	3909 lm	N	60°	60

ECO30W-720	SOLO50W-720	SOLO100W-720	E98353
0-10V EIdoLED ECOdrive 30W, for 1-3 fixtures	0-10V EIdoLED SOLOdrive 50W, for 1-4 fixtures	0-10VEIdoLED SOLOdrive 100W, for 1-8 fixtures	Outer casing (required, order separately)


Suelo_RJI | Drive-over spotlight | arrayLED 20W 580 mA



type	color	optic
Steel	CRI 80	E96918
	2700 K	2714 lm
	3000 K	2900 lm
	4000 K	2900 lm

ECO30W-580	SOLO50W-580	SOLO100W-580	E98353
0-10V EidoLED ECOdrive 30W, for 1-3 fixtures	0-10V EidoLED SOLOdrive 50W, for 1-4 fixtures	0-10VEidoLED SOLOdrive 100W, for 1-8 fixtures	Outer casing (required, order separately)

Suelo_R | Drive-over spotlight | powerLED 13W 350 mA



type			color			optic	
Steel	CRI 80	E97366	2700 K	1243 lm	M	5°	05
			3000 K	1338 lm	W		
			4000 K	1434 lm	N		

power supply options (remote only)



ECO30W-630	SOLO50W-630	SOLO100W-630	E84932
0-10V EidoLED ECOdrive 30W, for 1-3 fixtures	0-10V EidoLED SOLOdrive 50W, for 1-4 fixtures	0-10V EidoLED SOLOdrive 100W, for 1-8 fixtures	Outer casing (required, order separately)



The innovative narrow optics, slightly tapered, was especially designed to illuminate columns and tall plants.



Suelo_Q | Drive-over spotlight | powerLED 8W 630 mA





type			color			optic	
Grey	CRI 80	E94000	2700 K	610 lm	M	15°	15
Chrome	CRI 80	E93999	3000 K	644 lm	W	30°	30
Steel	CRI 80	E94001	4000 K	711 lm	N	60°	60
						Asym.	07

power supply options (remote only)



ECO30W-630 0-10V EldoLED ECOdrive 30W, for 1-3 fixtures	SOLO50W-630 0-10V EldoLED SOLOdrive 50W, for 1-4 fixtures	SOLO100W-630 0-10VEldoLED SOLOdrive 100W, for 1-8 fixtures	E98121 Outer casing (required, order separately)
---	---	--	--

Suelo_QJ | Drive-over spotlight | powerLED 8W 630 mA



type			color			optic	
Grey	CRI 80	E93960	2700 K	610 lm	M	15°	15
Chrome	CRI 80	E93959	3000 K	644 lm	W	30°	30
Steel	CRI 80	E93961	4000 K	711 lm	N	60°	60
						Asym.	07

power supply options (remote only)




ECO30W-630 0-10V EldoLED ECOdrive 30W, for 1-3 fixtures	SOLO50W-630 0-10V EldoLED SOLOdrive 50W, for 1-4 fixtures	SOLO100W-630 0-10VEldoLED SOLOdrive 100W, for 1-8 fixtures	E98121 Outer casing (required, order separately)
---	---	--	--

Suelo | In-ground outer-casing



type	Ø inch	h. inch	suitable for	
PVC	6.7	9.4	Suelo_R 13W optics 07	E84932

Suelo | In-ground outer-casing



type	Ø inch	h. inch	suitable for	
PVC	6.7	6.1	Suelo_R 13W optics 15, 30, 60, 00 Suelo_RJ 13W	E84933

Suelo | In-ground outer-casing



type	Ø inch	h. inch	suitable for	
PVC	10.6	10.2	Suelo_R 30W Suelo_RJ 30W	E98353

Suelo | In-ground outer-casing



type	Ø inch	h. inch	suitable for	
PVC	4.3	5.5	Suelo (no driver)	E98121

Suelo | In-ground outer-casing



type	Ø inch	h. inch	suitable for	
PVC	4.3	8.7	Suelo (with driver)	E98122