



**General:** Loop66 was designed to create very narrow lines of light on building facades in a symmetrical, four-way distribution.

**Fixture Body:** Open-pore Anodized and Powder Coated Die-Cast Aluminum.

**Diffuser:** Aluminum diffuser with coating treatment.

**Mounting details:** Surface mounted.

**Dimensions/Weight:** 4.4" (3.53 lbs)

**Driver:** Remote, Constant Current 120-277V Dimmable 0-10V.

**Wattage:** 25W (4.4")

**Cable:** Fixture comes with 3.28' of power cable.

**Safety features:** Fixture is equipped with Electrostatic discharge protection and Surge Protection (4 KV).

**IP rating:** IP66 for protection against dust and powerful water jets from any angle.

**IK rating:** IK 05

**ETL Certification:** ETL, wet location

**Optics:** Fixed with Narrow Spot Beam.

**Color temperatures:** 2700K – 3000K – 4000K.

**CRI:** 80+

**Lumen Maintenance:** L70 projections tested at Tj 65° C and Ta 25°.

**Warranty:** 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



4.4" (25W)


Delivered Lumens*	4.4"
NSP	1248

\*Values shown for 3000K

Ordering Information							
Product	Trim/Film	Type	Diameter	Wattage/Operation	Color Temp	Optic	Driver (Required) <sup>1</sup>
LOO = Loop66	WH = White BL = Black GR = Gray DB = Dark Brown	LE = Light Effects	44 = 4.4" Square	25 CC = 25W / Constant Current (630mA)	27 = 2700K 30 = 3000K 40 = 4000K	NSP = Narrow Spot	SOLO50W-630 SOLO100W-630

<sup>1</sup> See page 2

## 4.4" 25W CC



## DRIVER OPTIONS (pick one)

### C.C. Power supply options (remote only)

**SOLO50W-630**  
0-10V EidoLED  
SOLOdrive 50W  
for 1 fixture

**SOLO100W-630**  
0-10V EidoLED  
SOLOdrive 100W  
for 1-3 fixtures