



Orma Flush Trim | Fixed | 2.1" Ø



C.C. 4W DC - 350mA		Cct	lm S - D	Optic
Steel/Alu	E81181	M 2700	490 - 272	15 Spot (22°)
		W 3000	490 - 272	30 Flood (29°)
		N 4000	529 - 294	60 W.Flood (48°)
				25 Elliptical -

HC		Cct	lm S - D	Optic
Steel/Alu	E81182	M 2700	490 - 187	15 Spot (20°)
		W 3000	490 - 187	30 Flood (25°)
		N 4000	529 - 202	60 Flood (37°)

DL		Cct	lm S - D	Optic
Steel/Alu	E81183	M 2700	490 - 194	15 Spot (22°)
		W 3000	490 - 194	30 Flood (30°)
		N 4000	529 - 209	60 W.Flood (55°)

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1-3 fixtu es	0-10V EldoLED SOLOdrive 50W for 1-6 fixtu es	0-10V EldoLED SOLOdrive 100W for 1-12 fixtu es





C.V. 5W DC - 24 VDC		Cct	lm S - D	Optic
Steel/Alu	E81184	M 2700	490 - 272	15 Spot (22°)
		W 3000	490 - 272	30 Flood (29°)
		N 4000	529 - 294	60 W.Flood (48°)
				25 Elliptical -

HC		Cct	lm S - D	Optic
Steel/Alu	E81185	M 2700	490 - 187	15 Spot (20°)
		W 3000	490 - 187	30 Flood (25°)
		N 4000	529 - 202	60 Flood (37°)

DL		Cct	lm S - D	Optic
Steel/Alu	E81186	M 2700	490 - 194	15 Spot (22°)
		W 3000	490 - 194	30 Flood (30°)
		N 4000	529 - 209	60 W.Flood (55°)



Power supply options (remote only)

OT96-D010	OT96-JBX
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure	Osram, Non-dim 24VDC, 120-277VAC, Wet location



RTG E81181W15 / E81181W30

Orma Flush Trim | Fixed | 3.3" Ø



C.C. - 8W DC - 220 mA		Cct	lm S - D	Optic
Steel/Alu	E81187	M 2700	1080 - 858	15 Spot (15°)
		W 3000	1126 - 894	30 Flood (31°)
		N 4000	1188 - 944	60 W.Flood (61°)

HC		Cct	lm S - D	Optic
Steel/Alu	E81188	M 2700	1080 - 619	15 Spot (15°)
		W 3000	1126 - 646	30 Flood (27°)
		N 4000	1188 - 681	60 W.Flood (49°)

DL		Cct	lm S - D	Optic
Steel/Alu	E81189	M 2700	1080 - 576	15 Spot (16°)
		W 3000	1126 - 600	30 Flood (29°)
		N 4000	1188 - 634	60 W.Flood (53°)

Power supply options (remote only)

ECO30W-220	SOLO50W-220	SOLO100W-220
0-10V EldoLED ECOdrive 30W for 1 fixtu e	0-10V EldoLED SOLOdrive 50W for 1-2 fixtu es	0-10V EldoLED SOLOdrive 100W for 1-4 fixtu es

C.V. 9W DC - 24 VDC		Cct	lm S - D	Optic
Steel/Alu	E81190	M 2700	1193 - 955	15 Spot (15°)
		W 3000	1244 - 997	30 Flood (31°)
		N 4000	1313 - 1052	60 W.Flood (61°)

HC		Cct	lm S - D	Optic
Steel/Alu	E81191	M 2700	1193 - 687	15 Spot (15°)
		W 3000	1244 - 716	30 Flood (27°)
		N 4000	1313 - 756	60 W.Flood (49°)

DL		Cct	lm S - D	Optic
Steel/Alu	E81192	M 2700	1193 - 639	15 Spot (16°)
		W 3000	1244 - 667	30 Flood (29°)
		N 4000	1313 - 704	60 W.Flood (53°)



Power supply options (remote only)

OT96-D010	OT96-JBX
Osram, 10% 0-10V dim, 96W, 24VDC, 120-277VAC, supplied in a Dry location enclosure	Osram, Non-dim 24VDC, 120-277VAC, Wet location

technical information

NOTE: Using a Square Trim casing or a Vandalproof Round casing will make the fixture Semi-Flush.
 Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
 Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min.
 NOT suitable for submersible installations.
 Inter-lux reserves the right to make technical changes without notice.

Orma Flush Trim | Fixed | 4.9" Ø



C.C. 12W DC - 350mA	Cct	lm S - D	Optic
Steel/Alu E81193	M 2700	1724 - 1379	15 Spot (14°)
	W 3000	1724 - 1379	30 Flood (31°)
	N 4000	1854 - 1485	60 W.Flood (60°)

HC	Cct	lm S - D	Optic
Steel/Alu E81194	M 2700	1724 - 981	15 Spot (14°)
	W 3000	1724 - 981	30 Flood (28°)
	N 4000	1854 - 1055	60 W.Flood (49°)

DL	Cct	lm S - D	Optic
Steel/Alu E81195	M 2700	1724 - 1094	15 Spot (14°)
	W 3000	1724 - 1094	30 Flood (30°)
	N 4000	1854 - 1178	60 W.Flood (52°)

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W for 1 fixture	0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	0-10V EldoLED SOLOdrive 100W for 1-4 fixtures

E99652

Concrete
Casing
PVC




E99564*

Round Vandal
Resistant Casing
PVC



E99857*

Square Vandal
Resistant Casing
PVC



E83253

Tile
casing
PVC



NOTE: Using a Square Trim casing or a Vandalproof Round casing will make the fixture Semi-Flush.
 Delivered lumens shown are for 35 Flood, 30 Flood or 00 General optic and without glare control (HC or DL).
 Rated for temporary submersion up to 15' depth for up to a maximum of 1 hr and 30 min.
 NOT suitable for submersible installations.
 Inter-lux reserves the right to make technical changes without notice.

