

suelo



The real strength of the Suelo range is its sheer variety. Efficient, versatile, and safe, with a hardwearing flange, a black silkscreened protective screen for increased visual comfort, and the AquaStop® patented protection system, Suelo has been completely redesigned, with drive-over uplights offering unmistakable Linea Light Group quality.

Materials

Aluminum body

AISI 316L stainless steel flange



suelo range



	2 W	4.2 W	7.2 W	13 W	30 W
Suelo_R ○	Ø 1.2 in	Ø 2.5 in	Ø 3.6 in	-	-
Suelo_RJ ○	-	Ø 2.5 in	Ø 3.6 in	-	-
Suelo_RX ○	-	-	Ø 4.7 in	Ø 6.7 in	Ø 9.1 in
Suelo_RXJ ○	-	-	Ø 4.7 in	Ø 6.7 in	-
SueloPRO_R ○	Ø 1.4 in	Ø 2.5 in	Ø 3.6 in	-	-
SueloPRO_RX ○	Ø 2 in	-	Ø 4.7 in	Ø 6.7 in	-
Suelo_RX Double ○	-	-	-	Ø 6.7 in (12W)	Ø 9.1 in (24W)
Suelo Telescopic ○	-	-	-	Ø 7.9 in	Ø 7.9 in (25W)
Options	PRO_R, PRO_RX	_R, PRO_R PRO_R	_R, _RX, PRO_R, PRO_RX PRO_R, PRO_RX	_RX, PRO_R, PRO_RX _RX, PRO_RX	_RX _RX
CRI 80	2700K 3000K 4000K	2700K 3000K 4000K	2700K 3000K 4000K RGBW (_RX)	2700K 3000K 4000K RGBW (_RX)	2700K 3000K 4000K RGBW (_RX)
Standard	08° 15° 30° 60° 90° Diffused	10° 20° 30° 60° 90° Diffused Elliptic Asymmetric	06° 15° 20° 30° 60° 105° Diffused Elliptic Asymmetric	06° 15° 30° 35° 45° 60° Diffused Asymmetric	06° 15° 30° 35° 60° Asymmetric
Optics					
Pro	15° 30° 60° Elliptic Diffused	20° 30° 50°	06° 15° 30° 60°	15° 30° 60° Asymmetric	-
Driver	Remote	Remote	Remote	Remote 120-277V On/Off (PRO_RX, _RX Double)	Remote 120-277V On/Off (_RX, _RX Double)
Current	C.C. C.V.	C.C. C.V.	C.C. C.V.	C.C.	C.C.

The range


The Suelo family offers a variety of solutions for every design need: fixed and tiltable versions, small-flanged flush-mount uplights. There are PRO models with recessed optics. RGBW engines and beam control filters are also available. All models have the exclusive AquaStop® protection systems, and there are versions with 24V converters.



Visual comfort

Suelo fixtures with honeycomb louver, screen secondary light and reduce glare, maintaining a high-quality light. A darklight filter directs the illumination onto the intended part of the wall by sectioning part of the beam, and prevents glare even close to the source.

For full beam control and a drastically reduced glare risk, choose the Suelo PRO versions, in which the recessed source increases the screening angle, totally skimming off the secondary flow to give a cleaner, more concentrated and efficient light.



Suelo PRO



Suelo + Honeycomb




Suelo + Darklight

Performance and control


Six outputs to choose from, ranging from 1 to 30 watts, three color temperatures including warm light at 2700 and 3000K, and daylight at 4000K.

The uniquely wide spectrum of optics includes an elliptical, a wall wash for high, narrow walls, and an asymmetric version that gives an even, homogeneous wash.


Spot



Flood



Diffused



Asymmetric



Suelo_R | Up-Light | powerLED | Wet location | Driver remote | Walk over | 2W 630mA



Chrome **E93141**

2700K	219 lm	M	Narrow Spot	08
3000K	233 lm	W	Spot	15
4000K	249 lm	N	Medium Flood	30
			Flood	60
			Wide Flood	12
			General	00

Power supply options (remote only)

ECO30W-630	SOLO50W-630	SOLO100W-630
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-16 fixtures	0-10V EldoLED SOLOdrive 100W for 1-32 fixtures


Recessed casings




technical
information

Suelo_R | Up-Light | powerLED | Wet location | Driver remote | Driver over | 4.2W

E80443 / E80444 / E80445 / E80446




Recessed casings




E84936
Outer casing for ground-mounting installation


E81089 / E81090



Recessed casings



E84935
Outer casing for ground-mounting installation



C.C. - 350mA

Steel/Alu	E80443	2700K	490 lm	M	Spot	10
		3000K	490 lm	W	Medium Flood	20
		4000K	529 lm	N	Medium Flood	30
					Flood	60
					Elliptic	88
					Wide Flood	12
					General	00

Steel/Alu	E81089	2700K	490 lm	M	Asymmetric	07
		3000K	490 lm	W		
		4000K	529 lm	N		

HC	Steel/Alu	E80444	2700K	490 lm	M	Medium Flood	20
			3000K	490 lm	W	Medium Flood	30
			4000K	529 lm	N	Flood	60

Power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED EC0drive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-6 fixtures	0-10V EldoLED SOLOdrive 100W for 1-12 fixtures

C.V. - 24V

Steel/Alu	E80445	2700K	490 lm	M	Spot	10
		3000K	490 lm	W	Medium Flood	20
		4000K	529 lm	N	Medium Flood	30
					Flood	60
					Elliptic	88
					Wide Flood	12
					General	00

Steel/Alu	E81090	2700K	490 lm	M	Asymmetric	07
		3000K	490 lm	W		
		4000K	529 lm	N		

HC	Steel/Alu	E80446	2700K	490 lm	M	Medium Flood	20
			3000K	490 lm	W	Medium Flood	30
			4000K	529 lm	N	Flood	60



Power supply options (remote only)

OT96-D010	OT96-JBX
Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location	Osram, Non-dim 24V DC, 120-277VAC, Wet location

technical information



Suelo_R | Up-Light | powerLED | Wet location | Driver remote | Driver over | 7.2W



C.C. - 7.2W - 630mA

Steel/Alu	E80546	2700K	877 lm	M	Narrow Spot	06
		3000K	945 lm	W	Spot	15
		4000K	1013 lm	N	Medium Flood	30
					Flood	60
					Elliptic	88
					Wide Flood	12
					General	00
					Asymmetric	07



Steel/Alu	E80547	2700K	877 lm	M	Narrow Spot	06
		3000K	945 lm	W	Spot	15
		4000K	1013 lm	N	Medium Flood	30
					Flood	60

Power supply options (remote only)

ECO30W-630	SOLO50W-630	SOLO100W-630
0-10V EldoLED ECOdrive 30W for 1-3 fixtures	0-10V EldoLED SOLOdrive 50W for 1-4 fixtures	0-10V EldoLED SOLOdrive 100W for 1-8 fixtures

C.V. - 7.2W - 24V

Steel/Alu	E80550	2700K	877 lm	M	Narrow Spot	06
		3000K	945 lm	W	Spot	15
		4000K	1013 lm	N	Medium Flood	30
					Flood	60
					Elliptic	88
					Wide Flood	12
					General	00
					Asymmetric	07



Steel/Alu	E80551	2700K	877 lm	M	Narrow Spot	06
		3000K	945 lm	W	Spot	15
		4000K	1013 lm	N	Medium Flood	30
					Flood	60

Power supply options (remote only)

OT96-D010	OT96-JBX
Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location	Osram, Non-dim 24V DC, 120- 277VAC, Wet location



RGBW - 8W - 630mA


Steel/Alu	E81717	RGBW natural white	Q	Narrow Spot	06
		RGBW warm white	V	Medium Flood	15
				Flood	45

Power supply options (remote only)

PWR50W-630

DMX driver, EldoLED POWERdrive 50W
Factory pre-programmed or RDM programmable, DMX
control not included/Ordered separately
50W for 1-4 Fixtures

Recessed casings



E99680
Outer casing for
ground-mounting
installation

technical
information