


PAX-C...-NSP

Delivered Lumens - Narrow Spot

		Length [Wattage]	
		23 [8]	45 [19]
CCT	27	864	1728
	30	920	1841
	35	920	1841
	40	973	1948
Polar Plot / Cone Of Light Multiplier			
		23 [8]	45 [19]
		0.50	1.00



Beam Angle (0-180) = 16.7
Beam Angle (90-270) = 26.5


CONE OF LIGHT - 45" 19W 3000K NARROW SPOT PAX-C-45-19-...-30-NSP-...*

Throw Distance [Ft]	Illuminance [Fc]	Beam Diameter [Ft]
20	19	5.9
18	24	5.3
16	30	4.7
14	40	4.1
12	54	3.5
10	78	2.9
8	122	2.4
6	216	1.8
4	486	1.2
2	1944	0.6

PAX-C...-SP

Delivered Lumens - Spot

		Length [Wattage]	
		23 [8]	45 [19]
CCT	27	865	1730
	30	922	1844
	35	922	1844
	40	975	1951
Polar Plot / Cone Of Light Multiplier			
		23 [8]	45 [19]
		0.50	1.00



Beam Angle (0-180) = 25.8
Beam Angle (90-270) = 28.9


CONE OF LIGHT - 45" 19W 3000K SPOT PAX-C-45-19-...-30-SP-...*

Throw Distance [Ft]	Illuminance [Fc]	Beam Diameter [Ft]
20	16	9.2
18	19	8.2
16	24	7.3
14	32	6.4
12	43	5.5
10	62	4.6
8	97	3.7
6	172	2.7
4	388	1.8
2	1550	0.9

PAX-C...-FL

Delivered Lumens - Flood

		Length [Wattage]	
		23 [8]	45 [19]
CCT	27	861	1704
	30	908	1816
	35	908	1816
	40	960	1922
Polar Plot / Cone Of Light Multiplier			
		23 [8]	45 [19]
		0.50	1.00



Beam Angle (0-180) = 28.7
Beam Angle (90-270) = 34.8

CONE OF LIGHT - 45" 19W 3000K FLOOD PAX-C-45-19-...-30-FL-...*


Throw Distance [Ft]	Illuminance [Fc]	Beam Diameter [Ft]
20	16	9.2
18	19	8.2
16	24	7.3
14	32	6.4
12	43	5.5
10	62	4.6
8	97	3.7
6	172	2.7
4	388	1.8
2	1550	0.9

* Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.

PAX-C...-WFL

Delivered Lumens - Wide Flood

Length [Wattage]		
23 [8]		
45 [19]		
CCT		
27	850	1701
30	906	1811
35	906	1811
40	958	1917
Polar Plot / Cone Of Light Multiplier		
23 [8]		
45 [19]		
	0.50	1.00



Beam Angle (0-180) = 46.3
Beam Angle (90-270) = 51.5


CONE OF LIGHT - 45" 19W 3000K WIDE FLOOD PAX-C-45-19-...-30-WFL-...*

Throw Distance [Ft]	Illuminance [Fc]	Beam Diameter [Ft]
20	19	5.9
18	24	5.3
16	30	4.7
14	40	4.1
12	54	3.5
10	78	2.9
8	122	2.4
6	216	1.8
4	486	1.2
2	1944	0.6

PAX-C...-EL

Delivered Lumens - Elliptical

Length [Wattage]		
23 [8]		
45 [19]		
CCT		
27	855	1699
30	905	1811
35	905	1811
40	958	1916
Polar Plot / Cone Of Light Multiplier		
23 [8]		
45 [19]		
	0.50	1.00



Beam Angle (0-180) = 31.0
Beam Angle (90-270) = 48.0

CONE OF LIGHT - 45" 19W 3000K ELLIPTICAL PAX-C-45-19-...-30-EL-...*

Throw Distance [Ft]	Illuminance [Fc]	Beam Diameter [Ft]
20	16	9.2
18	19	8.2
16	24	7.3
14	32	6.4
12	43	5.5
10	62	4.6
8	97	3.7
6	172	2.7
4	388	1.8
2	1550	0.9