inter•lux



General: Paseo is a complete range of compact linear LED fixtures suitable to illuminate outdoor architectural elements or used as pathway lighting thanks to its Opaline version. Its 0.9" width makes Paseo one of the slimmest and most attractive products on the market. Paseo's versatility is given by multiple mounting accessories that allow to install the same fixture recessed in ground, wall, ceiling or surface mounted applications.

Fixture Body: Clear, UV resistant Polycarbonate.

Mounting/Housing: Multiple mounting Housings available. Anodized Aluminum recessed Housings for in-ground, wall or ceiling mount, with or without frame. Adjustable brackets for cove installation. Refer to accessory page for specific options.

Drive-over: Walk-Over only.

Dimensions/Weight: 22.7" (0.86 lbs) – 45.4" (1.96 lbs)

Driver: Integral, 120V only. Available in dimmable 0-10V 10% (ID), or Non-dim (IND).
Wattages: 7.7W (22.7") – 19.4W (45.4")
Cable: Fixture comes with 0.82' of cable (Power cable required, ordered separately).
Safety features: Built-in Aquastop® (Anti-wicking) and TCS® (Over tension and electrical discharge protection) systems.

IP rating: IP67 for temporary flooding up to 3.28' depth for up to a maximum of 30 mins. **IK rating:** IK 08 **ETL Certification:** ETL, wet location

Optics: Fixed. Available in Narrow Spot, Spot, Flood, Wide Flood or Elliptic. **Color temperatures:** 2700K – 3000K – 4000K. **CRI:** 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°. **Warranty:** 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



22.7" (7.7W) 45.4" (19.4W)

Ordering Information								
PA	X	С						
Product	Power	Туре	Length	Wattage/operation	Color Temp	Optic	+	Cables ¹
PA = Paseo	X = Extra Power	C = Clear	23 = 22.7"	8 IND = 7.7W / Integral 120V (Non-Dim) 8 ID = 7.7W / Integral 120V (0-10V Dim)	27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	NSP = Narrow Spot SP = Spot FL = Flood WFL = Wide Flood EL = Elliptic/Grazer	E83043 E83044 E83045 E83046	
		45 = 45.4"	19 IND = 19.4W / Integral 120V (Non-dim) 19 ID = 19.4W / Integral 120V (0-10V dim)			E83047 ID E89189 E98994 E98993 E89187		

¹See page 2




Housings & fixing systems Order separately, see pages 3-6






inter•lux

22.7" 8W IND/ID



45.4" 19W IND/ID



IND/ID Power Feed Cables (one power feed ¹ requ	ired per run / 10x fixtures max. per run)
--	---

E830431

59" line volt.196" lipower feed cablepowerF 3 pin M12F 3 pin

E83044¹ 196" line volt. power feed cable F 3 pin M12

ID Dimming Feed Cable (one power feed¹ and one 0-10V dimming² cable required per run / 10x fixtures max. per run)

E89189 ²	E98994 ²
196.9" 0-10V feed cable M 5 pin M12 (ID only)	196.9" 0-10V feed cable M 5 pin M12 + M 5 pin XLR (ID only)

Extension Cables (one power³ and one 0-10V dimming⁴ extension cable required in between fixtures for non-continuous runs)


E83045 ³	E83046 ³	E83047 ³	E989934	E891874
39" line volt. power extension cable M+F 3 pin M12	196" line volt. power extension cable M+F3 pin M12	393" line volt. power extension cable M+F 4 pin M12	196.9" 0-10V extension cable M+F 5 pin M12 (ID only)	393" 0-10V extension cable M+F 5 pin M12 (ID only)






inter•lux

Paseo | Floor with trim outer casing



Lower casing



0.9

Outer casing	Cable gland
E98355	E98471
E98430	E98472
E98356	E98473
E98357	E98474
	E98355 E98430 E98356




Installation accessories




Paseo | Floor trimless / Surface mount outer casing








0.9





Installation accessories








inter•lux

Paseo | Ceiling with trim outer housing





20.2 in x Paseo 20.2 in	E98374
22.7 in x Paseo 22.7 in	E98435
45.4 in x Paseo 45.4 in	E98375
57.2 in x Paseo 57.2 in	E98376
	20.2 in x Paseo 20.2 in 22.7 in x Paseo 22.7 in 45.4 in x Paseo 45.4 in 57.2 in x Paseo 57.2 in




Installation accessories



Paseo | Ceiling trimless outer housing





Anod. AL 20.2 in x Paseo 20.2 in	E98367
Anod. Al. 22.7 in x Paseo 22.7 in	E98434
Anod. Al. 45.4 in x Paseo 45.4 in	E98368
Anod. Al. 57.2 in x Paseo 57.2 in	E98369



Installation accessories









inter•lux

Paseo | Surface 3D outer housing





Anod. Al.	20.2 in x Paseo 20.2 in	E98836
Anod. Al.	22.7 in x Paseo 22.7 in	E98839
Anod. Al.	45.4 in x Paseo 45.4 in	E98837
Anod. Al.	57.2 in x Paseo 57.2 in	E98838



Installation accessories




Paseo | Surface adjustable outer housing



2.9		
	3.3	

Anod. Al. 20.4 in x Paseo 20.2 in	E98842
Anod. Al. 22.9 in x Paseo 22.7 in	E98843
Anod. Al. 45.6 in x Paseo 45.4 in	E98844
Anod. Al. 57.4 in x Paseo 57.2 in	E98845



Installation accessories







inter•lux


Paseo | Adjustable mounting clips





Mounting plate for uneven horizontal surfaces

(ordered separately)



32

0.1

E98771

Pair of fastening clips made of transparent polycarbonate to install the fixture in an even horizontal mounting surface. A directional accessory that allows Paseo tilt movement from + 90° to -90°.


L inches	S	L1 inches	
11.8 in 7.9 in		E98772	
Plate for 20	.2 or 20.7" Pa	seo fixtures	
L inche	S	L1 inches	
37.4 in	33.5 in	E98773	
Plate for45.4 or 57.2" Paseo fixtures			

The plate, without fixing it to the surface, can be used as a mobile support for the adjustable clips and fixture. Clips not included in codes E98772 - E98773 (ordered separately)

Paseo | Extraction key







E98475

The Paseo extraction key (ordered separately) allows its removal from the outer housing. Compatible with all Paseo outer housings.



