



RUB-WH-3D-...-CV-GE...			
Delivered Lumens - Narrow Spot			
		Length [Wattage]	
		39 [3 CV]	197 [3 CV]
CCT	27-	455	2275
	30-	506	2528
	40-	542	2710
		Polar Plot / Cone Of Light Multiplier	
		39 [3 CV]	197 [3 CV]
		1.00	5.00



Beam Angle (0-180) = 114.2
 Beam Angle (90-270) = 133.4

CONE OF LIGHT - 10W/reel 3000K		
General Illumination		
RUB-WH-3D-39-3-CV-30-GE*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Width [Ft]**
20	0	61.8
18	0	55.6
16	1	49.5
14	1	43.3
12	1	37.1
10	2	30.9
8	2	24.7
6	4	18.5
4	10	12.4
2	39	6.2

RUB-CON-3D-...-CV-GE...			
Delivered Lumens - Flood			
		Length [Wattage]	
		39 [3 CV]	197 [3 CV]
CCT	30-	250	1188
			Polar Plot / Cone Of Light Multiplier
			39 [3 CV]
		-	-



Beam Angle (0-180) = 105.8
 Beam Angle (90-270) = 130.2

CONE OF LIGHT - 10W/reel 3000K		
General Illumination		
RUB-CON-3D-39-3-CV-30-GE*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Width [Ft]**
20	0	52.9
18	0	47.6
16	0	42.3
14	0	37.0
12	1	31.7
10	1	26.4
8	1	21.2
6	2	15.9
4	5	10.6
2	21	5.3

*Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.