

20 Linear Under Cabinet

- Under cabinet and task light.
- Available in standard cabinet lengths and custom lengths.
- Mounts with invisible clip or magnet.
- On/off switch at fixture end with 120VAC plug-in driver..
- 90+ CRI, 3 Steps MacAdam delivering excellent color rendering.
- Identical LED technology used throughout all Whitegoods Linears, Coves and Perimeter products deliver consistent quality and performance throughout a project.
- Made in USA.
- 5-year warranty.



Under Cabinet (UC)

Housing Precision extruded aluminum for true dimensions and tolerances
Finishes: white and silver

Integration Invisible screw-mount clip or magnet

Distribution Wide angle illumination

LED Constant Voltage, 90+ CRI, 3 Steps MacAdam
120 nominal lumens/watt average (see spec sheet for delivered lumens)
L70 (TM21 Projected 85C) Static White = 60,000 hours

Lens OD - Opal Diffuser provides even, continuous line of light and general illumination
SD - Satin Clear Diffuser provides high efficiency soft edge beam, general illumination
MPL - Micro-prismatic lens provides lower brightness, general illumination

Driver 120VAC plug-in


Weight 0.5lbs per foot

Operating Temp Suitable for operation in maximum ambient temperature of 35C (95F)

Warranty 5-year Limited (see complete company warranty information)

Certifications ETL and ETL-C for dry and damp location, CE

Voltages 120VAC



Total Length includes 1" for switch.
1" clearance required for cable.

20 Linear Under Cabinet

| Model | Fixation | Pattern | Length | Power ¹ | CRI/CCT ² | Driver | Lens | Finish ³ |
|----------|----------|---------|--------|--------------------|----------------------|--------|-----------------------|---------------------|
| WG-20LUC | MM SC | S | 18 | L | 927 | S | OD (std) SD MPL | W (std) S |
| | | | 24 | M | 930 | | | |
| | | | 30 | H | 935 | | | |
| | | | 36 | | 940 | | | |
| | | | 42 | | | | | |
| 48 | | | | | | | | |

Model

- WG-20LUC = 20 Linear Under Cabinet

Fixation

- MM = Magnetic mounting
- SC = Screw clip

Pattern

- S = Straight run (for other product configurations see 20LDL-SM)

Length

Total length includes 1" for switch, requires 1" clearance for cable

- 18 = 18"
- 24 = 24"
- 30 = 30"
- 36 = 36"
- 42 = 42"
- 48 = 48"

Power¹

- L = 3W/ft low power (24V)
- M = 6W/ft mid power (24V)
- H = 10W/ft high power (24V)

CRI/CCT (90+ CRI)²

- 927 = 2700K
- 930 = 3000K
- 935 = 3500K
- 940 = 4000K

Driver (plug-in)

- S = Standard driver 120 - 240V, 50 - 60 Hz

Lens

- OD = Satin opal diffuser (standard)
- SD = Satin clear diffuser
- MPL = Micro-prismatic lens

Finish³

- W = White, 15% gloss, Tiger Drylac 49/11350 (standard)
- S = Silver, 15% gloss, Tiger Drylac 49/90500

Lenses/Accessories



Opal Diffuser (OD)
Satin Diffuser (SD)
Micro-prismatic Lens (MPL)

Whitegoods reserves the right to change any information without prior notice.

Notes

- 1 Wattage shown is for LED boards only, system wattage varies depending on driver selected.
- 2 See spec page for delivered lumens.
- 3 See Tiger Drylac color chart: inter-lux.com/tiger