


# 20 Linear Under Cabinet




Ordering Information								
Model	Fixation	Pattern	Length	Power <sup>1</sup>	CRI/CCT <sup>2</sup>	Driver	Lens	Finish <sup>3</sup>
WG-20LUC		S				S		
WG-20LUC	MM SC	S	18 24 30 36 42 48	L M H	927 930 935 940	S	OD (std) SD MPL	W (std) S



Total Length includes 1" for switch.  
1" clearance required for cable.

## Lenses/Accessories



## Luminaire

- Under cabinet and task light.
- Multiple lens options for diffuse, high efficiency and low brightness.
- Field replaceable LED boards.
- On / Off switch with 118" cable and plug.
- 90+ CRI, 3 Steps MacAdam delivering excellent color rendering.
- L70 (TM21 Projected 85C) Static White 60,000 hours.
- ETL and ETL-C for dry and damp location.

## Fixation

- MM = Magnetic mounting
- SC = Screw clip

## Pattern

- S = Straight run (for other product configurations see 20LDL-SM)

## Length

(Total length includes 1" for switch, requires 1" clearance for cable)

- 18 = 18"
- 24 = 24"
- 30 = 30"
- 36 = 36"
- 42 = 42"
- 48 = 48"

## Power<sup>1</sup>

- L = 3W/ft low power (24V)
- M = 6W/ft mid power (24V)
- H = 10W/ft high power (24V)

## CRI/CCT (90+ CRI)<sup>2</sup>

- 927 = 2700K
- 930 = 3000K
- 935 = 3500K
- 940 = 4000K

## Driver (plug-in)

- S = Standard driver 120 - 240V, 50 - 60 Hz

## Lens

- OD = Satin opal diffuser (standard)
- SD = Satin clear diffuser
- MPL = Micro-prismatic lens

## Finish<sup>3</sup>

- W = White, 15% gloss, RAL 9010 / Tiger Drylac 009/10120 (standard)
- S = Silver, 15% gloss, RAL 9006 / Tiger Drylac 049/90500

- 1 Wattage shown is for LED boards only, system wattage varies depending on driver selected.
- 2 See photometric data sheet for delivered lumens.
- 3 See Tiger Drylac color chart: [inter-lux.com/tiger](http://inter-lux.com/tiger)