


20 Linear Wash Light Recessed

WG-20LWW...-OD-W Delivered Lumens Per Foot

		Power			
		L [3 W/ft]	M [6 W/ft]	H [10 W/ft]	RGBW [7.6 W/ft]
CCT	927	183	366	640	-
	930	199	398	696	-
	935	236	473	827	-
	940	281	561	982	-
	WD ²	140	291	421	-
	RGBW ³	-	-	-	238
UGR ⁴		32.2	34.7	36.5	-




BEAM ANGLE (0-180) = 106.7
BEAM ANGLE (90-270) = 111.0

ILLUMINANCE - 48" OD H 3500K WG-20LWW...-S-48-H-935...-OD-W...¹

Mounting Height [ft]	Illuminance [fc at max cd]	Beam Width [ft]
2	292	5.4
4	73	10.8
6	32	16.1
8	18	21.5
10	12	26.9
12	8	32.3
14	6	37.7
16	5	43.0
18	4	48.4
20	3	53.8

WG-20LWW...-SD-W Delivered Lumens Per Foot

		Power			
		L [3 W/ft]	M [6 W/ft]	H [10 W/ft]	RGBW [7.6 W/ft]
CCT	927	253	506	886	-
	930	275	550	962	-
	935	326	654	1143	-
	940	388	776	1359	-
	WD ²	194	402	582	-
	RGBW ³	-	-	-	329
UGR ⁴		30.9	33.4	35.2	-




BEAM ANGLE (0-180) = 84.0
BEAM ANGLE (90-270) = 102.2

ILLUMINANCE - 48" SD H 3500K WG-20LWW...-S-48-H-935...-SD-W...¹

Mounting Height [ft]	Illuminance [fc at max cd]	Beam Width [ft]
2	509	3.6
4	127	7.2
6	57	10.8
8	32	14.4
10	20	18.0
12	14	21.6
14	10	25.2
16	8	28.8
18	6	32.4
20	5	36.0

WG-20LWW...-MPL-W Delivered Lumens Per Foot

		Power			
		L [3 W/ft]	M [6 W/ft]	H [10 W/ft]	RGBW [7.6 W/ft]
CCT	927	209	418	732	-
	930	228	455	796	-
	935	270	540	945	-
	940	321	642	1123	-
	WD ²	160	333	481	-
	RGBW ³	-	-	-	272
UGR ⁴		35	37.6	39.4	-



BEAM ANGLE (0-180) = 85.5
BEAM ANGLE (90-270) = 73.0

ILLUMINANCE - 48" MPL H 3500K WG-20LWW...-S-48-H-935...-MPL-W...¹

Mounting Height [ft]	Illuminance [fc at max cd]	Beam Width [ft]
2	477	3.7
4	119	7.4
6	53	11.1
8	30	14.8
10	19	18.5
12	13	22.2
14	10	25.9
16	7	29.6
18	6	33.3
20	5	37.0

Power Multiplier				
	L [3 W/ft]	M [6 W/ft]	H [10 W/ft]	RGBW [7.6 W/ft]
9XX/RGBW	0.29	0.57	1.00	0.29
WD	0.17	0.35	0.51	-
CCT Multiplier				
	927	930	935	940
	0.77	0.84	1.00	1.19

- 1 Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.
- 2 WD lumen data at maximum output (3000K).
- 3 RGBW lumen data at maximum output with 3000K White LED.
- 4 UGR value noted is the maximum UGR (crosswise) with 935 LEDs / 48" length.