

U060 LIGHTWAY

OPAL ACRYLIC / RECESSED FAMILY

inter•lux

U060 Profile --- Mounting AO Optic XX Beam ----- LED inserts

--- Dimming 40 IP --- Body finish N Emergency I Layout ----- Length

Profile **U060:** Profile 2.6 inch width
 Optic **AO:** Opal Acrylic
 Beam **XX:** No beam angle
 IP **40:** IP40
 Emergency **N:** No emergency
 Layout **I:** Linear straight run

Mounting

RD: Recessed - **RT:** Recessed - **RW:** Recessed trimless with trim with trim

LED inserts

(Mid-Power LED - CRI 80+)

Temperature	LED Type	W/ft	lm/ft
2700°K	827L2:	4.6	445
	827L3:	6.7	613
	827L4:	9.2	890
	827L5:	13.1	1227
3000°K	830L2:	4.6	470
	830L3:	6.7	647
	830L4:	9.2	939
	830L5:	13.1	1295
3500°K	835L2:	4.6	478
	835L3:	6.7	658
	835L4:	9.2	955
	835L5:	13.1	1316

Total connected load (W/ft) - Delivered Lumen (lm/ft)

Dimming

Integral driver

- C:** Non-Dim integral
- D:** Lutron - remote only
- E:** 0-10V dim integral

(Other dimming protocol are available upon request)

Body Finish

- B:** Black
- W:** White
- G:** Gray

Length (inch)

Recessed:

12 - 24 - 35 - 47 - 59 - 70 - 82 - 93 - 105

Recessed with trim:

13 - 25 - 36 - 48 - 59 - 71 - 82 - 94 - 106

Recessed trimless:

13 - 25 - 36 - 48 - 59 - 71 - 83 - 94 - 106

(For all 12 inch modules, driver is remote)

Electrical Data


120 - 277V Power range



Wide, even levels of illumination
 High angle distribution to illuminate adjacent walls


Section drawing (inch)

Recessed




2.7in x (L+0.1in)

Recessed with trim



2.9in x (L-0.8in)

Recessed trimless



3.9in x (L+0.2in)

Notes

- Total connected load: including driver + LED power consumption



410 381 1497 inter-lux.com answers@inter-lux.com
 Inter-lux reserves the right to make technical changes without notice.