


20 Linear Direct / Indirect Suspended Louver



Ordering Information

Model	Fixation	Pattern	Length	Direct*	Indirect*	Finish	Options
WG-20LDI-S direct / indirect	48 96	S	A	Specify options using chart below* See ex 1: L1-D010-LL45B	Specify options using chart below* See ex 2: M3-S-OD	W (std) B G F	DC

Luminaire

- Glare control louver for complete shielding of light source.
- Available in 4.74" increments.
- Field replaceable LED boards.
- 90+ CRI, 3 steps MacAdam.
- Powder coat painted white - RAL 9010.

Fixation

- 48 = 48" suspension cable standard
- 96 = 96" suspension cable, field-cuttable

Pattern

- S = Straight run (continuous runs of any length available in 4.74" increments)

Length

- A = Specify up to 94.8" in 4.74" increments (i.e. 23.7", 37.9" 47.4", 56.9", 85.3").

Power¹

- L = 3.2W/ft low power (24V)
- M = 6.4W/ft mid power (24V)

CRI/CCT²

90+ CRI (Low/Mid Power)

- 927 = 2700K (63/117 lm/ft)
- 930 = 3000K, (65/120 lm/ft)
- 935 = 3500K, (66/123 lm/ft)
- 940 = 4000K, (67/124 lm/ft)

Driver (remote)³

- X = No driver, ordered separately
- S = Standard driver 120-277V
- D010 = Osram, 10%, 0-10V dimming, 120-277V
- L3DAE = Lutron Hi-lume 1% EcoSystem, 120-277V
- L3DOE = Lutron Hi-lume Premier 0.1 EcoSystem, 120-277V
- DFPN = Lutron Forward Phase 1% 120VAC

Direct Lens

- LL45B = Linear louver black

Indirect Lens

- OD = Satin opal diffuser (standard)
- SD = Satin clear diffuser (high efficiency)

Finish

- W = White, 20% gloss, RAL9010 (standard)
- B = Black, 20% gloss
- G = Gray, 20% gloss
- F = Custom finished trim, specify RAL

Options

- DC = dual circuit

Emergency

- Emergency LED driver available, order separately.

*Direct/Indirect

Specify Power/CRI/CCT, Driver, Direct and Indirect Lens options

Power/CRI/CCT		Driver	Direct Lens	Indirect Lens
	L M	X	LL45B	OD
927	L1 M1	S		SD
930	L2 M2	D010		
935	L3 M3	L3DAE		
940	L4 M4	L3DOE		
		DFPN		

¹ Wattage shown does not include power supplies/drivers.

² Delivered lumens with black louver shown for one direction.

³ Remote power supply required. See power supply page for details.