



IR67-RWH-Z-...-ZS... DELIVERED LUMENS - Zoom Symmetric					
		Size [Wattage]			
		16 [6 CC]	24 [13 CC]	32 [20 CC]	39 [30 CC]
CCT	27-	129	322	n/a	1388
	30-	243	676	2206	3633
	40-	263	726	2368	3633
Polar Plot / Cone Of Light Multiplier					
		16 [6 CC]	24 [13 CC]	32 [20 CC]	39 [30 CC]
		0.07	0.19	0.61	1.00



Beam Angle (0-180) = 15.4  
Beam Angle (90-270) = 15.0

CONE OF LIGHT - 30W 3000K Zoom Symmetric IR67-RWH-Z-39-30-CC-30-ZS*		
Throw Distance [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]
20	119	5.4
18	147	4.9
16	186	4.3
14	243	3.8
12	330	3.2
10	475	2.7
8	743	2.2
6	1320	1.6
4	2971	1.1
2	11884	0.5

IR67-RWH-Z-...-ZE... DELIVERED LUMENS - Zoom Elliptical					
		Size [Wattage]			
		16 [6 CC]	24 [13 CC]	32 [20 CC]	39 [30 CC]
CCT	27-	123	594	555	1250
	30-	123	594	884	1302
	40-	133	639	592	1374
Polar Plot / Cone Of Light Multiplier					
		16 [6 CC]	24 [13 CC]	32 [20 CC]	39 [30 CC]
		0.09	-	0.68	1.00



Beam Angle (0-180) = 15.4  
Beam Angle (90-270) = 15.0

CONE OF LIGHT - 30W 3000K Zoom Elliptical IR67-RWH-Z-39-30-CC-30-ZE*		
Throw Distance [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]
20	5	17.0
18	6	15.3
16	7	13.6
14	9	11.9
12	13	10.2
10	18	8.5
8	28	6.8
6	51	5.1
4	114	3.4
2	456	1.7

\*Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.