Loro

inter•lux

Loro_R | Downlight | arrayLED 8 W 220 mA



type			color			optic	
White	CRI 95	**E97920**	2700 K	730 lm	**M**	15°	**15**
Black	CRI 95	**E97921**	3000 K	782 lm	**W**	30°	**30**
Grey	CRI 95	**E97924**	4000 K	842 lm	**N**	60°	**60**
Gold	CRI 95	**E97925**					
White	CRI 80	**E97695**	2700 K	970 lm	**M**	15°	**15**
Black	CRI 80	**E97696**	3000 K	1038 lm	**W**	30°	**30**
Grey	CRI 80	**E97697**	4000 K	1038 lm	**N**	60°	**60**
Gold	CRI 80	**E97698**					

power supply options (remote only)

ECO30W-220	**SOLO50W-220**	**SOLO100W-220**
0-10V EldoLED ECOdrive 30W, for 1-1 fixtures	0-10V EldoLED SOLOdrive 50W, for 1-2 fixtures	0-10VEldoLED SOLOdrive 100W, for 1-4 fixtures

Loro_R | Downlight | arrayLED 13 W 350 mA



type			color			optic	
White	CRI 95	**91749**	2700 K	1069 lm	**M**	15°	**15**
Black	CRI 95	**91750**	3000 K	1146 lm	**W**	30°	**30**
Grey	CRI 95	**91751**	4000 K	1234 lm	**N**	60°	**60**
Gold	CRI 95	**91752**					
White	CRI 80	**91204**	2700 K	1421 lm	**M**	15°	**15**
Black	CRI 80	**91205**	3000 K	1520 lm	**W**	30°	**30**
Grey	CRI 80	**91206**	4000 K	1520 lm	**N**	60°	**60**
Gold	CRI 80	**91207**					

power supply options (remote only)

ECO30W-350	**SOLO50W-350**	**SOLO100W-350**
0-10V EldoLED ECOdrive 30W, for 1-1 fixtures	0-10V EldoLED SOLOdrive 50W, for 1-2 fixtures	0-10VEldoLED SOLOdrive 100W, for 1-4 fixtures

Loro_R | Downlight | arrayLED 18 W 500 mA



type			color			optic	
White	CRI 95	**E91528**	2700 K	1476 lm	**M**	15°	**15**
Black	CRI 95	**E91541**	3000 K	1584 lm	**W**	30°	**30**
Grey	CRI 95	**E91542**	4000 K	1818 lm	**N**	60°	**60**
Gold	CRI 95	**E91544**					
White	CRI 80	**E91518**	2700 K	1818 lm	**M**	15°	**15**
Black	CRI 80	**E91519**	3000 K	1944 lm	**W**	30°	**30**
Grey	CRI 80	**E91520**	4000 K	2106 lm	**N**	60°	**60**
Gold	CRI 80	**E91521**					

power supply options (remote only)

ECO30W-500	**SOLO50W-500**	**SOLO100W-500**
0-10V EldoLED ECOdrive 30W, for 1-1 fixtures	0-10V EldoLED SOLOdrive 50W, for 1-2 fixtures	0-10VEldoLED SOLOdrive 100W, for 1-4 fixtures

Loro_X | Downlight | arrayLED 8 W 220 mA



type			color			optic	
White	CRI 80	**E91508**	2700 K	970 lm	**M**	15°	**15**
Black	CRI 80	**E91509**	3000 K	1038 lm	**W**	30°	**30**
Grey	CRI 80	**E91514**	4000 K	1038 lm	**N**	60°	**60**
Gold	CRI 80	**E91515**					

power supply options (remote only)

ECO30W-220	**SOLO50W-220**	**SOLO100W-220**
0-10V EldoLED ECOdrive 30W, for 1-1 fixtures	0-10V EldoLED SOLOdrive 50W, for 1-2 fixtures	0-10VEldoLED SOLOdrive 100W, for 1-4 fixtures

Loro_Q | Downlight | arrayLED 8 W 220 mA



type			color			optic	
White	CRI 95	**E97940**	2700 K	730 lm	**M**	15°	**15**
Black	CRI 95	**E97941**	3000 K	782 lm	**W**	30°	**30**
Grey	CRI 95	**E97944**	4000 K	842 lm	**N**	60°	**60**
Gold	CRI 95	**E97945**					
White	CRI 80	**E97699**	2700 K	970 lm	**M**	15°	**15**
Black	CRI 80	**E97700**	3000 K	1038 lm	**W**	30°	**30**
Grey	CRI 80	**E97701**	4000 K	1038 lm	**N**	60°	**60**
Gold	CRI 80	**E97702**					

power supply options (remote only)

ECO30W-220	**SOLO50W-220**	**SOLO100W-220**
0-10V EldoLED ECOdrive 30W, for 1-1 fixtures	0-10V EldoLED SOLOdrive 50W, for 1-2 fixtures	0-10VEldoLED SOLOdrive 100W, for 1-4 fixtures

Loro_Q | Downlight | arrayLED 13 W 350 mA



type			color			optic	
White	CRI 95	**E91753**	2700 K	1069 lm	**M**	15°	**15**
Black	CRI 95	**E91754**	3000 K	1146 lm	**W**	30°	**30**
Grey	CRI 95	**E91755**	4000 K	1234 lm	**N**	60°	**60**
Gold	CRI 95	**E91756**					
White	CRI 80	**E91208**	2700 K	1421 lm	**M**	15°	**15**
Black	CRI 80	**E91209**	3000 K	1520 lm	**W**	30°	**30**
Grey	CRI 80	**E91210**	4000 K	1520 lm	**N**	60°	**60**
Gold	CRI 80	**E91211**					

power supply options (remote only)

ECO30W-350	**SOLO50W-350**	**SOLO100W-350**
0-10V EldoLED ECOdrive 30W, for 1-1 fixtures	0-10V EldoLED SOLOdrive 50W, for 1-2 fixtures	0-10VEldoLED SOLOdrive 100W, for 1-4 fixtures

Loro_Q | Downlight | arrayLED 18 W 500 mA



type			color			optic	
White	CRI 95	**E91558**	2700 K	1476 lm	**M**	15°	**15**
Black	CRI 95	**E91559**	3000 K	1584 lm	**W**	30°	**30**
Grey	CRI 95	**E91561**	4000 K	1818 lm	**N**	60°	**60**
Gold	CRI 95	**E91562**					
White	CRI 80E	**E91524**	2700 K	1818 lm	**M**	15°	**15**
Black	CRI 80	**E91525**	3000 K	1944 lm	**W**	30°	**30**
Grey	CRI 80	**E91526**	4000 K	2106 lm	**N**	60°	**60**
Gold	CRI 80	**E 91527**					

power supply options (remote only)

ECO30W-500	**SOLO50W-500**	**SOLO100W-500**
0-10V EldoLED ECOdrive 30W, for 1-1 fixtures	0-10V EldoLED SOLOdrive 50W, for 1-2 fixtures	0-10VEldoLED SOLOdrive 100W, for 1-4 fixtures