Picrol

interlux

linea light i-LED

A discreet, practical, and versatile downlights, available in three different finishes. Outer casing installation. A **eye of light projected on the environment,** highly customizable according to the customer's needs thanks to the several types of optics available.

Passive heat dissipation
Brass or polyamide casing

Light management
Six optics available ensuring maximum design flexibility

Picrol | Decorative downlights | powerLED 1W 350 mA

C.C. IP44



type			color			optic	
White	CRI 80	**E91364**	3000 K	145 lm	**W**	10°	**10**
Chrome	CRI 80	**E86407**	4000 K	155 lm	**N**	30°	**30**
						50°	**50**
						70°	**70**
						120°	**12**
						Diff.	**00**

power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W, for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W, for 1-20 fixtures	0-10VEldoLED SOLOdrive 100W, for 1-40 fixtures

E84336

Concrete ceiling outer casing (optional)

Picrol | Decorative downlights | powerLED 1.5W 500 mA

C.C. IP44



type			color			optic	
White	CRI 80	**E91365**	3000 K	199 lm	**W**	10°	**10**
Chrome	CRI 80	**E86408**	3500 K	199 lm	**T**	30°	**30**
			4000 K	213 lm	**N**	50°	**50**
						70°	**70**
						120°	**12**
						Diff.	**00**

power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350
0-10V EldoLED ECOdrive 30W, for 1-15 fixtures	0-10V EldoLED SOLOdrive 50W, for 1-24 fixtures	0-10VEldoLED SOLOdrive 100W, for 1-48 fixtures

E84901

Concrete ceiling outer casing (optional)