


Loro\_R | Downlight | arrayLED | Damp Location | Driver remote | 8W 220mA



Balance - CRI 92

White	<b>E97920</b>	2700 K	883 lm	<b>M</b>	Spot	<b>15</b>
Black	<b>E97921</b>	3000 K	943 lm	<b>W</b>	Medium Flood	<b>30</b>
Grey	<b>E97924</b>	3500 K	943 lm	<b>T</b>	Flood	<b>60</b>
Gold	<b>E97925</b>	4000 K	1016 lm	<b>N</b>		



White	<b>E80791</b>
Black	<b>E80792</b>
Grey	<b>E80793</b>
Gold	<b>E80794</b>

Efficiency - CRI 80


White	<b>E97695</b>	2700 K	1088 lm	<b>M</b>	Spot	<b>15</b>
Black	<b>E97696</b>	3000 K	1088 lm	<b>W</b>	Medium Flood	<b>30</b>
Grey	<b>E97697</b>	3500 K	1088 lm	<b>T</b>	Flood	<b>60</b>
Gold	<b>E97698</b>	4000 K	1173 lm	<b>N</b>		



White	<b>E80787</b>
Black	<b>E80788</b>
Grey	<b>E80789</b>
Gold	<b>E80790</b>

Power supply options (remote only)


<b>ECO30W-220</b> 0-10V EldoLED ECOdrive 30W for 1 fixture	<b>SOLO50W-220</b> 0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	<b>SOLO100W-220</b> 0-10V EldoLED SOLOdrive 100W for 1-4 fixtures
--	---	---



>16 optics 30°  
>19 optics 15°, 60°

UGR

Loro\_R | Downlight | arrayLED | Damp Location | Driver remote | 13W 350mA



Balance - CRI 92

White	<b>E91749</b>	2700 K	1399 lm	<b>M</b>	Spot	<b>15</b>
Black	<b>E91750</b>	3000 K	1496 lm	<b>W</b>	Medium Flood	<b>30</b>
Grey	<b>E91751</b>	3500 K	1496 lm	<b>T</b>	Flood	<b>60</b>
Gold	<b>E91752</b>	4000 K	1610 lm	<b>N</b>		



White	<b>E80799</b>
Black	<b>E80800</b>
Grey	<b>E80801</b>
Gold	<b>E80802</b>

Efficiency - CRI 80


White	<b>E91204</b>	2700 K	1724 lm	<b>M</b>	Spot	<b>15</b>
Black	<b>E91205</b>	3000 K	1724 lm	<b>W</b>	Medium Flood	<b>30</b>
Grey	<b>E91206</b>	3500 K	1724 lm	<b>T</b>	Flood	<b>60</b>
Gold	<b>E91207</b>	4000 K	1854 lm	<b>N</b>		




White	<b>E80795</b>
Black	<b>E80796</b>
Grey	<b>E80797</b>
Gold	<b>E80798</b>

Power supply options (remote only)


<b>ECO30W-350</b> 0-10V EldoLED ECOdrive 30W for 1 fixture	<b>SOLO50W-350</b> 0-10V EldoLED SOLOdrive 50W for 1-2 fixtures	<b>SOLO100W-350</b> 0-10V EldoLED SOLOdrive 100W for 1-4 fixtures
--	---	---



UGR < 22



Loro\_R | Downlight | arrayLED | Damp Location | Driver remote | 25W 700mA



Balance - CRI 92

White	<b>E80672</b>	2700 K	2598 lm	<b>M</b>	Spot	<b>15</b>
Black	<b>E80673</b>	3000 K	2794 lm	<b>W</b>	Medium Flood	<b>30</b>
Grey	<b>E80704</b>	3500 K	2794 lm	<b>T</b>	Flood	<b>60</b>
Gold	<b>E80705</b>	4000 K	2990 lm	<b>N</b>		



White	<b>E80807</b>
Black	<b>E80808</b>
Grey	<b>E80809</b>
Gold	<b>E80810</b>

Efficiency - CRI 80


White	<b>E80670</b>	2700 K	3210 lm	<b>M</b>	Spot	<b>15</b>
Black	<b>E80671</b>	3000 K	3431 lm	<b>W</b>	Medium Flood	<b>30</b>
Grey	<b>E80702</b>	3500 K	3431 lm	<b>T</b>	Flood	<b>60</b>
Gold	<b>E80703</b>	4000 K	3431 lm	<b>N</b>		



White	<b>E80803</b>
Black	<b>E80804</b>
Grey	<b>E80805</b>
Gold	<b>E80806</b>

Power supply options (remote only)

<b>SOLO50W-700</b>	<b>SOLO100W-700</b>
0-10V EldoLED SOLOdrive 50W for 1 fixture	0-10V EldoLED SOLOdrive 100W for 1-3 fixtures



UGR < 22

technical  
information