

# Quara IP44 Nickel



**General:** With an elegant opening shaped light a drop of water, Quara family of step lights offers a classy while efficient solution for steps or could be used to emphasize any ground detail in a discrete way. Quara is available for both Indoor and Outdoor applications, round or square, recessed or semi-recessed, in multiple sizes and finishes, including stainless steel and nickel.

**Fixture Body:** Brushed Nickel.

**Diffuser:** UV Resistant Polycarbonate.

**Mounting details:** Wall mounted, semi-flush. Black PVC housing.

**Dimension/Weight:** 2.8" (1.79 lbs)

**Driver:** Remote, Constant Current 120-277V, Dimmable 0-10V.

**Wattage/Size:** 2W (2.8")

**Cable:** Fixture comes with 3.28' of power cable.

**IP rating:** IP44 for protection against objects larger than 0.04" and against water splashes

**IK rating:** IK 10

**ETL Certification:** ETL, damp location

**Optics:** Fixed with Asymmetric distribution.

**Color temperatures:** 2700K – 3000K – 3500K – 4000K.


**CRI:** 80+

**Lumen Maintenance:** L70 projections tested at Tj 65° C and Ta 25°.

**Warranty:** 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



2.6" RNI (2W)



2.8" SNI (2W)


Delivered Lumens*		2.8" (2W)
AS		85

\*Values shown for 3000K

Ordering Information							(Required) <sup>1</sup>		
Product	Trim	Type	Diameter	Wattage/Operation	Color Temp	Optic	+	Housing	Driver
QR44 = Quara IP44	RNI = Round Nickel SNI = Square Nickel	F = Fixed	26 = 26" 28 = 2.8"	2 CC = 2W / Constant Current (630mA)	27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	AS = Asymmetric		E84338	ECO30W-630 SOLO50W-630 SOLO100W-630

<sup>1</sup> See page 2

## 2.6" RNI (2W)



### Housing

**E84338**  
Recessed Housing



### DRIVER OPTIONS (pick one)


#### C.C. Power supply options (remote only)

**ECO30W-630**  
0-10V EldoLED  
ECOdrive 30W  
for 1-10 fixtures

**SOLO50W-630**  
0-10V EldoLED  
SOLOdrive 50W  
for 1-16 fixtures

**SOLO100W-630**  
0-10V EldoLED  
SOLOdrive 100W  
for 1-32 fixtures

## 2.8" SNI (2W)



### Housing

**E84338**  
Recessed Housing



### DRIVER OPTIONS (pick one)

#### C.C. Power supply options (remote only)

**ECO30W-630**  
0-10V EldoLED  
ECOdrive 30W  
for 1-10 fixtures

**SOLO50W-630**  
0-10V EldoLED  
SOLOdrive 50W  
for 1-16 fixtures

**SOLO100W-630**  
0-10V EldoLED  
SOLOdrive 100W  
for 1-32 fixtures