

# Quara IP44



**General:** With an elegant opening shaped light a drop of water, Quara family of step lights offers a classy while efficient solution for steps or could be used to emphasize any ground detail in a discrete way. Quara is available for both Indoor and Outdoor applications, round or square, recessed or semi-recessed, in multiple sizes and finishes, including stainless steel and nickel.

**Fixture Body:** Powder Coated Aluminum or Stainless Steel.

**Diffuser:** UV Resistant Polycarbonate.

**Mounting details:** Wall mounted, semi-flush. Black PVC housing.

**Dimensions/Weight:** 1.0" (0.26 lbs)

**Driver:** Remote, Constant Current 120-277V, Dimmable 0-10V.

**Wattage/Size:** 1W (1.0")

**Cable:** Fixture comes with 3.28' of power cable.

**IP rating:** IP44 for protection against objects larger than 0.04" and against water splashes

**IK rating:** IK 10

**ETL Certification:** ETL, damp location


**Optics:** Fixed with Asymmetric distribution.

**Color temperatures:** 2700K – 3000K – 3500K – 4000K.


**CRI:** 80+

**Lumen Maintenance:** L70 projections tested at Tj 65° C and Ta 25°.

**Warranty:** 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



1.0" Round (1W)



1.0" Square (1W)


Delivered Lumens*	1.0" (1W)
AS	9

\*Values shown for 3000K

Ordering Information							(Required) <sup>1</sup>		
Product	Trim	Type	Diameter	Wattage/Operation	Color Temp	Optic	+	Housing	Driver
QR44 = Quara IP44	RWH = Round White RGR = Round Gray RDB = Round Dark Brown RST = Round St. Steel SWH = Square White SGR = Square Gray SDB = Square Dark Brown SST = Square St. Steel	F = Fixed	10 = 1.0"	1 CC = 1W / Constant Current (350mA)	27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	AS = Asymmetric		E98950	ECO30W-350 SOLO50W-350 SOLO100W-350


<sup>1</sup> See page 2

## 1.0" Round (1W)



## Housing

**E98950**  
Recessed Housing



## DRIVER OPTIONS (pick one)


### C.C. Power supply options (remote only)

**ECO30W-350**  
0-10V EldoLED  
ECOdrive 30W  
for 1-10 fixtures

**SOLO50W-350**  
0-10V EldoLED  
SOLOdrive 50W  
for 1-16 fixtures


**SOLO100W-6350**  
0-10V EldoLED  
SOLOdrive 100W  
for 1-32 fixtures

## 1.0" Square (1W)



## Housing

**E98950**  
Recessed Housing



## DRIVER OPTIONS (pick one)

### C.C. Power supply options (remote only)

**ECO30W-350**  
0-10V EldoLED  
ECOdrive 30W  
for 1-10 fixtures

**SOLO50W-350**  
0-10V EldoLED  
SOLOdrive 50W  
for 1-16 fixtures

**SOLO100W-350**  
0-10V EldoLED  
SOLOdrive 100W  
for 1-32 fixtures