



Miniature LED ground or wall recessed fitting. Suitable for use in areas subject to foot traffic only.

- Materials: Aluminum, toughened glass
- Color Temp: 2700K, 3000K, 3500K or 4000K
- Lamp: MSL Star (1 x Osram Oslon Square)
- IP Rating: IP65
- Optics: 0.8"Ø (20mm) optics. Please refer to the table below for beam angle options and ordering information.
- Finish: White (Standard) Pure White RAL 9010 30% gloss
Black (Standard) Powdercoat Matte Black 5% gloss
Custom paint and anodized finishes available
- Dimming: EldoLED 0-10V or DMX
- Driver: Constant current remote driver required
Allow 2W at 700mA
- Cut out: 1.3"Ø (33mm)
- Locking: Fixed
- Available Tilt: Fixed
- Weight: 0.44lb (0.2kg)
- Deviation: Deepset versions

LED Information

Each LED "lamp" consists of one or more Osram Oslon Square power LED thermally bonded to an aluminum cored printed circuit board.



MSL Star

Ø21mm PCB with a single Osram Oslon Square LED. For Ø20mm optics.

Order Code	series.col temp.beam.finish.dimming
Example	Mole.3000K.10°.white.D010

Series	Color	Beam	Finish	Dimming and control	Deviation*
Mole	2700K 3000K 3500K 4000K	10° 13° 19° 35°	white black custom	D010 0-10V DMX DMX	Deepset version 1 2.3" (58mm) recessed length Deepset version 2 2.9" (73mm) recessed length

