
STX2.50







Surface mount lockable power LED spotlight using Xicato Module.

Materials: Aluminum

Color Temp: 2700K, 3000K, 3500K or 4000K

Lamp: Xicato XTM or XIM 9mm LES LED Module

Output: Please see table on second page. *Vibrant Series only available for 3000K*

CRI Ra: ≥80 or ≥95 Artist

Optics: 2"Ø (50mm) optics. Please refer to the table on the second page for beam

options and ordering information. Takes two accessories.

Finish: White (Standard) Pure White RAL 9010 30% gloss

Black (Standard) Powdercoat Matte Black 5% gloss Custom paint and anodized finishes available

Dimming: XIM 0-10V XTM EldoL

XTM EldoLED 0-10V, DMX, Integral or Dual Dim

Supply: XIM 48V DC

XTM Constant current remote driver

Locking: 2.5mm Allen key required


Available Tilt: ± 120°

Weight: 0.88" (0.4kg)

Accessories: Please refer to the table on the second page for lenses,

louvers and accessories. Barn door and wall washing

attachments are also available.



LED Information

This product uses the Xicato Module Technical advantages of the Xicato Module:

- Color consistency Initial; 1 x 2 MacAdam ellipses
- Color consistency Maintained; 3 MacAdam ellipses
- Excellent color rendering
- Uniform beam
- No multiple shadowing


STX2.50

inter•lux

Applications


Remote dimming No local drivers

REMOTE DIMMING WHERE LOCAL DRIVERS NOT PRACTICAL XICATO XIM 9MM BUSSED 48V AND CONTROL



Remote dimming Local drivers

REMOTE DIMMING WHERE LOCAL DRIVERS PREFERRED XICATO XTM 9MM MAINS AND CONTROL SIGNAL WIRING TO DRIVERS AT FITTINGS



Order Code	series.col temp.module.lumen code.beam.finish.dimming
Example	STX2.50.3000K.XTM9.S82.18°.black.D010

Series	Color	Module Type	Lumen Code - Max output and CRI	Beam	Finish	Dimming and control	Lenses, Louvers and Accessories
STX2.50	2700K 3000K 3500K 4000K	XTM9 XTM 9mm LES	\$82 Standard Series 82 1300lm 15.6 A95 Artist Series 95 930lm 15.6 V80 Vibrant Series V80 1300lm 15.6* V95 Vibrant Series V95 930lm 15.6*	18° 25° 39°	black	D010 Remote 0-10V DMX DMX 2DIM Dual dim (integral dimmer and remote 0-10V)	SL Symmetrical spread lens TE Soft Elliptical spread lens PE Sharp Elliptical spread lens HL Honeycomb louver DL Dichroic lens BD Barn doors WW Wall washer SN Snoot
		XIM9 XIM 9mm LES	\$82 Standard Series 82 700lm 9.7 A95 Artist Series 95 700lm 11.9 V80 Vibrant Series V80 700lm 9.7* V95 Vibrant Series V95 700lm 11.9*	18° 25° 39°	white black custom	D010 Remote 0-10V	

