



Contents	
2	product configurator
3	diagrams / drivers

**General:** Epitax is a family of low brightness, highly performing round LED downlights suitable to illuminate both residential and commercial applications. Epitax recessed LED allows for a defined beam, reducing the impact of the secondary light beam while reducing glare at the same time. Available in both Fixed and Adjustable, the Fixed version allows for Recessed or Semi-Recessed installation thanks to its distinct drop-down reflector system. Performance meets style.

**Fixture Body:** Powder Coated Aluminum 6026 (superior corrosion resistance) for 2W/4W/6W versions. UV resistant polycarbonate for 10W/15W versions.

**Trim:** Trimless or Bezel, Round.

**Mounting:** Recessed or Semi-Recessed in ceiling.

**Dimensions/Weight:** 1.1" (0.10 lbs) – 1.3" (0.28 lbs) – 2.5" (0.41 lbs) – 3.5" (1.13 lbs)

**Driver:** Remote, 120-277V Dimmable 0-10V or Non-Dim.

**Operation:** Constant Current (CC)

**CC features:** Less susceptible to voltage drop (exceeding 32' distance); Allows for dimming down to 0.1%; Fixtures need to be wired in series.

**Wattages:** 3W (1.1") – 2W (1.3") – 6.3W (1.3") – 10W (2.5") – 15W (3.5")

**Cable:** Fixture comes with 0.56' of power cable.

**IP rating:** IP44 (with an IP65 rating of the optical chamber). Fixture is protected against solid objects greater than 0.04" and against water splashes on the fixture trim or lens. Not suitable for Outdoor applications or direct water jets.

**ETL Certification:** ETL, damp location


**Optics:** Fixed (refer to Epitax Adjustable spec sheet for Adjustable version). Available in Ultra Spot – Spot – Narrow Flood – Flood – Medium Wide Flood – Wide Flood.

**Color temperatures:** 2700K – 3000K – 3500K – 4000K.

**CRI:** 92, (1.3", 2W 80 CRI)

**Lumen Maintenance:** L70 projections tested at Tj 65° C and Ta 25°.

**Warranty:** 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



Delivered Lumens*	1.1" (3W)	1.3" (2W)	1.3" (6.3W)	1.3" (6.3W) HC	2.5" (10W)	3.5" (15W)
USP	–	126	–	–	–	–
SP	–	–	508	352	678	–
NFL	204	–	416	254	682	1227
FL	195	–	–	–	–	1108
MWFL	–	–	–	229	617	–
WFL	200	–	417	–	–	917

\*Values shown for 3000K


Ordering Information							(Required)	
EPI		F	11	3 - CC				
Product	Trim	Type	Diameter	Wattage/Operation	Color Temp <sup>1</sup>	Optic	+	Driver
EPI = Epitax	RSRWH = Recessed/ Semi Rec. Round White RSRBL = Recessed/ Semi Rec. Round Black RSRGO = Recessed/ Semi Rec. Round Gold	F = Fixed	11 = 1.1"	3 CC = 3W / Constant Current (1000mA)	80-27 = 2700K 80-30 = 3000K 80-35 = 3500K 80-40 = 4000K	NFL = Narrow Flood (22°) FL = Flood (30°) WFL = Wide Flood (52°)		ECO30W-XXX SOLO50W-XXX SOLO100W-XXX
							E-C100005 E98527 E98528 E98529	

Ordering Information							(Required)	
EPI			13					
Product	Trim	Type	Diameter	Wattage/Operation	Color Temp <sup>1</sup>	Optic	+	Driver
EPI = Epitax	RSRWH = Recessed/ Semi Rec. Round White RSRBL = Recessed/ Semi Rec. Round Black RSRGO = Recessed/ Semi Rec. Round Gold	F = Fixed	13 = 1.3"	2 CC = 2W / Constant Current (630mA)	80-27 = 2700K 80-30 = 3000K 80-35 = 3500K 80-40 = 4000K	USP = Ultra Spot (5°)		ECO30W-XXX SOLO50W-XXX SOLO100W-XXX
		F = Fixed	13 = 1.3"	6 CC = 6.3W / Constant Current (700mA)	92-27 = 2700K 92-30 = 3000K 92-35 = 3500K 92-40 = 4000K	SP = Spot (19°) NFL = Narrow Flood (28°) WFL = Wide Flood (51°)		
		FHC = Fixed Honeycomb	13 = 1.3"	6 CC = 6.3W / Constant Current (700mA)	92-27 = 2700K 92-30 = 3000K 92-35 = 3500K 92-40 = 4000K	SP = Spot (17°) NFL = Narrow Flood (24°) MWFL = Medium Wide Flood (40°)		
							E-C100006 E98530 E98531 E98532	

Ordering Information							(Required)	
EPI		F	25	10 - CC				
Product	Trim	Type	Diameter	Wattage/Operation	Color Temp <sup>1</sup>	Optic	+	Driver
EPI = Epitax	RSRWH = Recessed/ Semi Rec. Round White RSRBL = Recessed/ Semi Rec. Round Black RSRGO = Recessed/ Semi Rec. Round Gold	F = Fixed	25 = 2.5"	10 CC = 10W / Constant Current (800mA)	92-27 = 2700K 92-30 = 3000K 92-35 = 3500K 92-40 = 4000K	SP = Spot (17°) NFL = Narrow Flood (28°) MWFL = Medium Wide Flood (42°)		ECO30W-XXX SOLO50W-XXX SOLO100W-XXX
							E98499 E98533 E98534 E98535	


Ordering Information							(Required)	
EPI		F	35	15 - CC				
Product	Trim	Type	Diameter	Wattage/Operation	Color Temp <sup>1</sup>	Optic	+	Driver
EPI = Epitax	RSRWH = Recessed/ Semi Rec. Round White RSRBL = Recessed/ Semi Rec. Round Black RSRGO = Recessed/ Semi Rec. Round Gold	F = Fixed	35 = 3.5"	15 CC = 15W / Constant Current (400mA)	92-27 = 2700K 92-30 = 3000K 92-35 = 3500K 92-40 = 4000K	NFL = Narrow Flood (22°) FL = Flood (37°) WFL = Wide Flood (50°)		ECO30W-XXX SOLO50W-XXX SOLO100W-XXX
							E98500 E98536 E98537 E98538	

## 1.1" 3W 1000mA




### Housing

**E-C100005**  
Recessed Housing  
for flush installation



**E98527** White  
**E98528** Black  
**E98529** Gold  
Recessed Housing  
with flange



### DRIVER OPTIONS (pick one)


#### C.C. Power supply options (remote only)

**ECO30W-1000**  
0-10V EldoLED  
ECODrive 30W  
for 1-7 fixtures

**SOLO50W-1000**  
0-10V EldoLED  
SOLOdrive 50W  
for 1-12 fixtures


**SOLO100W-1000**  
0-10V EldoLED  
SOLOdrive 100W  
for 1-24 fixtures

## 1.3" 2W 630mA




### Housing

**E-C100006**  
Recessed Housing  
for flush installation



**E98530** White  
**E98531** Black  
**E98532** Gold  
Recessed Housing  
with flange



### DRIVER OPTIONS (pick one)


#### C.C. Power supply options (remote only)

**ECO30W-630**  
0-10V EldoLED  
ECODrive 30W  
for 1-10 fixtures

**SOLO50W-630**  
0-10V EldoLED  
SOLOdrive 50W  
for 1-16 fixtures


**SOLO100W-630**  
0-10V EldoLED  
SOLOdrive 100W  
for 1-32 fixtures

## 1.3" 6.3W 700mA




### Housing

**E-C100006**  
Recessed Housing  
for flush installation



**E98530** White  
**E98531** Black  
**E98532** Gold  
Recessed Housing  
with flange



### DRIVER OPTIONS (pick one)


#### C.C. Power supply options (remote only)

**ECO30W-700**  
0-10V EldoLED  
ECODrive 30W  
for 1-3 fixtures

**SOLO50W-700**  
0-10V EldoLED  
SOLOdrive 50W  
for 1-6 fixtures


**SOLO100W-700**  
0-10V EldoLED  
SOLOdrive 100W  
for 1-12 fixtures

## 2.5" 10W 800mA




### Housing

**E98499**  
Recessed Housing  
for flush installation



**E98533** White  
**E98534** Black  
**E98535** Gold  
Recessed Housing  
with flange



### DRIVER OPTIONS (pick one)


#### C.C. Power supply options (remote only)

**ECO30W-800**  
0-10V EldoLED  
ECODrive 30W  
for 1-2 fixtures

**SOLO50W-800**  
0-10V EldoLED  
SOLOdrive 50W  
for 1-4 fixtures


**SOLO100W-800**  
0-10V EldoLED  
SOLOdrive 100W  
for 1-8 fixtures

3.5" 15W 400mA




Housing

**E98500**  
Recessed Housing  
for flush installation



**E98536** White  
**E98537** Black  
**E98538** Gold  
Recessed Housing  
with flange



DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)

**ECO30W-400**  
0-10V EidoLED  
ECOdrive 30W  
for 1 fixture

**SOLO50W-400**  
0-10V EidoLED  
SOLOdrive 50W  
for 1-2 fixtures

**SOLO100W-400**  
0-10V EidoLED  
SOLOdrive 100W  
for 1-4 fixtures