


## FIXED


EPI-RSRWH-F-...-NSP...						
Delivered Lumens - Narrow Spot						
		Diameter [Wattage]				
		11 [2 CC]	11 [4 CC]	14 [6 CC]	25 [10 CC]	35 [15 CC]
CCT	92-27-	107	-	-	-	-
	92-30-	121	-	-	-	-
	92-35-	121	-	-	-	-
	92-40-	-	-	-	-	-
Polar Plot / Cone Of Light Multiplier						
		11 [2 CC]	11 [4 CC]	14 [6 CC]	25 [10 CC]	35 [15 CC]
		1.00	-	-	-	-



Beam Angle (0-180) = 11.0  
Beam Angle (90-270) = 10.8

CONE OF LIGHT - 2W 3000K Narrow Spot EPI-RSRWH-F-11-2-CC-92-30-NSP*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]**
2	244	0.4
4	61	0.8
6	27	1.2
8	15	1.5
10	10	1.9
12	7	2.3
14	5	2.7
16	4	3.1
18	3	3.5
20	2	3.9


EPI-RSRWH-F-...-SP...						
Delivered Lumens - Spot						
		Diameter [Wattage]				
		11 [2 CC]	11 [4 CC]	14 [6 CC]	25 [10 CC]	35 [15 CC]
CCT	92-27-	102	277	375	628	1147
	92-30-	117	296	401	678	1227
	92-35-	117	296	401	678	1227
	92-40-	-	321	432	726	1319
Polar Plot / Cone Of Light Multiplier						
		11 [2 CC]	11 [4 CC]	14 [6 CC]	25 [10 CC]	35 [15 CC]
		0.10	0.24	0.33	0.55	1.00



Beam Angle (0-180) = 22.2  
Beam Angle (90-270) = 22.4

CONE OF LIGHT - 15W 3000K Spot EPI-RSRWH-F-35-15-CC-92-30-SP*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]**
2	1450	0.8
4	362	1.6
6	161	2.4
8	91	3.1
10	58	3.9
12	40	4.7
14	30	5.5
16	23	6.3
18	18	7.1
20	14	7.8

EPI-RSRWH-F-...-FL...						
Delivered Lumens - Flood						
		Diameter [Wattage]				
		11 [2 CC]	11 [4 CC]	14 [6 CC]	25 [10 CC]	35 [15 CC]
CCT	92-27-	98	227	328	633	1036
	92-30-	112	244	352	682	1108
	92-35-	112	244	352	682	1108
	92-40-	-	262	378	732	1191
Polar Plot / Cone Of Light Multiplier						
		11 [2 CC]	11 [4 CC]	14 [6 CC]	25 [10 CC]	35 [15 CC]
		1.00	-	-	-	-



Beam Angle (0-180) = 37.8  
Beam Angle (90-270) = 37.2


CONE OF LIGHT - 15W 3000K Flood EPI-RSRWH-F-35-15-CC-92-30-FL*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]**
2	658	1.4
4	164	2.7
6	73	4.1
8	41	5.5
10	26	6.8
12	18	8.2
14	13	9.6
16	10	11
18	8	12.3
20	7	13.7

\*Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.

\*\* Beam Diameter indicates on center spacing required to maintain Illuminance at Mounting Height.

## FIXED


EPI-RSRWH-F...-MWFL... DELIVERED LUMENS - MEDIUM WIDE FLOOD						
		Diameter [Wattage]				
		11 [2 CC]	11 [4 CC]	14 [6 CC]	25 [10 CC]	35 [15 CC]
CCT	92-27-	-	-	-	572	-
	92-30-	-	-	-	617	-
	92-35-	-	-	-	617	-
	92-40-	-	-	-	663	-
Polar Plot / Cone Of Light Multiplier						
		11 [2 CC]	11 [4 CC]	14 [6 CC]	25 [10 CC]	35 [15 CC]
		-	-	-	1.00	-



Beam Angle (0-180) = 42.0  
Beam Angle (90-270) = 41.2

CONE OF LIGHT - 10W 3000K Medium Wide Flood EPI-RSRWH-F-25-10-CC-92-30-MWFL*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]**
2	286	1.5
4	71	3.1
6	32	4.6
8	18	6.1
10	11	7.7
12	8	9.2
14	6	10.7
16	4	12.3
18	4	13.8
20	3	15.4

EPI-RSRWH-F...-WFL... Delivered Lumens - Wide Flood						
		Diameter [Wattage]				
		11 [2 CC]	11 [4 CC]	14 [6 CC]	25 [10 CC]	35 [15 CC]
CCT	92-27-	101	245	348	-	856
	92-30-	115	261	372	-	917
	92-35-	115	261	372	-	917
	92-40-	-	283	402	-	986
Polar Plot / Cone Of Light Multiplier						
		11 [2 CC]	11 [4 CC]	14 [6 CC]	25 [10 CC]	35 [15 CC]
		0.13	0.28	0.41	-	1.00



Beam Angle (0-180) = 50.6  
Beam Angle (90-270) = 50.2

CONE OF LIGHT - 15W 3000K Wide Flood EPI-RSRWH-F-35-15-CC-92-30-WFL*		
Mounting Height [Ft]	Illuminance [fc at max cd]	Beam Diameter [Ft]**
2	340	1.9
4	85	3.8
6	38	5.7
8	21	7.6
10	14	9.5
12	9	11.3
14	7	13.2
16	5	15.1
18	4	17
20	3	18.9

\*Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.

\*\* Beam Diameter indicates on center spacing required to maintain Illuminance at Mounting Height.