



General: With its microscopic 1" size, Eyelet40 fully integrates in any landscape application, providing a powerful and yet discrete illumination of small planters and trees. Eyelet is available in multiple optics, with a snoot accessory to shape the beam, and can be installed in different ways.

Fixture Body: Open-pore Anodized and Powder Coated Aluminum.

Glass: Extra-clear glass.

Bracket: Anodized Aluminum Bracket, Black Painted. Bracket pivots up to 180° on the vertical plane (no horizontal plane adjustment).

Mounting details: Fixture can be installed straight onto a surface or by using any of the mounting pegs available.

Dimensions/Weight: 1.0" (0.35 lbs)

Driver: Remote, 120-277V Dimmable 0-10V.

Wattage: 2W

Cable: Fixture comes with 3.28' of power cable.

IP rating: IP40 for protection against solid objects of 0.04" and greater.

IK rating: IK 03

ETL Certification: ETL, wet location

Optics: Fixed. Available in Spot – Flood – Wide Flood. Snoot accessory available.

Color temperatures: 2700K – 3000K – 4000K.

CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



1.0" (2W) RWH



1.0" (2W) SWH


Delivered Lumens*	1.0"
SP	170
FL	171
WFL	160

*Values shown for 3000K

Ordering Information									
Product	Trim/Finish	Type	Size	Wattage/Operation	Color Temp	Optic	+	Accessories ¹	Driver (Required) ¹
EY40 = Eyelet40	RWH = Round White RBL = Round Black RGR = Round Gray SWH = Square White SBL = Square Black SGR = Square Gray	F = Fixed	10 = 1.0"	2 CC = 2W / Constant Current (630mA)	27 = 2700K 30 = 3000K 40 = 4000K	SP = Spot FL = Flood WFL = Wide Flood		Peg E98624 E98669 Snoot E99746 E84992	ECO30W-630 SOLO50W-630 SOLO100W-630

¹ See page 2

1.0" 2W 630mA ROUND



DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)

ECO30W-630

0-10V EldoLED
ECOdrive 30W
for 1-10 fixtures


SOLO50W-630

0-10V EldoLED
SOLOdrive 50W
for 1-16 fixtures

SOLO100W-630

0-10V EldoLED
SOLOdrive 100W
for 1-32 fixtures

1.0" 2W 630mA SQUARE



DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)

ECO30W-630

0-10V EldoLED
ECOdrive 30W
for 1-10 fixtures

SOLO50W-630

0-10V EldoLED
SOLOdrive 50W
for 1-16 fixtures

SOLO100W-630

0-10V EldoLED
SOLOdrive 100W
for 1-32 fixtures

ACCESSORIES



E98624

Steel Peg
6.3" length



E98669

Peg
3.98" length



E99746

Snoot



E84992

Spanner, to
install snoot



Eyelet65 with snoot accessory