

Cut



General: Cut is a family of small step lights for outdoor applications with a minimalistic look which provides a well-defined line of light (blade). Its small scale and sharp beam create an attractive lighting effect, perfect to bring attention to steps and feature floors.

Fixture Body: Open pore Anodized and Powder Coated Aluminum.

Diffuser: Extra clear glass.

Mounting details: Wall mounted, semi-flush. Black PVC housing.

Dimensions/Weight: 2.6" (0.28 lbs) & 2.8" (0.33 lbs)

Driver: Remote, Constant Current 120-277V, Dimmable 0-10V.

Wattage/Size: 2W (2.6" & 2.8")

Cable: Fixture comes with 3.28' of power cable.

Safety features: Fixture is equipped with Aqua-Stop technology (anti-wicking) and Over voltage protection.

IP rating: IP65 for protection against dust and water jets from any angle.

IK rating: IK 10

ETL Certification: ETL, wet location

Optics: Fixed with Blade distribution (line of light).

Color temperatures: 2700K – 3000K – 4000K.

CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



2.6" Round (2W)



2.8" Square (2W)


Delivered Lumens*	2.8"
BL	28

*Values shown for 3000K

Ordering Information							(Required) ¹		
Product	Trim	Type	Diameter	Wattage/Operation	Color Temp	Optic	+	Housing	Driver
CUT = Cut	RWH = Round White RGR = Round Gray	F = Fixed	26 = 2.6"	2 CC = 2W / Constant Current (630mA)	27 = 2700K 30 = 3000K 40 = 4000K	BL = Blade	+	E84338	ECO30W-630 SOLO50W-630 SOLO100W-630
	SWH = Square White SGR = Square Gray	F = Fixed	28 = 2.8"					E84338	

¹ See page 2

2.6" Round (2W)



Housing

E84338

Recessed Housing



DRIVER OPTIONS (pick one)


C.C. Power supply options (remote only)

ECO30W-630
0-10V EldoLED
ECOdrive 30W
for 1-10 fixtures

SOLO50W-630
0-10V EldoLED
SOLOdrive 50W
for 1-16 fixtures

SOLO100W-630
0-10V EldoLED
SOLOdrive 100W
for 1-32 fixtures

2.8" Square (2W)



Housing

E84338

Recessed Housing



DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)

ECO30W-630
0-10V EldoLED
ECOdrive 30W
for 1-10 fixtures

SOLO50W-630
0-10V EldoLED
SOLOdrive 50W
for 1-16 fixtures

SOLO100W-630
0-10V EldoLED
SOLOdrive 100W
for 1-32 fixtures