

lvil

inter•lux



A drive-over uplight **also available in the tilt version**, ideally suited to **illuminate columns and external architectural elements**.

Passive heat dissipation



AISI 316 stainless steel casing for high salinity environments

Light management

Six optics available ensuring maximum design flexibility



lvil_R | Drive-over spotlight | powerLED 2W 630 mA





type			color		optic	
Grey	CRI 80	E97586	3000 K	233 lm	W	15° 15
Chrome	CRI 80	E97585	4000 K	249 lm	N	30° 30
Steel	CRI 80	E97587				60° 60
						120° 12
						Diff. 00

power supply options (remote only)



ECO30W-630	SOLO50W-630	SOLO100W-630	E84936
0-10V EldoLED ECOdrive 30W, for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W, for 1-16 fixtures	0-10V EldoLED SOLOdrive 100W, for 1-32 fixtures	Outer casing (required, order separately)

lvil_R | Drive-over spotlight | powerLED 2W 630 mA




type			color		optic	
Grey	CRI 80	E97084	3000 K	233 lm	W	3° 03
Chrome	CRI 80	E97083	4000 K	249 lm	N	
Steel	CRI 80	E97085				

power supply options (remote only)



ECO30W-630	SOLO50W-630	SOLO100W-630	E84935
0-10V EldoLED ECOdrive 30W, for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W, for 1-16 fixtures	0-10V EldoLED SOLOdrive 100W, for 1-32 fixtures	Outer casing (required, order separately)

Ivil_RJ | Drive-over spotlight | powerLED 2W 630 mA | tiltable beam




type		color			optic	
Grey	CRI 80	E97598	3000 K	233 lm	W	15° 15
Chrome	CRI 80	E97597	4000 K	249 lm	N	30° 30
Steel	CRI 80	E97599				60° 60
						120° 12

power supply options (remote only)



ECO30W-630	SOLO50W-630	SOLO100W-630	E84936
0-10V EldoLED ECOdrive 30W, for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W, for 1-16 fixtures	0-10VEldoLED SOLOdrive 100W, for 1-32 fixtures	Outer casing (required, order separately)

Ivil_RJI | Drive-over spotlight | powerLED 2W 630 mA | stainless steel | tiltable beam




type		color			optic	
Steel	CRI 80	E93932	3000 K	233 lm	W	8° 08
			4000 K	249 lm	N	15° 15
						30° 30
						60° 60

power supply options (remote only)



ECO30W-630	SOLO50W-630	SOLO100W-630	E84936
0-10V EldoLED ECOdrive 30W, for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W, for 1-16 fixtures	0-10VEldoLED SOLOdrive 100W, for 1-32 fixtures	Outer casing (required, order separately)

lvil_Q | Drive-over spotlight | powerLED 2W 630 mA



type

Grey	CRI 80	E97589
Chrome	CRI 80	E97588
Steel	CRI 80	E97590

color

3000 K	233 lm	W
4000 K	249 lm	N

optic


15°	15
30°	30
60°	60
120°	12

power supply options (remote only)



ECO30W-630 0-10V EidoLED ECOdrive 30W, for 1-10 fixtures	SOLO50W-630 0-10V EidoLED SOLOdrive 50W, for 1-16 fixtures	SOLO100W-630 0-10VEidoLED SOLOdrive 100W, for 1-32 fixtures	E84936 Outer casing (required, order separately)
--	--	---	--

lvil_QJ | Drive-over spotlight | powerLED 2W 630 mA | tilttable beam



type

Grey	CRI 80	E97601
Chrome	CRI 80	E97600
Steel	CRI 80	E97602

color

3000 K	233 lm	W
4000 K	249 lm	N

optic



15°	15
30°	30
60°	60
120°	12

power supply options (remote only)



ECO30W-630 0-10V EidoLED ECOdrive 30W, for 1-10 fixtures	SOLO50W-630 0-10V EidoLED SOLOdrive 50W, for 1-16 fixtures	SOLO100W-630 0-10VEidoLED SOLOdrive 100W, for 1-32 fixtures	E84936 Outer casing (required, order separately)
--	--	---	--

lvil_QJI | Drive-over spotlight | powerLED 2W 630 mA | stainless steel | tilttable beam



type

Steel	CRI 80	E93933
-------	--------	---------------

color

3000 K	233 lm	W
4000 K	249 lm	N

optic

8°	08
15°	15
30°	30
60°	60

power supply options (remote only)



ECO30W-630 0-10V EidoLED ECOdrive 30W, for 1-10 fixtures	SOLO50W-630 0-10V EidoLED SOLOdrive 50W, for 1-16 fixtures	SOLO100W-630 0-10VEidoLED SOLOdrive 100W, for 1-32 fixtures	E84936 Outer casing (required, order separately)
--	--	---	--

Ivil | Outer-casing



type	Ø in	h. in	suitable for	
PVC	2.7	5.5	Ivil (no driver)	E84936

Ivil | Outer-casing



type	Ø in	h. in	suitable for	
PVC	2.7	5.5	Ivil (no driver)	E84935