


Elin | Crystal spotlight | 5mmLED | Driver remote | 0.5W 24V



Chrome	E87337	3000 K	W	General	00
		3500 K	T		
		5000 K	C		
R - G - B - Y on request					

Power supply options (remote only)

OT96-D010

Osram, 10% 0-10V dim, 96W, 24V DC, 120-277VAC, supplied in a Dry location


OT96-JBX

Osram, Non-dim 24V DC, 120-277VAC, Wet location

659 Recessed casing
E84916 / E84335



Elin | Crystal spotlight | 5mmLED | Driver remote | 0.5W 24V



Chrome	E87340	RGB	Z	General	00
--------	---------------	-----	----------	---------	-----------

Power supply options (remote only)


EL96-DMX

LED Driver 96W, 24VDC, 120-277VAC, +EldoLED LINEARdrive LIN100D2 DMX/Sequencer Interface for RGB fixtures, remote mounted, supplied in a Dry Location Enclosure. DMX Control not included/order separately.

659 Recessed casing
E84916



Elin | Crystal spotlight | powerLED | Driver remote | 1W 350mA



Efficiency - CRI 80

Chrome	E91200	3000 K	107 lm	W	General	00
		3500 K	107 lm	T		
		4000 K	114 lm	N		
		5000 K	139 lm	C		

Power supply options (remote only)

ECO30W-350

0-10V EldoLED ECOdrive 30W for 1-10 fixtures

SOLO50W-350

0-10V EldoLED SOLOdrive 50W for 1-20 fixtures


SOLO100W-350

0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

659 Recessed casing
E84916 / E84335



Elin | Crystal spotlight | powerLED | Driver remote | 1.5W 500mA



Efficiency - CRI 80

Chrome	E87323	3000 K	143 lm	W	General	00
		3500 K	143 lm	T		
		4000 K	152 lm	N		
		5000 K	185 lm	C		

Power supply options (remote only)

ECO30W-500

0-10V EldoLED ECOdrive 30W for 1-10 fixtures

SOLO50W-500

0-10V EldoLED SOLOdrive 50W for 1-20 fixtures

SOLO100W-500

0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

659 Recessed casing
E84917

