



General: Elin is part of our Crystals collection. A series of small spot lights with crystal diffusers made in different shapes, some clear and some diffused but all of them with the goal to create a unique effect in the space.

Fixture Body: Brass (Chromium Plated).

Diffuser: Clear Glass.

Trim: Bezel.

Mounting: Semi-Recessed ceiling.

Dimensions/Weight: 0.8" @ 0.5W (0.03 lbs) - 0.8" @ 1W (0.11 lbs) - 0.8" @ 1.5W (0.15 lbs)

Driver: Remote. 24V Constant Voltage DC, 0-10V Dim or Non-Dim (0.5W variant) – Constant Current 120-277V Dimmable 0-10V or Non-Dim (1W & 1.5W variants).

Operation: Constant Current (CC) or Constant Voltage (CV).

CC features: Less susceptible to voltage drop (exceeding 32' distance); Allows for dimming down to 0.1%; Fixtures need to be wired in series.

CV features: Possibility to use higher wattage drivers and feed multiple fixtures with less drivers; fixtures need to be wired in parallel.

Wattages: 0.5W (CV) – 1W (CC) – 1.5W (CC)

Cable: Fixture comes with 0.39' of power cable.

IP rating: IP20. Fixture is protected against solid objects greater than 0.04". Not suitable for Outdoor applications or any contact with water.

ETL Certification: ETL, dry location

Optics: Fixed, General distribution.

Color temperatures: 2700K – 3000K – 4000K – 5000K.

CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



0.8" (0.5W CV)



0.8" (1W CC)



0.8" (1.5W CC)

Delivered Lumens ¹	0.8" [0.5 CV]	0.8" [1 CC]	0.8" [1.5 CC]
GE	96	107	143


¹Values shown for 3000K

Ordering Information								(Required)	
ELI	SFCH	D	O8			GE			
Product	Trim/Film	Type	Diameter	Wattage/Operation	Color Temp	Optic	+	Housing ²	Driver ²
ELI = Elin	SFCH = Semi-Flush Chrome	D = Diamond Shaped Crystal	O8 = 0.8"	0.5 CV = 0.5W / 24VDCConstant Voltage 1 CC = 1W / Constant Current (350mA) 1.5 CC = 1.5W / Constant Current (500mA)	27 = 2700K ¹ 30 = 3000K 40 = 4000K 50 = 5000K	GE = General distribution		0.5W/1W E84916 E84335 1.5W E84917	CV OT96-D010 OT96-JBX CC ECO30W-XXX SOLO50W-XXX SOLO100W-XXX

¹ N/A for CV

² See page 2

0.8" 0.5W CV



Housing

E84916

Recessed Housing



E84335

Recessed Housing



DRIVER OPTIONS (pick one)

C.V. Power supply options (remote only)


OT96-D010

Osram, 10% 0-10V dim,
96W, 24V DC, 120-277VAC,
supplied in a Dry location

OT96-JBX

Osram, Non-dim 24V DC,
120-277VAC, Wet location

0.8" 1W CC



Housing


E84916

Recessed Housing



E84335

Recessed Housing



DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)

ECO30W-500

0-10V EldoLED
ECOdrive 30W
for 1-10 fixtures


SOLO50W-500

0-10V EldoLED
SOLOdrive 50W
for 1-20 fixtures

SOLO100W-500

0-10V EldoLED
SOLOdrive 100W
for 1-40 fixtures


0.8" 1.5W CC



Housing

E84917

Recessed Housing



DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)

ECO30W-500

0-10V EldoLED
ECOdrive 30W
for 1-10 fixtures

SOLO50W-500

0-10V EldoLED
SOLOdrive 50W
for 1-20 fixtures

SOLO100W-500

0-10V EldoLED
SOLOdrive 100W
for 1-40 fixtures