

# envelope




A versatile and aesthetically minimal applique resembling a small envelope. Coming with single (fit for indoor installation), double or quadruple emission, Envelope allows to obtain light effects capable of lighting and furnishing all at once.

## **Materials**

Aluminum body

**Envelope\_1 | Path-marker | powerLED | Wet location | Driver remote | 1W 350mA**



Efficiency - CRI 80

White	<b>E96976</b>	2700 K	136 lm	<b>M</b>	Asymmetric	<b>07</b>
Grey	<b>E96978</b>	3000 K	145 lm	<b>W</b>		
DarkBrown	<b>E96979</b>	3500 K	145 lm	<b>T</b>		
		4000 K	155 lm	<b>N</b>		

**Power supply options (remote only)**

**ECO30W-350**

0-10V EldoLED ECOdrive 30W for 1-10 fixtures

**SOLO50W-350**

0-10V EldoLED SOLOdrive 50W for 1-20 fixtures


**SOLO100W-350**

0-10V EldoLED SOLOdrive 100W for 1-40 fixtures



659 Recessed casing  
**E84336 / E84915**

**Envelope\_2 | Path-marker | powerLED | Driver remote | 1W 350mA**



Efficiency - CRI 80

White	<b>E96971</b>	2700 K	136 lm	<b>M</b>	180°	<b>18</b>
Grey	<b>E96973</b>	3000 K	145 lm	<b>W</b>		
DarkBrown	<b>E96974</b>	3500 K	145 lm	<b>T</b>		
		4000 K	155 lm	<b>N</b>		

**Power supply options (remote only)**

**ECO30W-350**

0-10V EldoLED ECOdrive 30W for 1-10 fixtures

**SOLO50W-350**

0-10V EldoLED SOLOdrive 50W for 1-20 fixtures


**SOLO100W-350**

0-10V EldoLED SOLOdrive 100W for 1-40 fixtures



659 Recessed casing  
**E84336 / E84915**

**Envelope\_4 | Path-marker | powerLED | Driver remote | 1W 350mA**



Efficiency - CRI 80

White	<b>E96966</b>	2700 K	136 lm	<b>M</b>	180°	<b>18</b>
Grey	<b>E96968</b>	3000 K	145 lm	<b>W</b>		
DarkBrown	<b>E96969</b>	3500 K	145 lm	<b>T</b>		
		4000 K	155 lm	<b>N</b>		

**Power supply options (remote only)**

**ECO30W-350**

0-10V EldoLED ECOdrive 30W for 1-10 fixtures

**SOLO50W-350**

0-10V EldoLED SOLOdrive 50W for 1-20 fixtures

**SOLO100W-350**

0-10V EldoLED SOLOdrive 100W for 1-40 fixtures



659 Recessed casing  
**E84336 / E84915**