

Envelope IP66 Mini



General: With a simple, elegant, and minimalist design, Envelope is a family of round or square wall mounted step lights suitable for most projects (available for both indoor and outdoor applications). A recessed asymmetric optic that guarantees full cut-off while providing outstanding performances and a multitude of sizes and colors complete the range.

Fixture Body: Powder Coated Aluminum.

Diffuser: Silicone resin.

Mounting details: Wall mounted, semi-recessed. Black ABS housing available for both concrete and tile applications.

Dimensions/Weight: 1.6" (0.09 lbs)

Driver: Remote, 120-277V Dimmable 0-10V.

Wattage: 1W

Cable: Fixture comes with 3.28' of power cable.

IP rating: IP66 for protection against dust and powerful water jets from any angle.

IK rating: IK 10

ETL Certification: ETL, wet location

Optics: Fixed, Asymmetric.

Color temperatures: 2700K – 3000K – 3500K – 4000K.

CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



1.6" Round (1W)



1.6" Square (1W)


Delivered Lumens*	1.6"
AS	29

*Values shown for 3000K

Ordering Information							(Required) ¹		
Product	Trim	Type	Diameter	Wattage/Operation	Color Temp	Optic	+	Housing	Driver
EN66 = Envelope IP66	RWH = Round White RBL = Round Black RGR = Round Gray RDB = Round Dark Brown RBR = Round Brass RBG = Round Black Gray SWH = Square White SBL = Square Black SGR = Square Gray SDB = Square Dark Brown SBR = Square Brass SBG = Square Black Gray	ME = Mono Emission	16 = 1.6"	1 CC = 1W / Constant Current (350mA)	27 = 2700K 30 = 3000K 35 = 3500K 40 = 4000K	AS = Asymmetric	+	E84915 E84336	ECO30W-350 SOLO50W-350 SOLO100W-350

¹ See page 2

1.6" Round (1W)



Housing

E84915
Recessed Housing



E84336
Recessed Housing



DRIVER OPTIONS (pick one)


C.C. Power supply options (remote only)

ECO30W-350
0-10V EldoLED
ECOdrive 30W
for 1-10 fixtures

SOLO50W-350
0-10V EldoLED
SOLOdrive 50W
for 1-20 fixtures


SOLO100W-350
0-10V EldoLED
SOLOdrive 100W
for 1-40 fixtures

1.6" Square (1W)



Housing

E84915
Recessed Housing



E84336
Recessed Housing



DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)

ECO30W-350
0-10V EldoLED
ECOdrive 30W
for 1-10 fixtures

SOLO50W-350
0-10V EldoLED
SOLOdrive 50W
for 1-20 fixtures

SOLO100W-350
0-10V EldoLED
SOLOdrive 100W
for 1-40 fixtures