

Aspho

inter•lux



The recessed downlights synonymous with **effective, discreet and practical light**. Just the perfect product when distributed lighting is needed. Flange available in the square and round version.



Passive heat dissipation

Brass or steel casing

Light management

Eight optics available ensuring maximum design flexibility



Aspho_R | Decorative downlights | LED 0.5W 24V**type**

White	E88417
Chrome	E85001
Nickel	E85002

color



3000 K

optic**W**

30°

30**power supply options (remote only)****OT96-D010**

96W 24V 0-10V dim

**E84335**Concrete ceiling
outer casing
(optional)**Aspho_R** | Decorative downlights | powerLED 1W 350 mA**type**

White	CRI 80	E91340
Chrome	CRI 80	E85025
Nickel	CRI 80	E85026
Brass	CRI 80	E85027
Steel	CRI 80	E86875

color



3000 K 107 lm

W**optic**

70°

70

4000 K 114 lm

N**power supply options (remote only)****ECO30W-350**0-10V EldoLED
ECOdrive 30W,
for 1-10 fixtures**SOLO50W-350**0-10V EldoLED
SOLOdrive 50W,
for 1-20 fixtures**SOLO100W-350**0-10V EldoLED
SOLOdrive 100W,
for 1-40 fixtures**E84335**Concrete ceiling
outer casing
(optional)**Aspho_R** | Decorative downlights | powerLED 1W 350 mA**type**

White	CRI 80	E88418
Chrome	CRI 80	E85013
Nickel	CRI 80	E85014
Brass	CRI 80	E85015
Steel	CRI 80	E86873

color

3000 K 107 lm


W**optic**

120°

12

4000 K 114 lm

N**power supply options (remote only)****ECO30W-350**0-10V EldoLED
ECOdrive 30W,
for 1-10 fixtures**SOLO50W-350**0-10V EldoLED
SOLOdrive 50W,
for 1-20 fixtures**SOLO100W-350**0-10V EldoLED
SOLOdrive 100W,
for 1-40 fixtures**E84335**Concrete ceiling
outer casing
(optional)

Aspho_R | Decorative downlights | powerLED 1.5W 500 mA**type**

White	CRI 80	E91344
Chrome	CRI 80	E85959
Nickel	CRI 80	E85960
Brass	CRI 80	E85961
Steel	CRI 80	E86879

color


3000 K	143 lm	W
4000 K	152 lm	N

optic

70°	70
-----	-----------

power supply options (remote only)

ECO30W-500 0-10V EldoLED ECOdrive 30W, for 1-10 fixtures	SOLO50W-500 0-10V EldoLED SOLOdrive 50W, for 1-20 fixtures	SOLO100W-500 0-10V EldoLED SOLOdrive 100W, for 1-40 fixtures	E84917 Concrete ceiling outer casing (optional)
--	--	--	---

Aspho_R | Decorative downlights | powerLED 1.5W 500 mA**type**

White	CRI 80	E91346
Chrome	CRI 80	E85947
Nickel	CRI 80	E85948
Brass	CRI 80	E85949
Steel	CRI 80	E86877

color

3000 K	143 lm	W
4000 K	152 lm	N



optic

120°	12
------	-----------

power supply options (remote only)

ECO30W-500 0-10V EldoLED ECOdrive 30W, for 1-10 fixtures	SOLO50W-500 0-10V EldoLED SOLOdrive 50W, for 1-20 fixtures	SOLO100W-500 0-10V EldoLED SOLOdrive 100W, for 1-40 fixtures	E84917 Concrete ceiling outer casing (optional)
--	--	--	---

Aspho_Q | Decorative downlights | 0.2in LED 0.5W 24V



type

White	E91339
Chrome	E85004
Nickel	E85005

color

3000 K

optic

30° **30**

power supply options (remote only)

OT96-D010



96W 24V 0-10V dim



E84335

Concrete ceiling
outer casing
(optional)

Aspho_Q | Decorative downlights | powerLED 1W 350 mA



type

White	CRI 80	E91341
Chrome	CRI 80	E85028
Nickel	CRI 80	E85029

color

3000 K 107 lm

4000 K 114 lm

optic

70° **70****N**

power supply options (remote only)

ECO30W-350

0-10V EldoLED
ECOdrive 30W,
for 1-10 fixtures

SOLO50W-350

0-10V EldoLED
SOLOdrive 50W,
for 1-20 fixtures



SOLO100W-350

0-10V EldoLED
SOLOdrive 100W,
for 1-40 fixtures

E84335

Concrete ceiling
outer casing
(optional)

Aspho_Q | Decorative downlights | powerLED 1W 350 mA



type

White	CRI 80	E91343
Chrome	CRI 80	E85016
Nickel	CRI 80	E85017

color

3000 K 107 lm

4000 K 114 lm

optic

120° **12****N**

power supply options (remote only)

ECO30W-350

0-10V EldoLED
ECOdrive 30W,
for 1-10 fixtures

SOLO50W-350

0-10V EldoLED
SOLOdrive 50W,
for 1-20 fixtures



SOLO100W-350

0-10V EldoLED
SOLOdrive 100W,
for 1-40 fixtures

E84335

Concrete ceiling
outer casing
(optional)

Aspho_Q | Decorative downlights | powerLED 1.5W 500 mA



type

White	CRI 80	E91345
Chrome	CRI 80	E85962
Nickel	CRI 80	E85963

color

3000 K 143 lm

4000 K 152 lm

optic

70° **70****N**

power supply options (remote only)

ECO30W-500

0-10V EldoLED
ECOdrive 30W,
for 1-10 fixtures

SOLO50W-500

0-10V EldoLED
SOLOdrive 50W,
for 1-20 fixtures


SOLO100W-500

0-10V EldoLED
SOLOdrive 100W,
for 1-40 fixtures

E84917

Concrete ceiling
outer casing
(optional)

Aspho_Q | Decorative downlights | powerLED 1.5W 500 mA



type		color			optic	
White	CRI 80	E91347			3000 K	143 lm
Chrome	CRI 80	E85950			4000 K	152 lm
Nickel	CRI 80	E85951				

color		optic	
3000 K	143 lm	W	120°
4000 K	152 lm	N	12

power supply options (remote only)



ECO30W-500	SOLO50W-500	SOLO100W-500	E84917
0-10V EldoLED ECOdrive 30W, for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W, for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W, for 1-40 fixtures	Concrete ceiling outer casing (optional)

“Eos Hotel” - Lecce (Italy)

Aspho is synonymous with creative downlights solutions that successfully adapt to various environments: fun and elegant at the same time. Aspho_Q downlightss embellish the smart restaurant area of Lecce’s Eos Hotel, emphasising the refined wooden finishes of the bar counter.

