Crystals

inter•lux

linea light i-LED

The energy resulting from the combination of glass and light will amaze you over and over again. Fitted with a **prismatic ground transparent glass diffuser,** the family of recessed downlights Crystal embellish the spaces with a clear light.

Each piece is made unique by the artisan processing of glass: Therefore the effect achieved may be not perfectly homogeneous. Any small imperfections should be considered a product peculiarity.

Passive heat dissipation
Brass casing

Light management
Three shades of white and four colors for customizable lighting

Beriel | Crystal downlights | powerLED 1W 350 mA

C.C. IP20



type			color			optic	
Chrome	CRI 80	**E92285**	3000 K	107 lm	**W**	Diff.	**00**
			4000 K	114 lm	**N**		

power supply options (remote only)

ECO30W-350	SOLO50W-350	SOLO100W-350	E84335
0-10V EldoLED ECOdrive 30W, for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W, for 1-20 fixtures	0-10VEldoLED SOLOdrive 100W, for 1-40 fixtures	Concrete ceiling outer casing (optional)

Beriel | Crystal downlights | powerLED 1.5W 500 mA

C.C. IP20



type			color			optic	
White	CRI 80	**E92275**	3000 K	143 lm	**W**	Diff.	**00**
Chrome	CRI 80	**E87324**	4000 K	152 lm	**N**		

power supply options (remote only)

ECO30W-500	SOLO50W-500	SOLO100W-500	E84917
0-10V EldoLED ECOdrive 30W, for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W, for 1-20 fixtures	0-10VEldoLED SOLOdrive 100W, for 1-40 fixtures	Concrete ceiling outer casing (optional)

ALMAR
JESOLO

Elin | Crystal downlights | 0.2in LED 0.5W 24V

C.V. IP20



type			color		optic	
White		**E92631**	3000 K	**W**	Diff.	**00**
Chrome		**E87337**				

power supply options (remote only)

OT96-D010
96W 24V 0-10V dim

E84916
Concrete ceiling outer casing (optional)

E84335
Masonry outer casing (optional)

Elin | Crystal downlights | powerLED 1W 350 mA

C.C. IP20



type			color			optic	
White	CRI 80	**E91201**	3000 K	107 lm	**W**	Diff.	**00**
Chrome	CRI 80	**E91200**	4000 K	114 lm	**N**		

power supply options (remote only)

ECO30W-350
0-10V EldoLED ECOdrive 30W, for 1-10 fixtures

SOLO50W-350
0-10V EldoLED SOLOdrive 50W, for 1-20 fixtures

SOLO100W-350
0-10VEldoLED SOLOdrive 100W, for 1-40 fixtures

E84335
Masonry outer casing (optional)

Elin | Crystal downlights | powerLED 1.5W 500 mA

C.C. IP20



type			color			optic	
Chrome	CRI 80	**E87323**	3000 K	143 lm	**W**	Diff.	**00**
			4000 K	152 lm	**N**		

power supply options (remote only)

ECO30W-500
0-10V EldoLED ECOdrive 30W, for 1-10 fixtures

SOLO50W-500
0-10V EldoLED SOLOdrive 50W, for 1-20 fixtures

SOLO100W-500
0-10VEldoLED SOLOdrive 100W, for 1-40 fixtures

E84917
Concrete ceiling outer casing (optional)

Ture | Crystal downlights | powerLED 1.5W 500 mA

C.C. IP52



type			color			optic	
Chrome	CRI 80	**E87350**	3000 K	143 lm	**W**	Diff.	**00**
			4000 K	152 lm	**N**		

power supply options (remote only)

ECO30W-500	SOLO50W-500	SOLO100W-500	E84917
0-10V EldoLED ECOdrive 30W, for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W, for 1-20 fixtures	0-10VEldoLED SOLOdrive 100W, for 1-40 fixtures	oncrete ceiling outer casing (optional)

Ture | Crystal downlights | powerLED 1.5W 500 mA

C.C. IP52



type			color			optic	
Chrome	CRI 80	**E87353**	3000 K	199 lm	**W**	Diff.	**00**
			4000 K	213 lm	**N**		

power supply options (remote only)

ECO30W-500	SOLO50W-500	SOLO100W-500	E84954
0-10V EldoLED ECOdrive 30W, for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W, for 1-20 fixtures	0-10VEldoLED SOLOdrive 100W, for 1-40 fixtures	Concrete ceiling outer casing (optional)

Ture | Crystal downlights | powerLED 1.5W 500 mA

C.C. IP52



type			color			optic	
Chrome	CRI 80	**E87356**	3000 K	199 lm	**W**	Diff.	**00**
			4000 K	213 lm	**N**		

power supply options (remote only)

ECO30W-500	SOLO50W-500	SOLO100W-500	E84901
0-10V EldoLED ECOdrive 30W, for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W, for 1-20 fixtures	0-10VEldoLED SOLOdrive 100W, for 1-40 fixtures	Concrete ceiling outer casing (optional)

Gude | Crystal downlights | powerLED 1.5W 500 mA

C.C. IP54



type			color			optic	
Chrome	CRI 80	**E87330**	3000 K	143 lm	**W**	Diff.	**00**
			4000 K	152 lm	**N**		

power supply options (remote only)

ECO30W-500	SOLO50W-500	SOLO100W-500	E84917
0-10V EldoLED ECOdrive 30W, for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W, for 1-20 fixtures	0-10VEldoLED SOLOdrive 100W, for 1-40 fixtures	Outer casing (optional)

Gude | Crystal downlights | powerLED 1.5W 500 mA

C.C. IP54



type			color			optic	
Chrome	CRI 80	**E87332**	3000 K	199 lm	**W**	Diff.	**00**
			4000 K	213 lm	**N**		

power supply options (remote only)

ECO30W-500	SOLO50W-500	SOLO100W-500	E84954
0-10V EldoLED ECOdrive 30W, for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W, for 1-20 fixtures	0-10VEldoLED SOLOdrive 100W, for 1-40 fixtures	Concrete ceiling outer casing (optional)

Gude | Crystal downlights | powerLED 1.5W 500 mA

C.C. IP54



type			color			optic	
Chrome	CRI 80	**E87335**	3000 K	199 lm	**W**	Diff.	**00**
			4000 K	213 lm	**N**		

power supply options (remote only)

ECO30W-500	SOLO50W-500	SOLO100W-500	E84901
0-10V EldoLED ECOdrive 30W, for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W, for 1-20 fixtures	0-10VEldoLED SOLOdrive 100W, for 1-40 fixtures	Concrete ceiling outer casing (optional)