


Ture | Crystal spotlight | powerLED | Damp location | Driver remote | 1.5W 500mA



Efficiency - CRI 80

Chrome	E87350	3000 K	143 lm	W	General	00
		3500 K	143 lm	T		
		4000 K	152 lm	N		
		5000 K	185 lm	C		


Power supply options (remote only)

ECO30W-500	SOLO50W-500	SOLO100W-500
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures



▶ 659 Recessed casing
E84917

Ture | Crystal spotlight | powerLED | Damp location | Driver remote | 1.5W 500mA



Efficiency - CRI 80

Chrome	E87353	3000 K	199 lm	W	General	00
		3500 K	199 lm	T		
		4000 K	213 lm	N		
		5000 K	227 lm	C		


Power supply options (remote only)

ECO30W-500	SOLO50W-500	SOLO100W-500
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures



▶ 659 Recessed casing
E84954

Ture | Crystal spotlight | powerLED | Damp location | Driver remote | 1.5W 500mA



Efficiency - CRI 80

Chrome	E87356	3000 K	199 lm	W	General	00
		3500 K	199 lm	T		
		4000 K	213 lm	N		
		5000 K	227 lm	C		

Power supply options (remote only)

ECO30W-500	SOLO50W-500	SOLO100W-500
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures



▶ 659 Recessed casing
E84901

