



General: Ture is part of our Crystals collection. A series of small spot lights with crystal diffusers made in different shapes, some clear and some diffused but all of them with the goal to create a unique effect in the space.

Fixture Body: Brass (Chromium Plated).

Diffuser: Clear Glass.

Trim: Trimless.

Mounting: Semi-Recessed ceiling.

Dimensions/Weight: 0.8" (0.1 lbs) – 1.2" (0.11 lbs) – 1.6" (0.15 lbs)

Driver: Remote. Constant Current 120-277V, Dimmable 0-10V.

Operation: Constant Current (CC).

CC features: Less susceptible to voltage drop (exceeding 32' distance); Allows for dimming down to 0.1%; Fixtures need to be wired in series.

Wattages: 1.5W (applicable to all sizes).

Cable: Fixture comes with 0.39' of power cable.

IP rating: IP52. Protected against vertically falling drops of water.

ETL Certification: ETL, damp location

Optics: Fixed, General distribution.

Color temperatures: 2700K – 3000K – 4000K – 5000K.

CRI: 80+

Lumen Maintenance: L70 projections tested at Tj 65° C and Ta 25°.

Warranty: 5-year Limited Warranty on fixtures. 1-year Limited Warranty on Remote Drivers.



0.8" (1.5W)

1.2" (1.5W)



1.6" (1.5W)


Delivered Lumens*	0.8"	12"	16"
GE	143	199	199

*Values shown for 3000K

Ordering Information							(Required)	
TUR	TL	D		1.5 - CC		GE	+	
Product	Trim/Film	Type	Diameter	Wattage/Operation	Color Temp	Optic		Housing ¹
TUR = Ture	TL = Trimless	D = Diamond Shaped Crystal	08 = 0.8" 12 = 1.2" 16 = 1.6"	1.5 CC = 1.5W / Constant Current (500mA)	27 = 2700K 30 = 3000K 40 = 4000K 50 = 5000K	GE = General distribution		Drive ¹
								E84917 (08) E84954 (12) E84901 (16)
								ECO30W-500 SOLO50W-500 SOLO100W-500

¹ See page 2

0.8" 1W CC



Housing
E84917
Recessed Housing




DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)

ECO30W-500	SOLO50W-500	SOLO100W-500
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

1.2" 1W CC



Housing
E84954
Recessed Housing




DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)

ECO30W-500	SOLO50W-500	SOLO100W-500
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures

1.6" 1W CC



Housing
E84901
Recessed Housing



DRIVER OPTIONS (pick one)

C.C. Power supply options (remote only)

ECO30W-500	SOLO50W-500	SOLO100W-500
0-10V EldoLED ECOdrive 30W for 1-10 fixtures	0-10V EldoLED SOLOdrive 50W for 1-20 fixtures	0-10V EldoLED SOLOdrive 100W for 1-40 fixtures