


20 Linear Direct/Indirect Surface Wall Mount

WG-20LDI-...-M-...-OD-M-...-SD					
Delivered Lumens Per Foot					
		Power			
		L [3 W/ft]	M [6 W/ft]	H [10 W/ft]	RGBW [7.6 W/ft]
CCT	927	419	838	—	—
	930	456	911	—	—
	935	540	1082	—	—
	940	643	1285	—	—
	WD²	160	333	482	—
	RGBW³	—	—	—	272
UGR⁴		24.3	26.8	—	—



BEAM ANGLE (0-180) = 82.8
BEAM ANGLE (90-270) = 106.8


ILLUMINANCE - 48" OD SD M 3500		
WG-20LDI-...-S-48-M-935-...-OD-M-935-...-SD-W¹		
Mounting Height [ft]	Illuminance [fc at max cd]	Beam Width [ft]
2	259	3.5
4	65	7.1
6	29	10.6
8	16	14.1
10	10	17.6
12	7	21.2
14	5	24.7
16	4	28.2
18	3	31.7
20	3	35.3

Power Multiplier				
	L [3 W/ft]	M [6 W/ft]	H [10 W/ft]	RGBW [7.6 W/ft]
9XX/RGBW	0.5	1.00	—	—
WD	0.30	0.62	—	—

CCT Multiplier				
	927	930	935	940
	0.77	0.84	1.00	1.19

- 1 Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.
- 2 WD lumen data at maximum output (3000K).
- 3 RGBW lumen data at maximum output with 3000K White LED.
- 4 UGR value noted is the maximum UGR (crosswise) with 935 LEDs / 48" length.


WG-20LI-...-X-XXX-X-XX-...-OD-W					
Delivered Lumens Per Foot					
		Power			
		L [3 W/ft]	M [6 W/ft]	H [10 W/ft]	RGBW [7.6 W/ft]
CCT	927	176	352	617	—
	930	192	383	670	—
	935	227	455	796	—
	940	270	540	946	—
	WD²	135	280	405	—
	RGBW³	—	—	—	229
UGR⁴		—	—	—	—



BEAM ANGLE (0-180) = 110.1
BEAM ANGLE (90-270) = 110.1

ILLUMINANCE - 48" OD H 3500K		
WWG-20LI-...-S-48-X-XXX-X-XX-H-935-...-OD-W¹		
Offset Distance [ft]	Illuminance [fc at max cd]	Beam Width [ft]
2	277	5.7
4	69	11.4
6	31	17.2
8	17	22.9
10	11	28.6
12	8	34.3
14	6	40.1
16	4	45.8
18	3	51.5
20	3	57.2

WG-20LI-...-X-XXX-X-XX-...-SD-W					
Delivered Lumens Per Foot					
		Power			
		L [3 W/ft]	M [6 W/ft]	H [10 W/ft]	RGBW [7.6 W/ft]
CCT	927	248	495	867	—
	930	270	538	942	—
	935	319	640	1119	—
	940	380	760	1330	—
	WD²	190	394	569	—
	RGBW³	—	—	—	322
UGR⁴		—	—	—	—



BEAM ANGLE (0-180) = 80.2
BEAM ANGLE (90-270) = 100.7

ILLUMINANCE - 48" SD H 3500K		
WG-20LI-...-S-48-X-XXX-X-XX-H-935-...-SD-W¹		
Offset Distance [ft]	Illuminance [fc at max cd]	Beam Width [ft]
2	511	3.4
4	128	6.7
6	57	10.1
8	32	13.5
10	20	16.8
12	14	20.2
14	10	23.6
16	8	26.9
18	6	30.3
20	5	33.7

Power Multiplier				
	L [3 W/ft]	M [6 W/ft]	H [10 W/ft]	RGBW [7.6 W/ft]
9XX/RGBW	0.29	0.57	1.00	0.29
WD	0.17	0.35	0.51	—


CCT Multiplier				
	927	930	935	940
	0.77	0.84	1.00	1.19

- 1 Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.
- 2 WD lumen data at maximum output (3000K).
- 3 RGBW lumen data at maximum output with 3000K White LED.
- 4 UGR value noted is the maximum UGR (crosswise) with 935 LEDs / 48" length.

20 Linear Direct/Indirect Surface Wall Mount

WG-20LD-...-OD-X-XXX-X-XX-W Delivered Lumens Per Foot


		Power			
		L [3 W/ft]	M [6 W/ft]	H [10 W/ft]	RGBW [7.6 W/ft]
CCT	927	176	352	617	—
	930	192	383	670	—
	935	227	455	796	—
	940	270	540	946	—
	WD ²	135	280	405	—
	RGBW ³	—	—	—	229
UGR ⁴		26.7	29.3	31.1	—



BEAM ANGLE (0-180) = 110.3
BEAM ANGLE (90-270) = 110.4

WG-20LD-...-MPL-X-XXX-X-XX-W Delivered Lumens Per Foot


		Power			
		L [3 W/ft]	M [6 W/ft]	H [10 W/ft]	RGBW [7.6 W/ft]
CCT	927	209	418	731	—
	930	227	454	795	—
	935	270	540	944	—
	940	321	641	1122	—
	WD ²	160	332	480	—
	RGBW ³	—	—	—	272
UGR ⁴		26.3	28.9	30.7	—



BEAM ANGLE (0-180) = 85.5
BEAM ANGLE (90-270) = 73.8

WG-20LD-...-NL16-X-XXX-X-XX-W Delivered Lumens Per Foot

		Power			
		L [3 W/ft]	M [6 W/ft]	H [10 W/ft]	RGBW [7.6 W/ft]
CCT	927	207	414	725	—
	930	225	450	787	—
	935	267	535	936	—
	940	318	635	1112	—
	WD ²	158	329	476	—
	RGBW ³	—	—	—	269
UGR ⁴		17.8	20.3	22.1	—



BEAM ANGLE (0-180) = 10.4
BEAM ANGLE (90-270) = 75.1

inter•lux

ILLUMINANCE - 48" OD H 3500K

WG-20LD-...-S-48-H-935-...-OD-X-XXX-X-XX-W¹

Mounting Height [ft]	Illuminance [fc at max cd]	Beam Width [ft]
2	227	5.7
4	69	11.5
6	31	17.2
8	17	23
10	11	28.7
12	8	34.5
14	6	40.2
16	4	46
18	3	51.7
20	3	57.5

ILLUMINANCE - 48" MPL H 3500K

WG-20LD-...-S-48-H-935-...-MPL-X-XXX-X-XX-W¹

Mounting Height [ft]	Illuminance [fc at max cd]	Beam Width [ft]
2	478	3.7
4	119	7.4
6	53	11.1
8	30	14.8
10	19	18.5
12	13	22.2
14	10	25.9
16	7	29.6
18	6	33.3
20	5	37

ILLUMINANCE - 48" NL16 H 3500K

WG-20LD-...-S-48-H-935-...-NL16-X-XXX-X-XX-W¹

Mounting Height [ft]	Illuminance [fc at max cd]	Beam Width [ft]
2	2387	0.4
4	597	0.7
6	265	1.1
8	149	1.5
10	95	1.8
12	66	2.2
14	49	2.6
16	37	2.9
18	39	3.3
20	24	3.7

Power Multiplier				
	L [3 W/ft]	M [6 W/ft]	H [10 W/ft]	RGBW [7.6 W/ft]
9XX/RGBW	0.29	0.57	1.00	0.29
WD	0.17	0.35	0.51	—

CCT Multiplier				
	927	930	935	940
	0.77	0.84	1.00	1.19

- 1 Polar Plot and Cone of Light are applicable to part number noted; use Multiplication Factor table to approximate other models or refer to online photometry.
- 2 WD lumen data at maximum output (3000K).
- 3 RGBW lumen data at maximum output with 3000K White LED.
- 4 UGR value noted is the maximum UGR (crosswise) with 935 LEDs / 48" length.