


20 Linear Direct/Indirect


Surface Wall Mount



inter•lux



Lenses/Accessories



Ordering Information				Direct				Indirect					
Model	Fixation	Pattern	Length	Power ²	CRI/CCT ³	Driver ⁴	Lens	Power ²	CRI/CCT ³	Driver ⁴	Lens	Finish	Options
WG-20LDI direct/indirect	SW	S PI ¹ PO ¹	A A x B A x B x C A x B x A x B	L M H ²	927 930 935 940	X S D010 DPH	OD (std) MPL NL16 LL45B ⁵	L M H	927 930 935 940	X S D010 DPH	OD (std) SD	W (std) B S F	DC EM
WG-20LD direct					940	WD	L3DAE		940	WD	L3DAE		
WG-20LI indirect					RGBW	L3DOE EL96 DMX	LL45W ⁵ LL45S ⁵		RGBW	L3DOE EL96 DMX			

Luminaire

- Wall mounted fixture with minimal housing for continuous mounting to any desired length (1/4" increments).
- Multiple lenses and louvers for general, accent, decorative and grazing applications.
- Remote driver options (required). Field replaceable LED boards.
- Lengths and angles factory cut to exact field dimensions.
- 90+ CRI, 3 steps MacAdam.
- L70 (TM21 Projected 85C) Static White 60,000 hours, RGBW 50,000 hours, WD 36,000 hours.
- ETL and ETL-C for dry and damp location.

Fixation

- SW = Surface Wall Mount

Pattern

- S = Straight run
- PI = Standard patterns 2, 3 or 4 sided with 90° inside corners on the same plane¹
- PO = Standard patterns 2, 3 or 4 sided with 90° outside corners on the same plane¹

Length

- A, B, C = specify inches to the nearest 0.25" (i.e. 72.25") For patterns specify each length (i.e. 2 sided: A x B = 72.25" x 48"; 3 sided: A x B x C; 4 sided: A x B x A x B)

Power²

- L = 3W/ft low power (WD 2.7 W/ft) (24V)
- M = 6W/ft mid power (WD 5.5 W/ft) (24V) (RGBW - 7.6W/ft)
- H = 10W/ft high power (WD 8 W/ft) (24V) (LDI not to exceed 13 W/ft total)²

CRI/CCT (90+ CRI)³

- 927 = 2700K
- 930 = 3000K
- 935 = 3500K
- 940 = 4000K
- WD = Warm Dimming 1800 - 3000K
- RGBW = 3000K White (M power only)

Driver (Remote)⁴

- X = No driver, ordered separately
- S = Standard driver 120-277V
- D010 = Osram, 10%, 0-10V dimming, 120-277V
- DPH = Phase Dimming, 1% dimming, 120V only
- L3DAE = Lutron Hi-lume 1% EcoSystem, 120-277V
- L3DOE = Lutron Hi-lume Premier 0.1 EcoSystem, 120-277V
- EL96 = Osram / EldoLED, 24V, 0.1% 0-10V Dimming
- DMX = Osram / EldoLED, 24V, 0.1% DMX Dimming

Lens

- OD = Satin opal diffuser (standard)
- SD = Satin clear diffuser
- MPL = Micro-prismatic lens
- NL16 = Linear narrow lens, 16°
- LL45B = Linear louver black⁵
- LL45W = Linear louver white⁵
- LL45S = Linear louver satin⁵

Finish

- W = White, 15% gloss, RAL 9010 (standard)
- B = Black, 15% gloss, RAL 9005
- S = Silver, 15% gloss, RAL 9006
- F = Custom finished trim, specify RAL

Options

- DC = dual circuit
- EM = Emergency LED driver (remote only)

- 1 See pattern specs sheet.
- 2 Wattage is shown for LED boards only, system wattage varies depending on driver selected. Maximum combined wattage for Direct + Indirect shall not exceed 13 W/ft.
- 3 See photometric data sheet for delivered lumens.
- 4 Remote power supply required. See power supply page for details.
- 5 Straight runs only.

